



Bright up your space the smarter way

Essential SmartBright LowBay

Philips Essential SmartBright LowBay is a functional lighting by combining cost-efficiency with clean design. It offers customers all the benefits of LED lighting – reduced energy consumption, longer service time and less maintenance. Flexible, safe, and reliable, Essential SmartBright LowBay is a perfect LED replacement to conventional CFL LowBay system, allowing you to bright up your supermarkets, retail shops, and sports recreational spaces the smarter way.

Benefits

- Energy saving up to 55%
- 1 to 1 replacement to CFL45W, 65W and 85W
- Comfort light quality
- Safe & Reliable

Features

- High efficacy: 80 lumens per watt
- Lumen Output of 1600lm, 2400lm and 3200lm
- High quality optical plate ensure good uniformity
- 15,000hrs lifetime @Ta25°C in compliance with CB and EMC norms

Application

- General indoor low ceiling applications:
- Supermarket; Retail shops; Sports hall ; Warehouse etc.

Essential SmartBright LowBay


Versions



BY088P LED40



BY088P LED30



BY088P LED20

Product details



Essential SmartBright Lowbay
BY088P Side



Essential SmartBright Lowbay
BY088P Top

Essential SmartBright LowBay

Application conditions

Ambient temperature range	-20 to +40 °C
Suitable for random switching	No

Approval and application

Mech. impact protection code	IK03
Ingress protection code	IP20

Controls and dimming

Dimmable	No
----------	----

Operating and electrical

Input Voltage	220-240 V
---------------	-----------

General information

CE mark	-
Protection class IEC	Safety class I
Optical cover/lens type	Polycarbonate bowl/cover
Driver included	Yes
ENEC mark	-
Flammability mark	For mounting on normally flammable surfaces
Glow-wire test	Temperature 650 °C, duration 5 s
Light source replaceable	No
Number of gear units	1 unit
Optic type	Wide beam
Service tag	Yes

Initial performance (IEC compliant)

Initial chromaticity	SDCM<5
Init. Color Rendering Index	≥80
Initial LED luminaire efficacy	80 lm/W
Luminous flux tolerance	+/-10%

Mechanical and housing

Color	Gray and black
-------	----------------

Initial performance (IEC compliant)

Order Code	Full Product Name	Init. Corr. Color		
		Temperature	Initial luminous flux	Initial input power
911401667203	BY088P LED40/CW	6500 K	3200 lm	40 W
911401667303	BY088P LED40/NW	4000 K	3200 lm	40 W
911401667403	BY088P LED40/WW	3000 K	3200 lm	40 W
911401668303	BY088P LED40/CW OL	6500 K	3200 lm	40 W
911401668403	BY088P LED40/NW OL	4000 K	3200 lm	40 W
911401668503	BY088P LED40/WW OL	3000 K	3200 lm	40 W
911401667503	BY088P LED30/CW	6500 K	2400 lm	30 W
911401667603	BY088P LED30/NW	4000 K	2400 lm	30 W
911401667703	BY088P LED30/WW	3000 K	2400 lm	30 W
911401668603	BY088P LED30/CW OL	6500 K	2400 lm	30 W
911401668703	BY088P LED30/NW OL	4000 K	2400 lm	30 W
911401668803	BY088P LED30/WW OL	3000 K	2400 lm	30 W
911401667803	BY088P LED20/CW	6500 K	1600 lm	20 W
911401667903	BY088P LED20/NW	4000 K	1600 lm	20 W
911401668003	BY088P LED20/WW	3000 K	1600 lm	20 W
911401668903	BY088P LED20/CW OL	6500 K	1600 lm	20 W
911401669003	BY088P LED20/NW OL	4000 K	1600 lm	20 W
911401669103	BY088P LED20/WW OL	3000 K	1600 lm	20 W

