



FlexBlend heading the way to efficient and flexible furnished offices areas

FlexBlend, Surface Mounted

Philips FlexBlend is an attractive family of surface mounted and suspended luminaires, next to Flexblend recessed. The luminaire range is enabling building owners to advance their lighting operations, by offering office-compliant lighting with a return on investment of less than 3 to 4 years. FlexBlend provides the required flexibility through the adaptability in design. This gives the possibility to install the luminaires easily in the field, at any moment. Even when today's luminaire is suspended, tomorrow this can be adapted to a surface mounted installation at the venue. And the other way around. . The surface mounted and suspended luminaire range fit to many different office spaces like open plan office, corridors, reception or meeting rooms. FlexBlend is offered in both lines and as standalone, using the same lighting module. This gives the option to the users to use FlexBlend as standalone now, and tomorrow, as line. The controller is integrated in the luminaire. As technology is changing fast, the ideal lighting solution is also expected to be ready to incorporate innovations that can help optimize operations further. For this reason, FlexBlend holds all connectivity and future ready options available. As System Ready luminaire it can be paired with lighting management systems such as the Philips SpaceWise, and to software-based lighting systems as Interact Office wired (PoE) and Interact Office wireless and/or existing and upcoming sensor innovations. The luminaire range is therefore future ready and can be delivered without any system component, and in a next phase, in the field to be upgraded. An attractive opportunity for new installations and renovations.

FlexBlend, Surface Mounted

Benefits

- Return of investment less than 3 years
- A flexible office, with application flexibility to the choice of luminaires to fit many office areas
- Future ready: scalable and ready to be connected to controls and lighting systems

Features

- Fully office compliant (UGR <19, L65< 3000cd/sm) , light level according to office applications requirements
- Homogenous and uniform light effect
- Various mounting options, dimensional variety and local options
- Integrated sensors
- Ready to be connected to software based lighting systems such as Interact Office

Application

- Offices
- Education
- Healthcare

Warnings and Safety

- The product is IPX0 & as such is not protected against water ingress & as such we strongly recommend that The environment in which The luminaire is to be installed is suitably checked
- If The above advice is not taken and The luminaires are subject to water ingress, Philips / Signify cannot guarantee safe failure & product warranty will become void

Specifications

Ambient Temperature	+10 to +25 °C +10 to +40 °C
Driver	Power supply unit with DALI and SystemReady interface (Power supply unit with DALI and SystemReady interface) Power supply unit with DALI interface (Power supply unit with DALI interface)
Initial correlated color temperature	3000 K, 4000 K
Initial input power	19.5 W, 20.5 W, 21.5 W, 22 W, 24 W, 24.5 W, 25 W, 26.5 W, 27 W, 27.5 W, 28 W, 28.5 W, 31 W, 32 W, 32.5 W, 34 W, 35 W, 35.5 W, 36 W, 36.5 W, 38 W, 39 W, 43 W, 45 W, 48 W

Initial LED luminaire efficacy	92, 98.5, 100, 102, 103, 104, 105, 106, 107, 108, 116, 118, 121, 123, 125, 126, 127, 130, 131, 132, 133, 136, 137, 138, 140, 143 lm/W
Initial luminous flux	2600 lm, 2800 lm, 3500 lm, 3600 lm, 4000 lm, 4200 lm, 4500 lm, 5000 lm, 5200 lm
Input voltage	220 to 240 V
Material	Housing: steel
Warranty period	5 years

Versions

FLEXBLEND STAND-ALONE



FLEXBLEND STAND-ALONE



FlexBlend, Surface Mounted

Versions



FLEXBLEND STAND-ALONE



FLEXBLEND STAND-ALONE



FLEXBLEND STAND-ALONE



FLEXBLEND STAND-ALONE



FLEXBLEND STAND-ALONE



FLEXBLEND STAND-ALONE



FLEXBLEND STAND-ALONE



FLEXBLEND STAND-ALONE - 82°
x 85° -



FLEXBLEND STAND-ALONE -
Power supply unit with DALI and
SystemReady interface, InterAct
ready - Wide beam - 120°

FlexBlend, Surface Mounted

Product details

FlexBlend Surface Mounted
SM340C WH



FlexBlend Surface Mounted
SM340C WH



FlexBlend Suspended SP340P WH



FlexBlend Surface Mounted
SM340C brackets



FlexBlend Surface Mounted
SM340C SI



FlexBlend Surface Mounted
SM340C SI



FlexBlend Suspended SP340P SI



FlexBlend Surface Mounted
SM340C PCS BK



FlexBlend Surface Mounted
SM340C BK



FlexBlend, Surface Mounted

Product details



FlexBlend Surface Mounted
SM340C BK



FlexBlend Surface Mounted
SM340C BK



FlexBlend Surface Mounted
SM340C MLO BK



FlexBlend Surface Mounted
SM340C BK



FlexBlend Suspended SP340P BK



FlexBlend Surface Mounted
SM340C O BK



FlexBlend Suspended SP340P WH



FlexBlend Surface Mounted
SM340C WH

FlexBlend, Surface Mounted

Product details



FlexBlend Surface Mounted
SM340C MLO WH



FlexBlend Surface Mounted
SM340C O SI



FlexBlend Surface Mounted
SM340C



FlexBlend Surface Mounted
SM340C O SI



FlexBlend_Surface_Mounted-
Suspended_Emergency Lighting



FlexBlend_Surface_Mounted-
Suspended_Emergency Lighting



FlexBlend_Surface_Mounted-
Suspended_Emergency Lighting



FlexBlend_Surface_Mounted-
Suspended_Emergency Lighting

FlexBlend, Surface Mounted

Product details

FlexBlend_Surface_Mounted-
Suspended_Emergency Lighting



FlexBlend_Surface_Mounted-
Suspended_Emergency Lighting



FlexBlend_Surface_Mounted-
Suspended_Emergency Lighting



FlexBlend_Surface_Mounted-
Suspended_Emergency Lighting



FlexBlend_Surface_Mounted-
Suspended_Emergency Lighting



FlexBlend_Surface_Mounted-
SM340C-MLO-WH-SWZU-12DPP



Accessories

FLEXBLEND S&S ACCESSORIES

Ordercode 910925867343



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867344



FlexBlend, Surface Mounted

Accessories



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867345



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867346



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867347



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867348



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867352



FLEXBLEND S&S ACCESSORIES -
- V - - Hz - - - - - White

Ordercode 910925867353



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867437



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867438

FlexBlend, Surface Mounted

Accessories

FLEXBLEND S&S ACCESSORIES

Ordercode 910925867439



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867440,
910925867441



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867445



FlexBlend, Surface Mounted

Application conditions	
Maximum dim level	1%
Approval and application	
Mech. impact protection code	IK02
Ingress protection code	IP20
Operating and electrical	
Input Voltage	220 to 240 V
General information	
CE mark	CE mark
Protection class IEC	Safety class I
Driver included	Yes
Flammability mark	For mounting on normally flammable surfaces
Light source replaceable	No
Number of gear units	1 unit
Optic type	Wide beam
Initial performance (IEC compliant)	
Init. Color Rendering Index	>90
Luminous flux tolerance	+/-10%
Light technical	
Flickering	1
Stroboscopic effect	0.4

Application conditions

Order Code	Full Product Name	Ambient temperature range	Suitable for random switching
910925867099	SM340C 35S/940 PSD PCS L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867134	SM340C 36S/940 PSD PCS L120 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867135	SM340C 42S/940 PSD PCS L120 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867865	SM340C 28S/940 PSD PCS L120 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867868	SM340C 28S/930 PSD PCS L120 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867869	SM340C 36S/930 PSD PCS L120 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867878	SM340C 45S/940 PSD PCS L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867879	SM340C 52S/940 PSD PCS L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867882	SM340C 35S/930 PSD PCS L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867883	SM340C 45S/930 PSD PCS L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867902	SM341C 26S/940 PSD PCS L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867903	SM341C 35S/940 PSD PCS L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867101	SM340C 35S/940 PSD PCS L150 SI	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867873	SM340C 28S/940 PSD PCS L120 SI	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867874	SM340C 36S/940 PSD PCS L120 SI	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867887	SM340C 45S/940 PSD PCS L150 SI	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867888	SM340C 52S/940 PSD PCS L150 SI	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867906	SM341C 26S/940 PSD PCS L150 SI	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867907	SM341C 35S/940 PSD PCS L150 SI	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867102	SM340C 35S/940 PSD PCS L150 BK	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867108	SM340C 35S/940 PSD MLO L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867136	SM340C 36S/940 PSD MLO L120 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867137	SM340C 40S/940 PSD MLO L120 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867262	SM341C 35S/940 PSD MLO L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867866	SM340C 28S/940 PSD MLO L120 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)

Order Code	Full Product Name	Ambient temperature range	Suitable for random switching
910925867870	SM340C 28S/930 PSD MLO L120 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867871	SM340C 36S/930 PSD MLO L120 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867880	SM340C 45S/940 PSD MLO L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867881	SM340C 50S/940 PSD MLO L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867884	SM340C 35S/930 PSD MLO L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867885	SM340C 45S/930 PSD MLO L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867904	SM341C 26S/940 PSD MLO L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867109	SM340C 35S/940 PSD MLO L150 SI	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867875	SM340C 28S/940 PSD MLO L120 SI	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867876	SM340C 36S/940 PSD MLO L120 SI	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867889	SM340C 45S/940 PSD MLO L150 SI	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867890	SM340C 50S/940 PSD MLO L150 SI	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867908	SM341C 26S/940 PSD MLO L150 SI	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867909	SM341C 35S/940 PSD MLO L150 SI	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867110	SM340C 35S/940 PSD MLO L150 BK	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867116	SM340C 35S/940 PSD O L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867867	SM340C 36S/940 PSD O L120 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867872	SM340C 36S/930 PSD O L120 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867886	SM340C 35S/930 PSD O L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867905	SM341C 26S/940 PSD O L150 WH	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867877	SM340C 36S/940 PSD O L120 SI	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867891	SM340C 35S/940 PSD O L150 SI	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925867892	SM340C 35S/940 PSD O L150 BK	+10 to +40 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925868098	SM340C 36S/940 PSD MLO ELP3 L120 WH	+10 to +25 °C	Yes (relates to presence/ movement detection and daylight harvesting)
910925868898	SM340C 45S/940 SRD MLO U4 L150 WH	+10 to +40 °C	No

FlexBlend, Surface Mounted

Order Code	Full Product Name	Ambient temperature	Suitable for random switching
		range	
910925868899	SM340C 52S/940 SRD PCS U4 L150 WH	+10 to +40 °C	No
910925868901	SM340C 45S/940 SRD PCS U4 L150 WH	+10 to +40 °C	No
910925868902	SM340C 35S/940 SRD PCS U4 L150 WH	+10 to +40 °C	No
910925868903	SM340C 42S/940 SRD PCS U4 L120 WH	+10 to +40 °C	No
910925868904	SM340C 36S/940 SRD PCS U4 L120 WH	+10 to +40 °C	No

Controls and dimming

Order Code	Full Product Name	Dimmable	Order Code	Full Product Name	Dimmable
910925867099	SM340C 35S/940 PSD PCS L150 WH	Yes	910925867881	SM340C 50S/940 PSD MLO L150 WH	Yes
910925867134	SM340C 36S/940 PSD PCS L120 WH	Yes	910925867884	SM340C 35S/930 PSD MLO L150 WH	Yes
910925867135	SM340C 42S/940 PSD PCS L120 WH	Yes	910925867885	SM340C 45S/930 PSD MLO L150 WH	Yes
910925867865	SM340C 28S/940 PSD PCS L120 WH	Yes	910925867904	SM341C 26S/940 PSD MLO L150 WH	Yes
910925867868	SM340C 28S/930 PSD PCS L120 WH	Yes	910925867109	SM340C 35S/940 PSD MLO L150 SI	Yes
910925867869	SM340C 36S/930 PSD PCS L120 WH	Yes	910925867875	SM340C 28S/940 PSD MLO L120 SI	Yes
910925867878	SM340C 45S/940 PSD PCS L150 WH	Yes	910925867876	SM340C 36S/940 PSD MLO L120 SI	Yes
910925867879	SM340C 52S/940 PSD PCS L150 WH	Yes	910925867889	SM340C 45S/940 PSD MLO L150 SI	Yes
910925867882	SM340C 35S/930 PSD PCS L150 WH	Yes	910925867890	SM340C 50S/940 PSD MLO L150 SI	Yes
910925867883	SM340C 45S/930 PSD PCS L150 WH	Yes	910925867908	SM341C 26S/940 PSD MLO L150 SI	Yes
910925867902	SM341C 26S/940 PSD PCS L150 WH	Yes	910925867909	SM341C 35S/940 PSD MLO L150 SI	Yes
910925867903	SM341C 35S/940 PSD PCS L150 WH	Yes	910925867110	SM340C 35S/940 PSD MLO L150 BK	Yes
910925867101	SM340C 35S/940 PSD PCS L150 SI	Yes	910925867116	SM340C 35S/940 PSD O L150 WH	Yes
910925867873	SM340C 28S/940 PSD PCS L120 SI	Yes	910925867867	SM340C 36S/940 PSD O L120 WH	Yes
910925867874	SM340C 36S/940 PSD PCS L120 SI	Yes	910925867872	SM340C 36S/930 PSD O L120 WH	Yes
910925867887	SM340C 45S/940 PSD PCS L150 SI	Yes	910925867886	SM340C 35S/930 PSD O L150 WH	Yes
910925867888	SM340C 52S/940 PSD PCS L150 SI	Yes	910925867905	SM341C 26S/940 PSD O L150 WH	Yes
910925867906	SM341C 26S/940 PSD PCS L150 SI	Yes	910925867877	SM340C 36S/940 PSD O L120 SI	Yes
910925867907	SM341C 35S/940 PSD PCS L150 SI	Yes	910925867891	SM340C 35S/940 PSD O L150 SI	Yes
910925867102	SM340C 35S/940 PSD PCS L150 BK	Yes	910925867892	SM340C 35S/940 PSD O L150 BK	Yes
910925867108	SM340C 35S/940 PSD MLO L150 WH	Yes	910925868098	SM340C 36S/940 PSD MLO ELP3 L120 WH	Yes
910925867136	SM340C 36S/940 PSD MLO L120 WH	Yes	910925868898	SM340C 45S/940 SRD MLO U4 L150 WH	Wireless Dim
910925867137	SM340C 40S/940 PSD MLO L120 WH	Yes	910925868899	SM340C 52S/940 SRD PCS U4 L150 WH	Wireless Dim
910925867262	SM341C 35S/940 PSD MLO L150 WH	Yes	910925868901	SM340C 45S/940 SRD PCS U4 L150 WH	Wireless Dim
910925867866	SM340C 28S/940 PSD MLO L120 WH	Yes	910925868902	SM340C 35S/940 SRD PCS U4 L150 WH	Wireless Dim
910925867870	SM340C 28S/930 PSD MLO L120 WH	Yes	910925868903	SM340C 42S/940 SRD PCS U4 L120 WH	Wireless Dim
910925867871	SM340C 36S/930 PSD MLO L120 WH	Yes	910925868904	SM340C 36S/940 SRD PCS U4 L120 WH	Wireless Dim
910925867880	SM340C 45S/940 PSD MLO L150 WH	Yes			

General information (1/2)

FlexBlend, Surface Mounted

Order Code	Full Product Name	Beam angle of light		Glow-wire test	Product Family Code	Order Code	Full Product Name	Beam angle of light		Glow-wire test	Product Family Code
		source	ENEC mark					source	ENEC mark		
910925867099	SM340C 35S/940 PSD PCS L150 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C	910925867888	SM340C 52S/940 PSD PCS L150 SI	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C
910925867134	SM340C 36S/940 PSD PCS L120 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C	910925867906	SM341C 26S/940 PSD PCS L150 SI	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM341C
910925867135	SM340C 42S/940 PSD PCS L120 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C	910925867907	SM341C 35S/940 PSD PCS L150 SI	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM341C
910925867865	SM340C 28S/940 PSD PCS L120 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C	910925867102	SM340C 35S/940 PSD PCS L150 BK	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C
910925867868	SM340C 28S/930 PSD PCS L120 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C	910925867108	SM340C 35S/940 PSD MLO L150 WH	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925867869	SM340C 36S/930 PSD PCS L120 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C	910925867136	SM340C 36S/940 PSD MLO L120 WH	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925867878	SM340C 45S/940 PSD PCS L150 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C	910925867137	SM340C 40S/940 PSD MLO L120 WH	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925867879	SM340C 52S/940 PSD PCS L150 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C	910925867262	SM341C 35S/940 PSD MLO L150 WH	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM341C
910925867882	SM340C 35S/930 PSD PCS L150 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C	910925867866	SM340C 28S/940 PSD MLO L120 WH	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925867883	SM340C 45S/930 PSD PCS L150 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C	910925867870	SM340C 28S/930 PSD MLO L120 WH	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925867902	SM341C 26S/940 PSD PCS L150 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM341C	910925867871	SM340C 36S/930 PSD MLO L120 WH	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925867903	SM341C 35S/940 PSD PCS L150 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM341C	910925867880	SM340C 45S/940 PSD MLO L150 WH	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925867101	SM340C 35S/940 PSD PCS L150 SI	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C	910925867881	SM340C 50S/940 PSD MLO L150 WH	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925867873	SM340C 28S/940 PSD PCS L120 SI	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C	910925867884	SM340C 35S/930 PSD MLO L150 WH	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925867874	SM340C 36S/940 PSD PCS L120 SI	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C	910925867885	SM340C 45S/930 PSD MLO L150 WH	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925867887	SM340C 45S/940 PSD PCS L150 SI	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C	910925867904	SM341C 26S/940 PSD MLO L150 WH	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM341C

FlexBlend, Surface Mounted

Order Code	Full Product Name	Beam angle of light		Glow-wire test	Product Family Code
		source	ENEC mark		
910925867109	SM340C 35S/940 PSD MLO L150 SI	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925867875	SM340C 28S/940 PSD MLO L120 SI	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925867876	SM340C 36S/940 PSD MLO L120 SI	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925867889	SM340C 45S/940 PSD MLO L150 SI	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925867890	SM340C 50S/940 PSD MLO L150 SI	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925867908	SM341C 26S/940 PSD MLO L150 SI	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM341C
910925867909	SM341C 35S/940 PSD MLO L150 SI	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM341C
910925867110	SM340C 35S/940 PSD MLO L150 BK	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925867116	SM340C 35S/940 PSD O L150 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C
910925867867	SM340C 36S/940 PSD O L120 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C
910925867872	SM340C 36S/930 PSD O L120 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C
910925867886	SM340C 35S/930 PSD O L150 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C

Order Code	Full Product Name	Beam angle of light		Glow-wire test	Product Family Code
		source	ENEC mark		
910925867905	SM341C 26S/940 PSD O L150 WH	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM341C
910925867877	SM340C 36S/940 PSD O L120 SI	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C
910925867891	SM340C 35S/940 PSD O L150 SI	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C
910925867892	SM340C 35S/940 PSD O L150 BK	120 °	ENEC plus mark	Temperature 850 °C, duration 30 s	SM340C
910925868098	SM340C 36S/940 PSD MLO ELP3 L120 WH	120 °	ENEC plus mark	Temperature 650 °C, duration 30 s	SM340C
910925868898	SM340C 45S/940 SRD MLO U4 L150 WH	- °	ENEC mark	Temperature 650 °C, duration 30 s	SM340C
910925868899	SM340C 52S/940 SRD PCS U4 L150 WH	- °	ENEC mark	Temperature 850 °C, duration 30 s	SM340C
910925868901	SM340C 45S/940 SRD PCS U4 L150 WH	- °	ENEC mark	Temperature 850 °C, duration 30 s	SM340C
910925868902	SM340C 35S/940 SRD PCS U4 L150 WH	- °	ENEC mark	Temperature 850 °C, duration 30 s	SM340C
910925868903	SM340C 42S/940 SRD PCS U4 L120 WH	- °	ENEC mark	Temperature 850 °C, duration 30 s	SM340C
910925868904	SM340C 36S/940 SRD PCS U4 L120 WH	- °	ENEC mark	Temperature 850 °C, duration 30 s	SM340C

General information (2/2)

Order Code	Full Product Name	Service tag
910925867099	SM340C 35S/940 PSD PCS L150 WH	Yes
910925867134	SM340C 36S/940 PSD PCS L120 WH	Yes
910925867135	SM340C 42S/940 PSD PCS L120 WH	Yes
910925867865	SM340C 28S/940 PSD PCS L120 WH	Yes
910925867868	SM340C 28S/930 PSD PCS L120 WH	Yes
910925867869	SM340C 36S/930 PSD PCS L120 WH	Yes
910925867878	SM340C 45S/940 PSD PCS L150 WH	Yes
910925867879	SM340C 52S/940 PSD PCS L150 WH	Yes
910925867882	SM340C 35S/930 PSD PCS L150 WH	Yes

Order Code	Full Product Name	Service tag
910925867883	SM340C 45S/930 PSD PCS L150 WH	Yes
910925867902	SM341C 26S/940 PSD PCS L150 WH	Yes
910925867903	SM341C 35S/940 PSD PCS L150 WH	Yes
910925867101	SM340C 35S/940 PSD PCS L150 SI	Yes
910925867873	SM340C 28S/940 PSD PCS L120 SI	Yes
910925867874	SM340C 36S/940 PSD PCS L120 SI	Yes
910925867887	SM340C 45S/940 PSD PCS L150 SI	Yes
910925867888	SM340C 52S/940 PSD PCS L150 SI	Yes
910925867906	SM341C 26S/940 PSD PCS L150 SI	Yes

FlexBlend, Surface Mounted

Order Code	Full Product Name	Service tag
910925867907	SM341C 35S/940 PSD PCS L150 SI	Yes
910925867102	SM340C 35S/940 PSD PCS L150 BK	Yes
910925867108	SM340C 35S/940 PSD MLO L150 WH	Yes
910925867136	SM340C 36S/940 PSD MLO L120 WH	Yes
910925867137	SM340C 40S/940 PSD MLO L120 WH	Yes
910925867262	SM341C 35S/940 PSD MLO L150 WH	Yes
910925867866	SM340C 28S/940 PSD MLO L120 WH	Yes
910925867870	SM340C 28S/930 PSD MLO L120 WH	Yes
910925867871	SM340C 36S/930 PSD MLO L120 WH	Yes
910925867880	SM340C 45S/940 PSD MLO L150 WH	Yes
910925867881	SM340C 50S/940 PSD MLO L150 WH	Yes
910925867884	SM340C 35S/930 PSD MLO L150 WH	Yes
910925867885	SM340C 45S/930 PSD MLO L150 WH	Yes
910925867904	SM341C 26S/940 PSD MLO L150 WH	Yes
910925867109	SM340C 35S/940 PSD MLO L150 SI	Yes
910925867875	SM340C 28S/940 PSD MLO L120 SI	Yes
910925867876	SM340C 36S/940 PSD MLO L120 SI	Yes
910925867889	SM340C 45S/940 PSD MLO L150 SI	Yes
910925867890	SM340C 50S/940 PSD MLO L150 SI	Yes

Order Code	Full Product Name	Service tag
910925867908	SM341C 26S/940 PSD MLO L150 SI	Yes
910925867909	SM341C 35S/940 PSD MLO L150 SI	Yes
910925867110	SM340C 35S/940 PSD MLO L150 BK	Yes
910925867116	SM340C 35S/940 PSD O L150 WH	Yes
910925867867	SM340C 36S/940 PSD O L120 WH	Yes
910925867872	SM340C 36S/930 PSD O L120 WH	Yes
910925867886	SM340C 35S/930 PSD O L150 WH	Yes
910925867905	SM341C 26S/940 PSD O L150 WH	Yes
910925867877	SM340C 36S/940 PSD O L120 SI	Yes
910925867891	SM340C 35S/940 PSD O L150 SI	Yes
910925867892	SM340C 35S/940 PSD O L150 BK	Yes
910925868098	SM340C 36S/940 PSD MLO ELP3 L120 WH	Yes
910925868898	SM340C 45S/940 SRD MLO U4 L150 WH	-
910925868899	SM340C 52S/940 SRD PCS U4 L150 WH	-
910925868901	SM340C 45S/940 SRD PCS U4 L150 WH	-
910925868902	SM340C 35S/940 SRD PCS U4 L150 WH	-
910925868903	SM340C 42S/940 SRD PCS U4 L120 WH	-
910925868904	SM340C 36S/940 SRD PCS U4 L120 WH	-

Initial performance (IEC compliant) (1/2)

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux
910925867099	SM340C 35S/940 PSD PCS L150 WH	(0.43, 0.40)	4000 K	140 lm/W	3500 lm
910925867134	SM340C 36S/940 PSD PCS L120 WH	(0.43, 0.40)	4000 K	136 lm/W	3600 lm
910925867135	SM340C 42S/940 PSD PCS L120 WH	(0.43, 0.40)	4000 K	131 lm/W	4200 lm
910925867865	SM340C 28S/940 PSD PCS L120 WH	(0.43, 0.40)	4000 K	137 lm/W	2800 lm
910925867868	SM340C 28S/930 PSD PCS L120 WH	(0.43, 0.40)	3000 K	127 lm/W	2800 lm
910925867869	SM340C 36S/930 PSD PCS L120 WH	(0.43, 0.40)	3000 K	131 lm/W	3600 lm
910925867878	SM340C 45S/940 PSD PCS L150 WH	(0.43, 0.40)	4000 K	138 lm/W	4500 lm
910925867879	SM340C 52S/940 PSD PCS L150 WH	(0.43, 0.40)	4000 K	133 lm/W	5200 lm
910925867882	SM340C 35S/930 PSD PCS L150 WH	(0.43, 0.40)	3000 K	130 lm/W	3500 lm

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux
910925867883	SM340C 45S/930 PSD PCS L150 WH	(0.43, 0.40)	3000 K	132 lm/W	4500 lm
910925867902	SM341C 26S/940 PSD PCS L150 WH	(0.43, 0.40)	4000 K	133 lm/W	2600 lm
910925867903	SM341C 35S/940 PSD PCS L150 WH	(0.43, 0.40)	4000 K	140 lm/W	3500 lm
910925867101	SM340C 35S/940 PSD PCS L150 SI	(0.43, 0.40)	4000 K	140 lm/W	3500 lm
910925867873	SM340C 28S/940 PSD PCS L120 SI	(0.43, 0.40)	4000 K	137 lm/W	2800 lm
910925867874	SM340C 36S/940 PSD PCS L120 SI	(0.43, 0.40)	4000 K	136 lm/W	3600 lm
910925867887	SM340C 45S/940 PSD PCS L150 SI	(0.43, 0.40)	4000 K	138 lm/W	4500 lm
910925867888	SM340C 52S/940 PSD PCS L150 SI	(0.43, 0.40)	4000 K	133 lm/W	5200 lm
910925867906	SM341C 26S/940 PSD PCS L150 SI	(0.43, 0.40)	4000 K	133 lm/W	2600 lm

FlexBlend, Surface Mounted

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux
910925867907	SM341C 35S/940 PSD PCS L150 SI	(0.43, 0.40)	4000 K	140 lm/W	3500 lm
910925867102	SM340C 35S/940 PSD PCS L150 BK	(0.43, 0.40)	4000 K	140 lm/W	3500 lm
910925867108	SM340C 35S/940 PSD MLO L150 WH	(0.43, 0.40)	4000 K	108 lm/W	3500 lm
910925867136	SM340C 36S/940 PSD MLO L120 WH	(0.43, 0.40)	4000 K	103 lm/W	3600 lm
910925867137	SM340C 40S/940 PSD MLO L120 WH	(0.43, 0.40)	4000 K	103 lm/W	4000 lm
910925867262	SM341C 35S/940 PSD MLO L150 WH	(0.43, 0.40)	4000 K	108 lm/W	3500 lm
910925867866	SM340C 28S/940 PSD MLO L120 WH	(0.43, 0.40)	4000 K	106 lm/W	2800 lm
910925867870	SM340C 28S/930 PSD MLO L120 WH	(0.43, 0.40)	3000 K	102 lm/W	2800 lm
910925867871	SM340C 36S/930 PSD MLO L120 WH	(0.43, 0.40)	3000 K	98.5 lm/W	3600 lm
910925867880	SM340C 45S/940 PSD MLO L150 WH	(0.43, 0.40)	4000 K	105 lm/W	4500 lm
910925867881	SM340C 50S/940 PSD MLO L150 WH	(0.43, 0.40)	4000 K	104 lm/W	5000 lm
910925867884	SM340C 35S/930 PSD MLO L150 WH	(0.43, 0.40)	3000 K	103 lm/W	3500 lm
910925867885	SM340C 45S/930 PSD MLO L150 WH	(0.43, 0.40)	3000 K	100 lm/W	4500 lm

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux
910925867904	SM341C 26S/940 PSD MLO L150 WH	(0.43, 0.40)	4000 K	107 lm/W	2600 lm
910925867109	SM340C 35S/940 PSD MLO L150 SI	(0.43, 0.40)	4000 K	108 lm/W	3500 lm
910925867875	SM340C 28S/940 PSD MLO L120 SI	(0.43, 0.40)	4000 K	106 lm/W	2800 lm
910925867876	SM340C 36S/940 PSD MLO L120 SI	(0.43, 0.40)	4000 K	103 lm/W	3600 lm
910925867889	SM340C 45S/940 PSD MLO L150 SI	(0.43, 0.40)	4000 K	105 lm/W	4500 lm
910925867890	SM340C 50S/940 PSD MLO L150 SI	(0.43, 0.40)	4000 K	104 lm/W	5000 lm
910925867908	SM341C 26S/940 PSD MLO L150 SI	(0.43, 0.40)	4000 K	107 lm/W	2600 lm
910925867909	SM341C 35S/940 PSD MLO L150 SI	(0.43, 0.40)	4000 K	108 lm/W	3500 lm
910925867110	SM340C 35S/940 PSD MLO L150 BK	(0.43, 0.40)	4000 K	108 lm/W	3500 lm
910925867116	SM340C 35S/940 PSD O L150 WH	(0.43, 0.40)	4000 K	125 lm/W	3500 lm
910925867867	SM340C 36S/940 PSD O L120 WH	(0.43, 0.40)	4000 K	126 lm/W	3600 lm
910925867872	SM340C 36S/930 PSD O L120 WH	(0.43, 0.40)	3000 K	116 lm/W	3600 lm
910925867886	SM340C 35S/930 PSD O L150 WH	(0.43, 0.40)	3000 K	123 lm/W	3500 lm
910925867905	SM341C 26S/940 PSD O L150 WH	(0.43, 0.40)	4000 K	121 lm/W	2600 lm
910925867877	SM340C 36S/940 PSD O L120 SI	(0.43, 0.40)	4000 K	126 lm/W	3600 lm
910925867891	SM340C 35S/940 PSD O L150 SI	(0.43, 0.40)	4000 K	125 lm/W	3500 lm

FlexBlend, Surface Mounted

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux
910925867892	SM340C 35S/940 PSD O L150 BK	(0.43, 0.40)	4000 K	125 lm/W	3500 lm
910925868098	SM340C 36S/940 PSD MLO ELP3 L120 WH	(0.38, 0.37)	4000 K	92 lm/W	3600 lm
910925868898	SM340C 45S/940 SRD MLO U4 L150 WH	0.38,0.37	4000 K	118 lm/W	4500 lm
910925868899	SM340C 52S/940 SRD PCS U4 L150 WH	0.38,0.37	4000 K	121 lm/W	5200 lm
910925868901	SM340C 45S/940 SRD	0.38,0.37	4000 K	125 lm/W	4500 lm

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux
	PCS U4 L150 WH				
910925868902	SM340C 35S/940 SRD PCS U4 L150 WH	0.38,0.37	4000 K	143 lm/W	3500 lm
910925868903	SM340C 42S/940 SRD PCS U4 L120 WH	0.38,0.37	4000 K	118 lm/W	4200 lm
910925868904	SM340C 36S/940 SRD PCS U4 L120 WH	0.38,0.37	4000 K	116 lm/W	3600 lm

Initial performance (IEC compliant) (2/2)

Order Code	Full Product Name	Initial input power
910925867099	SM340C 35S/940 PSD PCS L150 WH	25 W
910925867134	SM340C 36S/940 PSD PCS L120 WH	26.5 W
910925867135	SM340C 42S/940 PSD PCS L120 WH	32 W
910925867865	SM340C 28S/940 PSD PCS L120 WH	20.5 W
910925867868	SM340C 28S/930 PSD PCS L120 WH	22 W
910925867869	SM340C 36S/930 PSD PCS L120 WH	27.5 W
910925867878	SM340C 45S/940 PSD PCS L150 WH	32.5 W
910925867879	SM340C 52S/940 PSD PCS L150 WH	39 W
910925867882	SM340C 35S/930 PSD PCS L150 WH	27 W
910925867883	SM340C 45S/930 PSD PCS L150 WH	34 W
910925867902	SM341C 26S/940 PSD PCS L150 WH	19.5 W
910925867903	SM341C 35S/940 PSD PCS L150 WH	25 W
910925867101	SM340C 35S/940 PSD PCS L150 SI	25 W
910925867873	SM340C 28S/940 PSD PCS L120 SI	20.5 W
910925867874	SM340C 36S/940 PSD PCS L120 SI	26.5 W
910925867887	SM340C 45S/940 PSD PCS L150 SI	32.5 W
910925867888	SM340C 52S/940 PSD PCS L150 SI	39 W
910925867906	SM341C 26S/940 PSD PCS L150 SI	19.5 W
910925867907	SM341C 35S/940 PSD PCS L150 SI	25 W
910925867102	SM340C 35S/940 PSD PCS L150 BK	25 W
910925867108	SM340C 35S/940 PSD MLO L150 WH	32.5 W
910925867136	SM340C 36S/940 PSD MLO L120 WH	35 W
910925867137	SM340C 40S/940 PSD MLO L120 WH	39 W
910925867262	SM341C 35S/940 PSD MLO L150 WH	32.5 W
910925867866	SM340C 28S/940 PSD MLO L120 WH	26.5 W
910925867870	SM340C 28S/930 PSD MLO L120 WH	27.5 W
910925867871	SM340C 36S/930 PSD MLO L120 WH	36.5 W
910925867880	SM340C 45S/940 PSD MLO L150 WH	43 W

Order Code	Full Product Name	Initial input power
910925867881	SM340C 50S/940 PSD MLO L150 WH	48 W
910925867884	SM340C 35S/930 PSD MLO L150 WH	34 W
910925867885	SM340C 45S/930 PSD MLO L150 WH	45 W
910925867904	SM341C 26S/940 PSD MLO L150 WH	24 W
910925867109	SM340C 35S/940 PSD MLO L150 SI	32.5 W
910925867875	SM340C 28S/940 PSD MLO L120 SI	26.5 W
910925867876	SM340C 36S/940 PSD MLO L120 SI	35 W
910925867889	SM340C 45S/940 PSD MLO L150 SI	43 W
910925867890	SM340C 50S/940 PSD MLO L150 SI	48 W
910925867908	SM341C 26S/940 PSD MLO L150 SI	24 W
910925867909	SM341C 35S/940 PSD MLO L150 SI	32.5 W
910925867110	SM340C 35S/940 PSD MLO L150 BK	32.5 W
910925867116	SM340C 35S/940 PSD O L150 WH	28 W
910925867867	SM340C 36S/940 PSD O L120 WH	28.5 W
910925867872	SM340C 36S/930 PSD O L120 WH	31 W
910925867886	SM340C 35S/930 PSD O L150 WH	28.5 W
910925867905	SM341C 26S/940 PSD O L150 WH	21.5 W
910925867877	SM340C 36S/940 PSD O L120 SI	28.5 W
910925867891	SM340C 35S/940 PSD O L150 SI	28 W
910925867892	SM340C 35S/940 PSD O L150 BK	28 W
910925868098	SM340C 36S/940 PSD MLO ELP3 L120 WH	39 W
910925868898	SM340C 45S/940 SRD MLO U4 L150 WH	38 W
910925868899	SM340C 52S/940 SRD PCS U4 L150 WH	43 W
910925868901	SM340C 45S/940 SRD PCS U4 L150 WH	36 W
910925868902	SM340C 35S/940 SRD PCS U4 L150 WH	24.5 W
910925868903	SM340C 42S/940 SRD PCS U4 L120 WH	35.5 W
910925868904	SM340C 36S/940 SRD PCS U4 L120 WH	31 W

FlexBlend, Surface Mounted

Mechanical and housing

Order Code	Full Product Name	Color
910925867099	SM340C 35S/940 PSD PCS L150 WH	White RAL 9003
910925867134	SM340C 36S/940 PSD PCS L120 WH	White RAL 9003
910925867135	SM340C 42S/940 PSD PCS L120 WH	White RAL 9003
910925867865	SM340C 28S/940 PSD PCS L120 WH	White RAL 9003
910925867868	SM340C 28S/930 PSD PCS L120 WH	White RAL 9003
910925867869	SM340C 36S/930 PSD PCS L120 WH	White RAL 9003
910925867878	SM340C 45S/940 PSD PCS L150 WH	White RAL 9003
910925867879	SM340C 52S/940 PSD PCS L150 WH	White RAL 9003
910925867882	SM340C 35S/930 PSD PCS L150 WH	White RAL 9003
910925867883	SM340C 45S/930 PSD PCS L150 WH	White RAL 9003
910925867902	SM341C 26S/940 PSD PCS L150 WH	White RAL 9003
910925867903	SM341C 35S/940 PSD PCS L150 WH	White RAL 9003
910925867101	SM340C 35S/940 PSD PCS L150 SI	Silver RAL 9006
910925867873	SM340C 28S/940 PSD PCS L120 SI	Silver RAL 9006
910925867874	SM340C 36S/940 PSD PCS L120 SI	Silver RAL 9006
910925867887	SM340C 45S/940 PSD PCS L150 SI	Silver RAL 9006
910925867888	SM340C 52S/940 PSD PCS L150 SI	Silver RAL 9006
910925867906	SM341C 26S/940 PSD PCS L150 SI	Silver RAL 9006
910925867907	SM341C 35S/940 PSD PCS L150 SI	Silver RAL 9006
910925867102	SM340C 35S/940 PSD PCS L150 BK	Black RAL 9004
910925867108	SM340C 35S/940 PSD MLO L150 WH	White RAL 9003
910925867136	SM340C 36S/940 PSD MLO L120 WH	White RAL 9003
910925867137	SM340C 40S/940 PSD MLO L120 WH	White RAL 9003
910925867262	SM341C 35S/940 PSD MLO L150 WH	White RAL 9003
910925867866	SM340C 28S/940 PSD MLO L120 WH	White RAL 9003
910925867870	SM340C 28S/930 PSD MLO L120 WH	White RAL 9003
910925867871	SM340C 36S/930 PSD MLO L120 WH	White RAL 9003
910925867880	SM340C 45S/940 PSD MLO L150 WH	White RAL 9003

Order Code	Full Product Name	Color
910925867881	SM340C 50S/940 PSD MLO L150 WH	White RAL 9003
910925867884	SM340C 35S/930 PSD MLO L150 WH	White RAL 9003
910925867885	SM340C 45S/930 PSD MLO L150 WH	White RAL 9003
910925867904	SM341C 26S/940 PSD MLO L150 WH	White RAL 9003
910925867109	SM340C 35S/940 PSD MLO L150 SI	Silver RAL 9006
910925867875	SM340C 28S/940 PSD MLO L120 SI	Silver RAL 9006
910925867876	SM340C 36S/940 PSD MLO L120 SI	Silver RAL 9006
910925867889	SM340C 45S/940 PSD MLO L150 SI	Silver RAL 9006
910925867890	SM340C 50S/940 PSD MLO L150 SI	Silver RAL 9006
910925867908	SM341C 26S/940 PSD MLO L150 SI	Silver RAL 9006
910925867909	SM341C 35S/940 PSD MLO L150 SI	Silver RAL 9006
910925867110	SM340C 35S/940 PSD MLO L150 BK	Black RAL 9004
910925867116	SM340C 35S/940 PSD O L150 WH	White RAL 9003
910925867867	SM340C 36S/940 PSD O L120 WH	White RAL 9003
910925867872	SM340C 36S/930 PSD O L120 WH	White RAL 9003
910925867886	SM340C 35S/930 PSD O L150 WH	White RAL 9003
910925867905	SM341C 26S/940 PSD O L150 WH	White RAL 9003
910925867877	SM340C 36S/940 PSD O L120 SI	Silver RAL 9006
910925867891	SM340C 35S/940 PSD O L150 SI	Silver RAL 9006
910925867892	SM340C 35S/940 PSD O L150 BK	Black RAL 9004
910925868098	SM340C 36S/940 PSD MLO ELP3 L120 WH	White RAL 9003
910925868898	SM340C 45S/940 SRD MLO U4 L150 WH	White
910925868899	SM340C 52S/940 SRD PCS U4 L150 WH	White
910925868901	SM340C 45S/940 SRD PCS U4 L150 WH	White
910925868902	SM340C 35S/940 SRD PCS U4 L150 WH	White
910925868903	SM340C 42S/940 SRD PCS U4 L120 WH	White
910925868904	SM340C 36S/940 SRD PCS U4 L120 WH	White

Over time performance (IEC compliant)

Order Code	Full Product Name	Driver failure rate at 5000 h
910925867099	SM340C 35S/940 PSD PCS L150 WH	-
910925867134	SM340C 36S/940 PSD PCS L120 WH	-
910925867135	SM340C 42S/940 PSD PCS L120 WH	-
910925867865	SM340C 28S/940 PSD PCS L120 WH	-
910925867868	SM340C 28S/930 PSD PCS L120 WH	-
910925867869	SM340C 36S/930 PSD PCS L120 WH	-
910925867878	SM340C 45S/940 PSD PCS L150 WH	-
910925867879	SM340C 52S/940 PSD PCS L150 WH	-
910925867882	SM340C 35S/930 PSD PCS L150 WH	-
910925867883	SM340C 45S/930 PSD PCS L150 WH	-
910925867902	SM341C 26S/940 PSD PCS L150 WH	-
910925867903	SM341C 35S/940 PSD PCS L150 WH	-
910925867101	SM340C 35S/940 PSD PCS L150 SI	-
910925867873	SM340C 28S/940 PSD PCS L120 SI	-
910925867874	SM340C 36S/940 PSD PCS L120 SI	-
910925867887	SM340C 45S/940 PSD PCS L150 SI	-
910925867888	SM340C 52S/940 PSD PCS L150 SI	-

Order Code	Full Product Name	Driver failure rate at 5000 h
910925867906	SM341C 26S/940 PSD PCS L150 SI	-
910925867907	SM341C 35S/940 PSD PCS L150 SI	-
910925867102	SM340C 35S/940 PSD PCS L150 BK	-
910925867108	SM340C 35S/940 PSD MLO L150 WH	-
910925867136	SM340C 36S/940 PSD MLO L120 WH	-
910925867137	SM340C 40S/940 PSD MLO L120 WH	-
910925867262	SM341C 35S/940 PSD MLO L150 WH	-
910925867866	SM340C 28S/940 PSD MLO L120 WH	-
910925867870	SM340C 28S/930 PSD MLO L120 WH	-
910925867871	SM340C 36S/930 PSD MLO L120 WH	-
910925867880	SM340C 45S/940 PSD MLO L150 WH	-
910925867881	SM340C 50S/940 PSD MLO L150 WH	-
910925867884	SM340C 35S/930 PSD MLO L150 WH	-
910925867885	SM340C 45S/930 PSD MLO L150 WH	-
910925867904	SM341C 26S/940 PSD MLO L150 WH	-
910925867109	SM340C 35S/940 PSD MLO L150 SI	-
910925867875	SM340C 28S/940 PSD MLO L120 SI	-

FlexBlend, Surface Mounted

Order Code	Full Product Name	Driver failure rate at 5000 h
910925867876	SM340C 36S/940 PSD MLO L120 SI	-
910925867889	SM340C 45S/940 PSD MLO L150 SI	-
910925867890	SM340C 50S/940 PSD MLO L150 SI	-
910925867908	SM341C 26S/940 PSD MLO L150 SI	-
910925867909	SM341C 35S/940 PSD MLO L150 SI	-
910925867110	SM340C 35S/940 PSD MLO L150 BK	-
910925867116	SM340C 35S/940 PSD O L150 WH	-
910925867867	SM340C 36S/940 PSD O L120 WH	-
910925867872	SM340C 36S/930 PSD O L120 WH	-
910925867886	SM340C 35S/930 PSD O L150 WH	-
910925867905	SM341C 26S/940 PSD O L150 WH	-

Order Code	Full Product Name	Driver failure rate at 5000 h
910925867877	SM340C 36S/940 PSD O L120 SI	-
910925867891	SM340C 35S/940 PSD O L150 SI	-
910925867892	SM340C 35S/940 PSD O L150 BK	-
910925868098	SM340C 36S/940 PSD MLO ELP3 L120 WH	0.05 %
910925868898	SM340C 45S/940 SRD MLO U4 L150 WH	-
910925868899	SM340C 52S/940 SRD PCS U4 L150 WH	-
910925868901	SM340C 45S/940 SRD PCS U4 L150 WH	-
910925868902	SM340C 35S/940 SRD PCS U4 L150 WH	-
910925868903	SM340C 42S/940 SRD PCS U4 L120 WH	-
910925868904	SM340C 36S/940 SRD PCS U4 L120 WH	-

