



# Greenline V3 – The light weight optimized designed product with best cost

## Greenline V3

Greenline family is a comprehensive one which offers varied solutions for difference applications. With the help of this range customers are able to achieve results with best of lighting and equally good uniformities. The product series aesthetically also meets and gels with outside environment. The option of providing connected solution is an added advantage with this range. A robust yet compact outdoor LED luminaires, designed with a focus on easy installation and maintenance.

### Benefits

- LED lighting solution that stands out in terms of efficiency, versatility and connectivity.
- Stands out as best in class in circular economy. Robust mechanical structure enabling high IP and IK ratings
- An option of using 7-Pin NEMA socket enabling easy access to the digital era of lighting with advanced lighting features that plan, monitor and control outdoor lighting networks.

### Features

- Robust pressure Die cast Aluminium housing
- Option of Glass and Polycarbonate diffuser
- Varied colour temperature options available (3000K-6500K)
- High Impact resistance IK08
- Highly energy efficient solution (120 lm/W)

## Greenline V3

### Application

- Road and Street
- Municipal Buildings
- Security Lighting

### Versions



### Product details

BRP410 LED140 CW



## Application conditions

Ambient temperature range	+10 to +35 °C
---------------------------	---------------

## Approval and application

Mech. impact protection code	6 J (IK08)
Ingress protection code	IP66

## Controls and dimming

Dimmable	Yes
----------	-----

## General information

Luminaire light beam spread	120°
Light source color	757 cool white
Driver included	Yes
Flammability mark	For mounting on normally flammable surfaces
Optic type	Wide street optic

## Initial performance (IEC compliant)

Init. Corr. Color Temperature	5700 K
Init. Color Rendering Index	≥70
System Power	120 W

## Mechanical and housing

Color	Dark gray
-------	-----------

## Approval and application

Order Code	Full Product Name	Surge Protection (Common/Differential)
919515814840	BRP410 LED145 CW M2 FG PSU	Surge protection level until 4 kV
919515814841	BRP410 LED145 CW M2 FG PSU SPD	Surge protection level until 10 kV
919515814842	BRP410 LED140 CW M2 FG PSU	Surge protection level until 4 kV
919515814843	BRP410 LED140 CW M2 FG PSU SPD	Surge protection level until 10 kV
919515814844	BRP410 LED140 CW M2 PC PSU	Surge protection level until 4 kV
919515814845	BRP410 LED140 CW M2 PC PSU SPD	Surge protection level until 10 kV

## General information

Order Code	Full Product Name	Optical cover/lens type
919515814840	BRP410 LED145 CW M2 FG PSU	Glass
919515814841	BRP410 LED145 CW M2 FG PSU SPD	Glass
919515814842	BRP410 LED140 CW M2 FG PSU	Glass

Order Code	Full Product Name	Optical cover/lens type
919515814843	BRP410 LED140 CW M2 FG PSU SPD	Glass
919515814844	BRP410 LED140 CW M2 PC PSU	UV stabilized Polycarbonate cover
919515814845	BRP410 LED140 CW M2 PC PSU SPD	UV stabilized Polycarbonate cover

## Initial performance (IEC compliant)

Order Code	Full Product Name	Initial luminous flux
919515814840	BRP410 LED145 CW M2 FG PSU	14500 lm
919515814841	BRP410 LED145 CW M2 FG PSU SPD	14500 lm
919515814842	BRP410 LED140 CW M2 FG PSU	14000 lm

Order Code	Full Product Name	Initial luminous flux
919515814843	BRP410 LED140 CW M2 FG PSU SPD	14000 lm
919515814844	BRP410 LED140 CW M2 PC PSU	14000 lm
919515814845	BRP410 LED140 CW M2 PC PSU SPD	14000 lm

