



The flexible light line

KeyLine, Suspended

These days, many office owners and office lighting designers prefer lines of light. The reason is simple. Not only do light lines come in a minimalistic design; they also offer far more choice and flexibility. Short or long lines and luminaires, standalone luminaires, different shapes and even a variety of colors; anything is possible. And with KeyLine, all these benefits come at a competitive price while still complying with office lighting norms. KeyLine is a superb light line range with a slim, minimalistic design and a high lumen output to illuminate the brightest office spaces. But with comfortable, low levels of glare it's also easy on the eye and complies with UGR19. That makes KeyLine ideal for linear applications, as well as standalone suspended or surface-mounted luminaires. A range that offers the ultimate flexibility and unlimited possibilities. KeyLine design flexibility comes in the form of different lengths, colors and light outputs – including L-shapes, as well as straight lines. All with high efficiency up to 130 lm/W, and the option to upgrade with wireless connectivity and control. Add to that attractive pricing, and with KeyLine you can also enjoy excellent value that ensures a superb total cost of ownership.

Benefits

- Suitable for office applications
- Excellent total cost of ownership
- Wide range of options to suit the demands of different offices

Features

- Comfortable, low glare: <UGR19 for the full range
- High lumen output, up to 4000lm for 1.2m version
- Interact Connectivity ready with wireless drivers
- Standard options in different lengths, colors and light outputs
- Customization options

Application

- Offices
- Retail
- Education

KeyLine, Suspended

Warnings and Safety

- KeyLine luminaires have an IPX0 classification and are not protected against water ingress. We strongly recommend that the installation environment is checked for suitability.
- If – despite the IPX0 classification warning – luminaires are subject to water ingress, Philips and Signify cannot guarantee safety or prevent failure. In this case the product warranty does not apply and becomes void.

Specifications

Ambient Temperature	+10 to +35 °C	Initial LED luminaire efficacy	127, 130, 133, 135, 136, 138, 142 lm/W
Beam spread luminaire	74° x 74°	Initial luminous flux	2600 lm, 2700 lm, 3400 lm, 3800 lm, 4000 lm, 5000 lm
Initial correlated color temperature	3000 K, 4000 K	Light source color	830 warm white, 840 neutral white
Initial input power	19.6 W, 20 W, 24 W, 25 W, 30 W, 37 W, 37.5 W	Warranty period	5 years

Versions



KeyLine suspended L1200, alu



KeyLine suspended L1200, white



KeyLine suspended L1200, bk



KeyLine - Power supply unit with SystemReady interface, InterAct ready - Medium beam - 74° x 74°



KeyLine suspended L1500, alu



KeyLine suspended L1500, white



KeyLine suspended L1500, bk



KeyLine L-corner, alu

KeyLine, Suspended

Versions

KeyLine L-corner, white



KeyLine L-corner, black



Product details

KeyLine line coupling, alu



KeyLine configuration with L-corner SM350X



KeyLine alu with suspension set for suspended mounting



KeyLine alu with end-cap accessory



KeyLine structured optics UGR19 (PCS)



KeyLine SM350C, alu



KeyLine, Suspended

Product details



KeyLine alu line coupling with coupling piece accessory



KeyLine alu with ceiling bracket accessory for surface mounting



KeyLine alu with coupling piece accessory for line mounting



KeyLine line configuration, white



KeyLine SM350C, white



KeyLine line coupling, white



KeyLine white line coupling with coupling piece accessory



KeyLine white with coupling piece accessory for line mounting



KeyLine white with suspension set for suspended mounting

KeyLine, Suspended

Product details



KeyLine white with ceiling bracket accessory for surface mounting



KeyLine white with end-cap accessory



KeyLine black with ceiling bracket accessory for surface mounting



KeyLine black with coupling piece accessory for line mounting



KeyLine black with end-cap accessory



KeyLine line coupling, black



KeyLine line configuration, black



KeyLine SM350C, black



KeyLine black line coupling with coupling piece accessory



KeyLine black with suspension set for suspended mounting

KeyLine, Suspended


Product details



KeyLine_SM350C_WIA_DPP1



KeyLine_SM350C_WIA_DPP3



KeyLine_SM350C_WIA_DPP2



KeyLine L-corner, alu



KeyLine L-corner, white



KeyLine L-corner, black

Accessories



KeyLine -- V -- Hz -----
White

Ordercode 910925868341



KeyLine -- V -- Hz -----
Black

Ordercode 910925868342

KeyLine, Suspended

Accessories



KeyLine -- V -- Hz -----
Silver

Ordercode 910925868343



KeyLine -- V -- Hz -----
-

Ordercode 910925868344



KeyLine -- V -- Hz -----
-

Ordercode 910925868345



KeyLine -- V -- Hz -----
White

Ordercode 910925868346



KeyLine -- V -- Hz -----
Silver

Ordercode 910925868347



KeyLine -- V -- Hz -----
-

Ordercode 910925868348



KeyLine -- V -- Hz -----
Silver

Ordercode 910925868349



KeyLine -- V -- Hz -----
Silver

Ordercode 910925868350

KeyLine, Suspended

Application conditions

Ambient temperature range	+10 to +35 °C
Suitable for random switching	No

Approval and application

Mech. impact protection code	IK02
Ingress protection code	IP20

Operating and electrical

Input Voltage	220 to 240 V
---------------	--------------

General information

Beam angle of light source	120 °
CE mark	CE mark
Protection class IEC	Safety class I
Driver included	Yes
ENEC mark	ENEC mark
Flammability mark	For mounting on normally flammable surfaces
Light source replaceable	No
Number of gear units	1 unit
Optic type	Medium beam

Initial performance (IEC compliant)

Init. Color Rendering Index	>80
Luminous flux tolerance	+/-10%

Light technical

Flickering	1
Stroboscopic effect	0.4

Application conditions

Order Code	Full Product Name	Maximum dim level
910925868303	SM350C 27S/840 PSU PCS L1200 ALU	Not applicable
910925868353	SM350C 40S/840 PSU PCS L1200 ALU	Not applicable
910925868356	SM350C 27S/840 PSD PCS L1200 ALU	1%
910925868359	SM350C 40S/840 PSD PCS L1200 ALU	1%
910925868368	SM350C 27S/830 PSU PCS L1200 ALU	Not applicable
910925868370	SM350C 40S/830 PSU PCS L1200 ALU	Not applicable
910925868372	SM350C 27S/830 PSD PCS L1200 ALU	1%
910925868374	SM350C 40S/830 PSD PCS L1200 ALU	1%
910925868351	SM350C 27S/840 PSU PCS L1200 WH	Not applicable
910925868354	SM350C 40S/840 PSU PCS L1200 WH	Not applicable
910925868357	SM350C 27S/840 PSD PCS L1200 WH	1%
910925868360	SM350C 40S/840 PSD PCS L1200 WH	1%
910925868369	SM350C 27S/830 PSU PCS L1200 WH	Not applicable
910925868371	SM350C 40S/830 PSU PCS L1200 WH	Not applicable
910925868373	SM350C 27S/830 PSD PCS L1200 WH	1%
910925868375	SM350C 40S/830 PSD PCS L1200 WH	1%
910925868352	SM350C 27S/840 PSU PCS L1200 BK	Not applicable
910925868355	SM350C 40S/840 PSU PCS L1200 BK	Not applicable
910925868358	SM350C 27S/840 PSD PCS L1200 BK	1%
910925868361	SM350C 40S/840 PSD PCS L1200 BK	1%
910925868362	SM350C 27S/840 WIA PCS L1200 ALU	1%
910925868363	SM350C 27S/840 WIA PCS L1200 WH	1%
910925868364	SM350C 27S/840 WIA PCS L1200 BK	1%
910925868365	SM350C 40S/840 WIA PCS L1200 ALU	1%
910925868366	SM350C 40S/840 WIA PCS L1200 WH	1%
910925868367	SM350C 40S/840 WIA PCS L1200 BK	1%
910925868376	SM350C 34S/840 PSU PCS L1500 ALU	Not applicable
910925868379	SM350C 50S/840 PSU PCS L1500 ALU	Not applicable
910925868382	SM350C 34S/840 PSD PCS L1500 ALU	1%
910925868385	SM350C 50S/840 PSD PCS L1500 ALU	1%
910925868377	SM350C 34S/840 PSU PCS L1500 WH	Not applicable
910925868380	SM350C 50S/840 PSU PCS L1500 WH	Not applicable
910925868383	SM350C 34S/840 PSD PCS L1500 WH	1%
910925868386	SM350C 50S/840 PSD PCS L1500 WH	1%
910925868378	SM350C 34S/840 PSU PCS L1500 BK	Not applicable
910925868381	SM350C 50S/840 PSU PCS L1500 BK	Not applicable
910925868384	SM350C 34S/840 PSD PCS L1500 BK	1%
910925868387	SM350C 50S/840 PSD PCS L1500 BK	1%
910925868388	SM350X 27S/840 PSD L60L60 PCS ALU	1%
910925868389	SM350X 27S/840 PSD L60L60 PCS WH	1%
910925868390	SM350X 27S/840 PSD L60L60 PCS BK	1%

Controls and dimming

Order Code	Full Product Name	Dimmable	Order Code	Full Product Name	Dimmable
910925868303	SM350C 27S/840 PSU PCS L1200 ALU	No	910925868370	SM350C 40S/830 PSU PCS L1200 ALU	No
910925868353	SM350C 40S/840 PSU PCS L1200 ALU	No	910925868372	SM350C 27S/830 PSD PCS L1200 ALU	Yes
910925868356	SM350C 27S/840 PSD PCS L1200 ALU	Yes	910925868374	SM350C 40S/830 PSD PCS L1200 ALU	Yes
910925868359	SM350C 40S/840 PSD PCS L1200 ALU	Yes	910925868351	SM350C 27S/840 PSU PCS L1200 WH	No
910925868368	SM350C 27S/830 PSU PCS L1200 ALU	No	910925868354	SM350C 40S/840 PSU PCS L1200 WH	No

KeyLine, Suspended

Order Code	Full Product Name	Dimmable
910925868357	SM350C 27S/840 PSD PCS L1200 WH	Yes
910925868360	SM350C 40S/840 PSD PCS L1200 WH	Yes
910925868369	SM350C 27S/830 PSU PCS L1200 WH	No
910925868371	SM350C 40S/830 PSU PCS L1200 WH	No
910925868373	SM350C 27S/830 PSD PCS L1200 WH	Yes
910925868375	SM350C 40S/830 PSD PCS L1200 WH	Yes
910925868352	SM350C 27S/840 PSU PCS L1200 BK	No
910925868355	SM350C 40S/840 PSU PCS L1200 BK	No
910925868358	SM350C 27S/840 PSD PCS L1200 BK	Yes
910925868361	SM350C 40S/840 PSD PCS L1200 BK	Yes
910925868362	SM350C 27S/840 WIA PCS L1200 ALU	Yes
910925868363	SM350C 27S/840 WIA PCS L1200 WH	Yes
910925868364	SM350C 27S/840 WIA PCS L1200 BK	Yes
910925868365	SM350C 40S/840 WIA PCS L1200 ALU	Yes
910925868366	SM350C 40S/840 WIA PCS L1200 WH	Yes
910925868367	SM350C 40S/840 WIA PCS L1200 BK	Yes

Order Code	Full Product Name	Dimmable
910925868376	SM350C 34S/840 PSU PCS L1500 ALU	No
910925868379	SM350C 50S/840 PSU PCS L1500 ALU	No
910925868382	SM350C 34S/840 PSD PCS L1500 ALU	Yes
910925868385	SM350C 50S/840 PSD PCS L1500 ALU	Yes
910925868377	SM350C 34S/840 PSU PCS L1500 WH	No
910925868380	SM350C 50S/840 PSU PCS L1500 WH	No
910925868383	SM350C 34S/840 PSD PCS L1500 WH	Yes
910925868386	SM350C 50S/840 PSD PCS L1500 WH	Yes
910925868378	SM350C 34S/840 PSU PCS L1500 BK	No
910925868381	SM350C 50S/840 PSU PCS L1500 BK	No
910925868384	SM350C 34S/840 PSD PCS L1500 BK	Yes
910925868387	SM350C 50S/840 PSD PCS L1500 BK	Yes
910925868388	SM350X 27S/840 PSD L60L60 PCS ALU	Yes
910925868389	SM350X 27S/840 PSD L60L60 PCS WH	Yes
910925868390	SM350X 27S/840 PSD L60L60 PCS BK	Yes

General information

Order Code	Full Product Name	Glow-wire test	Product Family Code
910925868303	SM350C 27S/840 PSU PCS L1200 ALU	Temperature 850 °C, duration 30 s	SM350C
910925868353	SM350C 40S/840 PSU PCS L1200 ALU	Temperature 850 °C, duration 30 s	SM350C
910925868356	SM350C 27S/840 PSD PCS L1200 ALU	Temperature 850 °C, duration 30 s	SM350C
910925868359	SM350C 40S/840 PSD PCS L1200 ALU	Temperature 850 °C, duration 30 s	SM350C
910925868368	SM350C 27S/830 PSU PCS L1200 ALU	Temperature 850 °C, duration 30 s	SM350C
910925868370	SM350C 40S/830 PSU PCS L1200 ALU	Temperature 850 °C, duration 30 s	SM350C
910925868372	SM350C 27S/830 PSD PCS L1200 ALU	Temperature 850 °C, duration 30 s	SM350C
910925868374	SM350C 40S/830 PSD PCS L1200 ALU	Temperature 850 °C, duration 30 s	SM350C
910925868351	SM350C 27S/840 PSU PCS L1200 WH	Temperature 850 °C, duration 30 s	SM350C
910925868354	SM350C 40S/840 PSU PCS L1200 WH	Temperature 850 °C, duration 30 s	SM350C
910925868357	SM350C 27S/840 PSD PCS L1200 WH	Temperature 850 °C, duration 30 s	SM350C
910925868360	SM350C 40S/840 PSD PCS L1200 WH	Temperature 850 °C, duration 30 s	SM350C
910925868369	SM350C 27S/830 PSU PCS L1200 WH	Temperature 850 °C, duration 30 s	SM350C
910925868371	SM350C 40S/830 PSU PCS L1200 WH	Temperature 850 °C, duration 30 s	SM350C
910925868373	SM350C 27S/830 PSD PCS L1200 WH	Temperature 850 °C, duration 30 s	SM350C

Order Code	Full Product Name	Glow-wire test	Product Family Code
910925868375	SM350C 40S/830 PSD PCS L1200 WH	Temperature 850 °C, duration 30 s	SM350C
910925868352	SM350C 27S/840 PSU PCS L1200 BK	Temperature 850 °C, duration 30 s	SM350C
910925868355	SM350C 40S/840 PSU PCS L1200 BK	Temperature 850 °C, duration 30 s	SM350C
910925868358	SM350C 27S/840 PSD PCS L1200 BK	Temperature 850 °C, duration 30 s	SM350C
910925868361	SM350C 40S/840 PSD PCS L1200 BK	Temperature 850 °C, duration 30 s	SM350C
910925868362	SM350C 27S/840 WIA PCS L1200 ALU	Temperature 650 °C, duration 30 s	SM350C
910925868363	SM350C 27S/840 WIA PCS L1200 WH	Temperature 650 °C, duration 30 s	SM350C
910925868364	SM350C 27S/840 WIA PCS L1200 BK	Temperature 650 °C, duration 30 s	SM350C
910925868365	SM350C 40S/840 WIA PCS L1200 ALU	Temperature 650 °C, duration 30 s	SM350C
910925868366	SM350C 40S/840 WIA PCS L1200 WH	Temperature 650 °C, duration 30 s	SM350C
910925868367	SM350C 40S/840 WIA PCS L1200 BK	Temperature 650 °C, duration 30 s	SM350C
910925868376	SM350C 34S/840 PSU PCS L1500 ALU	Temperature 850 °C, duration 30 s	SM350C
910925868379	SM350C 50S/840 PSU PCS L1500 ALU	Temperature 850 °C, duration 30 s	SM350C
910925868382	SM350C 34S/840 PSD PCS L1500 ALU	Temperature 850 °C, duration 30 s	SM350C
910925868385	SM350C 50S/840 PSD PCS L1500 ALU	Temperature 850 °C, duration 30 s	SM350C

KeyLine, Suspended

Order Code	Full Product Name	Glow-wire test	Product Family Code
910925868377	SM350C 34S/840 PSU PCS L1500 WH	Temperature 850 °C, duration 30 s	SM350C
910925868380	SM350C 50S/840 PSU PCS L1500 WH	Temperature 850 °C, duration 30 s	SM350C
910925868383	SM350C 34S/840 PSD PCS L1500 WH	Temperature 850 °C, duration 30 s	SM350C
910925868386	SM350C 50S/840 PSD PCS L1500 WH	Temperature 850 °C, duration 30 s	SM350C
910925868378	SM350C 34S/840 PSU PCS L1500 BK	Temperature 850 °C, duration 30 s	SM350C
910925868381	SM350C 50S/840 PSU PCS L1500 BK	Temperature 850 °C, duration 30 s	SM350C

Order Code	Full Product Name	Glow-wire test	Product Family Code
910925868384	SM350C 34S/840 PSD PCS L1500 BK	Temperature 850 °C, duration 30 s	SM350C
910925868387	SM350C 50S/840 PSD PCS L1500 BK	Temperature 850 °C, duration 30 s	SM350C
910925868388	SM350X 27S/840 PSD L60L60 PCS ALU	Temperature 850 °C, duration 30 s	SM350X
910925868389	SM350X 27S/840 PSD L60L60 PCS WH	Temperature 850 °C, duration 30 s	SM350X
910925868390	SM350X 27S/840 PSD L60L60 PCS BK	Temperature 850 °C, duration 30 s	SM350X

Initial performance (IEC compliant) (1/2)

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux
910925868303	SM350C 27S/840 PSU PCS L1200 ALU	(0.39, 0.38) SDCM <3	4000 K	138 lm/W	2700 lm
910925868353	SM350C 40S/840 PSU PCS L1200 ALU	(0.39, 0.38) SDCM <3	4000 K	133 lm/W	4000 lm
910925868356	SM350C 27S/840 PSD PCS L1200 ALU	(0.39, 0.38) SDCM <3	4000 K	135 lm/W	2700 lm
910925868359	SM350C 40S/840 PSD PCS L1200 ALU	(0.39, 0.38) SDCM <3	4000 K	133 lm/W	4000 lm
910925868368	SM350C 27S/830 PSU PCS L1200 ALU	(0.43, 0.40) SDCM <3	3000 K	133 lm/W	2600 lm
910925868370	SM350C 40S/830 PSU PCS L1200 ALU	(0.43, 0.40) SDCM <3	3000 K	127 lm/W	3800 lm
910925868372	SM350C 27S/830 PSD PCS L1200 ALU	(0.43, 0.40) SDCM <3	3000 K	130 lm/W	2600 lm
910925868374	SM350C 40S/830 PSD PCS L1200 ALU	(0.43, 0.40) SDCM <3	3000 K	127 lm/W	3800 lm

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux
910925868351	SM350C 27S/840 PSU PCS L1200 WH	(0.39, 0.38) SDCM <3	4000 K	138 lm/W	2700 lm
910925868354	SM350C 40S/840 PSU PCS L1200 WH	(0.39, 0.38) SDCM <3	4000 K	133 lm/W	4000 lm
910925868357	SM350C 27S/840 PSD PCS L1200 WH	(0.39, 0.38) SDCM <3	4000 K	135 lm/W	2700 lm
910925868360	SM350C 40S/840 PSD PCS L1200 WH	(0.39, 0.38) SDCM <3	4000 K	133 lm/W	4000 lm
910925868369	SM350C 27S/830 PSU PCS L1200 WH	(0.43, 0.40) SDCM <3	3000 K	133 lm/W	2600 lm
910925868371	SM350C 40S/830 PSU PCS L1200 WH	(0.43, 0.40) SDCM <3	3000 K	127 lm/W	3800 lm
910925868373	SM350C 27S/830 PSD PCS L1200 WH	(0.43, 0.40) SDCM <3	3000 K	130 lm/W	2600 lm
910925868375	SM350C 40S/830 PSD PCS L1200 WH	(0.43, 0.40) SDCM <3	3000 K	127 lm/W	3800 lm

KeyLine, Suspended

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux
910925868352	SM350C 27S/840 PSU PCS L1200 BK	(0.39, 0.38) SDCM <3	4000 K	138 lm/W	2700 lm
910925868355	SM350C 40S/840 PSU PCS L1200 BK	(0.39, 0.38) SDCM <3	4000 K	133 lm/W	4000 lm
910925868358	SM350C 27S/840 PSD PCS L1200 BK	(0.39, 0.38) SDCM <3	4000 K	135 lm/W	2700 lm
910925868361	SM350C 40S/840 PSD PCS L1200 BK	(0.39, 0.38) SDCM <3	4000 K	133 lm/W	4000 lm
910925868362	SM350C 27S/840 WIA PCS L1200 ALU	(0.39, 0.38) SDCM <3	4000 K	135 lm/W	2700 lm
910925868363	SM350C 27S/840 WIA PCS L1200 WH	(0.39, 0.38) SDCM <3	4000 K	135 lm/W	2700 lm
910925868364	SM350C 27S/840 WIA PCS L1200 BK	(0.39, 0.38) SDCM <3	4000 K	135 lm/W	2700 lm
910925868365	SM350C 40S/840 WIA PCS L1200 ALU	(0.39, 0.38) SDCM <3	4000 K	133 lm/W	4000 lm
910925868366	SM350C 40S/840 WIA PCS L1200 WH	(0.39, 0.38) SDCM <3	4000 K	133 lm/W	4000 lm
910925868367	SM350C 40S/840 WIA PCS L1200 BK	(0.39, 0.38) SDCM <3	4000 K	133 lm/W	4000 lm
910925868376	SM350C 34S/840 PSU PCS L1500 ALU	(0.39, 0.38) SDCM <3	4000 K	142 lm/W	3400 lm
910925868379	SM350C 50S/840 PSU PCS L1500 ALU	(0.39, 0.38) SDCM <3	4000 K	135 lm/W	5000 lm
910925868382	SM350C 34S/840 PSD SDCM <3	(0.39, 0.38)	4000 K	136 lm/W	3400 lm

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux
	PCS L1500 ALU				
910925868385	SM350C 50S/840 PSD PCS L1500 ALU	(0.39, 0.38) SDCM <3	4000 K	133 lm/W	5000 lm
910925868377	SM350C 34S/840 PSU PCS L1500 WH	(0.39, 0.38) SDCM <3	4000 K	142 lm/W	3400 lm
910925868380	SM350C 50S/840 PSU PCS L1500 WH	(0.39, 0.38) SDCM <3	4000 K	135 lm/W	5000 lm
910925868383	SM350C 34S/840 PSD PCS L1500 WH	(0.39, 0.38) SDCM <3	4000 K	136 lm/W	3400 lm
910925868386	SM350C 50S/840 PSD PCS L1500 WH	(0.39, 0.38) SDCM <3	4000 K	133 lm/W	5000 lm
910925868378	SM350C 34S/840 PSU PCS L1500 BK	(0.39, 0.38) SDCM <3	4000 K	142 lm/W	3400 lm
910925868381	SM350C 50S/840 PSU PCS L1500 BK	(0.39, 0.38) SDCM <3	4000 K	135 lm/W	5000 lm
910925868384	SM350C 34S/840 PSD PCS L1500 BK	(0.39, 0.38) SDCM <3	4000 K	136 lm/W	3400 lm
910925868387	SM350C 50S/840 PSD PCS L1500 BK	(0.39, 0.38) SDCM <3	4000 K	133 lm/W	5000 lm
910925868388	SM350X 27S/840 PSD L60L60 PCS ALU	(0.39, 0.38) SDCM <3	4000 K	135 lm/W	2700 lm
910925868389	SM350X 27S/840 PSD L60L60 PCS WH	(0.39, 0.38) SDCM <3	4000 K	135 lm/W	2700 lm
910925868390	SM350X 27S/840 PSD L60L60 PCS BK	(0.39, 0.38) SDCM <3	4000 K	135 lm/W	2700 lm

KeyLine, Suspended

Initial performance (IEC compliant) (2/2)

Order Code	Full Product Name	Initial input power
910925868303	SM350C 27S/840 PSU PCS L1200 ALU	19.6 W
910925868353	SM350C 40S/840 PSU PCS L1200 ALU	30 W
910925868356	SM350C 27S/840 PSD PCS L1200 ALU	20 W
910925868359	SM350C 40S/840 PSD PCS L1200 ALU	30 W
910925868368	SM350C 27S/830 PSU PCS L1200 ALU	19.6 W
910925868370	SM350C 40S/830 PSU PCS L1200 ALU	30 W
910925868372	SM350C 27S/830 PSD PCS L1200 ALU	20 W
910925868374	SM350C 40S/830 PSD PCS L1200 ALU	30 W
910925868351	SM350C 27S/840 PSU PCS L1200 WH	19.6 W
910925868354	SM350C 40S/840 PSU PCS L1200 WH	30 W
910925868357	SM350C 27S/840 PSD PCS L1200 WH	20 W
910925868360	SM350C 40S/840 PSD PCS L1200 WH	30 W
910925868369	SM350C 27S/830 PSU PCS L1200 WH	19.6 W
910925868371	SM350C 40S/830 PSU PCS L1200 WH	30 W
910925868373	SM350C 27S/830 PSD PCS L1200 WH	20 W
910925868375	SM350C 40S/830 PSD PCS L1200 WH	30 W
910925868352	SM350C 27S/840 PSU PCS L1200 BK	19.6 W
910925868355	SM350C 40S/840 PSU PCS L1200 BK	30 W
910925868358	SM350C 27S/840 PSD PCS L1200 BK	20 W
910925868361	SM350C 40S/840 PSD PCS L1200 BK	30 W
910925868362	SM350C 27S/840 WIA PCS L1200 ALU	20 W

Order Code	Full Product Name	Initial input power
910925868363	SM350C 27S/840 WIA PCS L1200 WH	20 W
910925868364	SM350C 27S/840 WIA PCS L1200 BK	20 W
910925868365	SM350C 40S/840 WIA PCS L1200 ALU	30 W
910925868366	SM350C 40S/840 WIA PCS L1200 WH	30 W
910925868367	SM350C 40S/840 WIA PCS L1200 BK	30 W
910925868376	SM350C 34S/840 PSU PCS L1500 ALU	24 W
910925868379	SM350C 50S/840 PSU PCS L1500 ALU	37 W
910925868382	SM350C 34S/840 PSD PCS L1500 ALU	25 W
910925868385	SM350C 50S/840 PSD PCS L1500 ALU	37.5 W
910925868377	SM350C 34S/840 PSU PCS L1500 WH	24 W
910925868380	SM350C 50S/840 PSU PCS L1500 WH	37 W
910925868383	SM350C 34S/840 PSD PCS L1500 WH	25 W
910925868386	SM350C 50S/840 PSD PCS L1500 WH	37.5 W
910925868378	SM350C 34S/840 PSU PCS L1500 BK	24 W
910925868381	SM350C 50S/840 PSU PCS L1500 BK	37 W
910925868384	SM350C 34S/840 PSD PCS L1500 BK	25 W
910925868387	SM350C 50S/840 PSD PCS L1500 BK	37.5 W
910925868388	SM350X 27S/840 PSD L60L60 PCS ALU	20 W
910925868389	SM350X 27S/840 PSD L60L60 PCS WH	20 W
910925868390	SM350X 27S/840 PSD L60L60 PCS BK	20 W

Mechanical and housing

Order Code	Full Product Name	Color
910925868303	SM350C 27S/840 PSU PCS L1200 ALU	Aluminum
910925868353	SM350C 40S/840 PSU PCS L1200 ALU	Aluminum
910925868356	SM350C 27S/840 PSD PCS L1200 ALU	Aluminum
910925868359	SM350C 40S/840 PSD PCS L1200 ALU	Aluminum
910925868368	SM350C 27S/830 PSU PCS L1200 ALU	Aluminum
910925868370	SM350C 40S/830 PSU PCS L1200 ALU	Aluminum
910925868372	SM350C 27S/830 PSD PCS L1200 ALU	Aluminum
910925868374	SM350C 40S/830 PSD PCS L1200 ALU	Aluminum
910925868351	SM350C 27S/840 PSU PCS L1200 WH	White RAL 9003
910925868354	SM350C 40S/840 PSU PCS L1200 WH	White RAL 9003
910925868357	SM350C 27S/840 PSD PCS L1200 WH	White RAL 9003
910925868360	SM350C 40S/840 PSD PCS L1200 WH	White RAL 9003
910925868369	SM350C 27S/830 PSU PCS L1200 WH	White RAL 9003
910925868371	SM350C 40S/830 PSU PCS L1200 WH	White RAL 9003
910925868373	SM350C 27S/830 PSD PCS L1200 WH	White RAL 9003
910925868375	SM350C 40S/830 PSD PCS L1200 WH	White RAL 9003
910925868352	SM350C 27S/840 PSU PCS L1200 BK	Black RAL 9004
910925868355	SM350C 40S/840 PSU PCS L1200 BK	Black RAL 9004
910925868358	SM350C 27S/840 PSD PCS L1200 BK	Black RAL 9004
910925868361	SM350C 40S/840 PSD PCS L1200 BK	Black RAL 9004
910925868362	SM350C 27S/840 WIA PCS L1200 ALU	Aluminum

Order Code	Full Product Name	Color
910925868363	SM350C 27S/840 WIA PCS L1200 WH	White RAL 9003
910925868364	SM350C 27S/840 WIA PCS L1200 BK	Black RAL 9004
910925868365	SM350C 40S/840 WIA PCS L1200 ALU	Aluminum
910925868366	SM350C 40S/840 WIA PCS L1200 WH	White RAL 9003
910925868367	SM350C 40S/840 WIA PCS L1200 BK	Black RAL 9004
910925868376	SM350C 34S/840 PSU PCS L1500 ALU	Aluminum
910925868379	SM350C 50S/840 PSU PCS L1500 ALU	Aluminum
910925868382	SM350C 34S/840 PSD PCS L1500 ALU	Aluminum
910925868385	SM350C 50S/840 PSD PCS L1500 ALU	Aluminum
910925868377	SM350C 34S/840 PSU PCS L1500 WH	White RAL 9003
910925868380	SM350C 50S/840 PSU PCS L1500 WH	White RAL 9003
910925868383	SM350C 34S/840 PSD PCS L1500 WH	White RAL 9003
910925868386	SM350C 50S/840 PSD PCS L1500 WH	White RAL 9003
910925868378	SM350C 34S/840 PSU PCS L1500 BK	Black RAL 9004
910925868381	SM350C 50S/840 PSU PCS L1500 BK	Black RAL 9004
910925868384	SM350C 34S/840 PSD PCS L1500 BK	Black RAL 9004
910925868387	SM350C 50S/840 PSD PCS L1500 BK	Black RAL 9004
910925868388	SM350X 27S/840 PSD L60L60 PCS ALU	Aluminum
910925868389	SM350X 27S/840 PSD L60L60 PCS WH	White RAL 9003
910925868390	SM350X 27S/840 PSD L60L60 PCS BK	Black RAL 9004

KeyLine, Suspended

