



Ledinaire Streetlight – Simple and Reliable

Ledinaire StreetLight

Ledinaire Streetlight has been designed with Led transition in mind. Whether to refurbish old HID lanterns, or on a new country street, where you want citizens to feel safe. Ledinaire Streetlight offers simple benefits and reliable performance

Benefits

- Insulation class II
- Standard surge protection level of 4 kV
- High efficacy up to 117 lm/W

Features

- Easy to install
- Suitable for different applications thanks to medium wide light distribution
- Warm or neutral white color temperatures can accommodate various places
- Easy logistics

Application

- Residential
- Road and Street

Ledinaire StreetLight

Versions



Ledinaire StreetLight BRP056

Ledinaire StreetLight BRP062

Application conditions

Maximum dim level	Not applicable
-------------------	----------------

Approval and application

Mech. impact protection code	IK07
Surge Protection (Common/Differential)	Luminaire surge protection level until 4 kV differential mode and 4 kV common mode

Controls and dimming

Dimmable	No
----------	----

General information

Luminaire light beam spread	-
CE mark	CE mark
Optical cover/lens type	Polycarbonate
Driver included	Yes
Flammability mark	-
Light source replaceable	No
Number of gear units	1 unit
Optic type	-

Initial performance (IEC compliant)

Init. Color Rendering Index	>70
-----------------------------	-----

Light technical

Standard tilt angle side entry	0°
Standard tilt angle posttop	-
Upward light output ratio	0

Mechanical and housing

Color	Dark gray
-------	-----------

General information

Order Code	Full Product Name	Light source color	Lamp family code
919515814268	BRP056 LED34/730 PSU 27W SLF CE	730 warm white	LED34
919515814269	BRP056 LED53/730 PSU 42W SLF CE	730 warm white	LED53
919515814271	BRP056 LED35/740 PSU 27W SLF CE	740 neutral white	LED35
919515814272	BRP056 LED55/740 PSU 42W SLF CE	740 neutral white	LED55
919515814270	BRP062 LED70/730 PSU 54W SLA CE	730 warm white	LED70
919515814273	BRP062 LED72/740 PSU 54W SLA CE	740 neutral white	LED72

Initial performance (IEC compliant)

Ledinaire StreetLight

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial luminous flux
919515814268	BRP056 LED34/730 PSU 27W SLF CE	3000 K	2952.2 lm
919515814269	BRP056 LED53/730 PSU 42W SLF CE	3000 K	4606.6 lm
919515814271	BRP056 LED35/740 PSU 27W SLF CE	4000 K	3101.1 lm

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial luminous flux
919515814272	BRP056 LED55/740 PSU 42W SLF CE	4000 K	4850.1 lm
919515814270	BRP062 LED70/730 PSU 54W SLA CE	3000 K	6107.5 lm
919515814273	BRP062 LED72/740 PSU 54W SLA CE	4000 K	6302.2 lm

