



# Miniaturized downlight with leading optical performance and great diversity

## LuxSpace G4

LuxSpace Gen4 is the a new LED downlight range combining light comfort and leading performance with luxury looking

### Benefits

- Visual comfort
- Multiple options for various applications
- Smart lighting


### Features

- Miniaturized form factor
- High optical efficiency
- Great product diversity
- Tunable white

### Application

- Office
- shopping mall
- hotel
- retail

## Versions



DN58XB DN59XB D100 D125

DN58XB DN59XB D150 D200

DN591B LED20/TWH PSD C D150

Luxspace G4



Luxspace G4

Luxspace G4

Luxspace G4

### Application conditions

Ambient temperature range -20 to +40 °C

### Operating and electrical

Input Voltage 220 to 240 V

### General information

CE mark CE mark

## Application conditions

Order Code	Full Product Name	Maximum dim level
911401536641	DN588B LED6/830 PSU C D100 WH WB GC	Not applicable
911401536741	DN588B LED6/840 PSU C D100 WH WB GC	Not applicable
911401536841	DN588B LED6/930 PSU C D100 WH WB GC	Not applicable
911401536941	DN588B LED6/940 PSU C D100 WH WB GC	Not applicable
911401537041	DN588B LED6/830 PSU C D100 WH MB GC	Not applicable
911401537141	DN588B LED6/840 PSU C D100 WH MB GC	Not applicable
911401537241	DN588B LED6/930 PSU C D100 WH MB GC	Not applicable
911401537341	DN588B LED6/940 PSU C D100 WH MB GC	Not applicable
911401537441	DN589B LED10/830 PSU C D125 WH WB GC	Not applicable
911401537541	DN589B LED10/840 PSU C D125 WH WB GC	Not applicable
911401537641	DN589B LED10/930 PSU C D125 WH WB GC	Not applicable
911401537741	DN589B LED10/940 PSU C D125 WH WB GC	Not applicable
911401537841	DN589B LED10/830 PSU C D125 WH MB GC	Not applicable

Order Code	Full Product Name	Maximum dim level
911401537941	DN589B LED10/840 PSU C D125 WH MB GC	Not applicable
911401538041	DN589B LED10/930 PSU C D125 WH MB GC	Not applicable
911401538141	DN589B LED10/940 PSU C D125 WH MB GC	Not applicable
911401538241	DN589B LED10/830 PSD C D125 WH WB GC	1%
911401538341	DN589B LED10/840 PSD C D125 WH WB GC	1%
911401538441	DN589B LED10/930 PSD C D125 WH WB GC	1%
911401538541	DN589B LED10/940 PSD C D125 WH WB GC	1%
911401538641	DN589B LED10/830 PSD C D125 WH MB GC	1%
911401538741	DN589B LED10/840 PSD C D125 WH MB GC	1%
911401538841	DN589B LED10/930 PSD C D125 WH MB GC	1%
911401538941	DN589B LED10/940 PSD C D125 WH MB GC	1%
911401539041	DN590B LED15/830 PSU C D125 WH WB GC	Not applicable
911401539141	DN590B LED15/840 PSU C D125 WH WB GC	Not applicable

Order Code	Full Product Name	Maximum dim level	Order Code	Full Product Name	Maximum dim level
911401539241	DN590B LED15/930 PSU C D125 WH WB GC	Not applicable	911401543841	DN591B LED20/840 PSD C D150 WH MB GC	1%
911401539341	DN590B LED15/940 PSU C D125 WH WB GC	Not applicable	911401543941	DN591B LED20/930 PSD C D150 WH MB GC	1%
911401539441	DN590B LED15/830 PSU C D125 WH MB GC	Not applicable	911401544041	DN591B LED20/940 PSD C D150 WH MB GC	1%
911401539541	DN590B LED15/840 PSU C D125 WH MB GC	Not applicable	911401544141	DN592B LED25/830 PSU C D150 WH WB GC	Not applicable
911401539641	DN590B LED15/930 PSU C D125 WH MB GC	Not applicable	911401544241	DN592B LED25/840 PSU C D150 WH WB GC	Not applicable
911401539741	DN590B LED15/940 PSU C D125 WH MB GC	Not applicable	911401544341	DN592B LED25/930 PSU C D150 WH WB GC	Not applicable
911401539841	DN590B LED15/830 PSD C D125 WH WB GC	1%	911401544441	DN592B LED25/940 PSU C D150 WH WB GC	Not applicable
911401539941	DN590B LED15/840 PSD C D125 WH WB GC	1%	911401544541	DN592B LED25/830 PSU C D150 WH MB GC	Not applicable
911401540041	DN590B LED15/930 PSD C D125 WH WB GC	1%	911401544641	DN592B LED25/840 PSU C D150 WH MB GC	Not applicable
911401540141	DN590B LED15/940 PSD C D125 WH WB GC	1%	911401544741	DN592B LED25/930 PSU C D150 WH MB GC	Not applicable
911401540241	DN590B LED15/830 PSD C D125 WH MB GC	1%	911401544841	DN592B LED25/940 PSU C D150 WH MB GC	Not applicable
911401540341	DN590B LED15/840 PSD C D125 WH MB GC	1%	911401544941	DN592B LED25/830 PSD C D150 WH WB GC	1%
911401540441	DN590B LED15/930 PSD C D125 WH MB GC	1%	911401545041	DN592B LED25/840 PSD C D150 WH WB GC	1%
911401540541	DN590B LED15/940 PSD C D125 WH MB GC	1%	911401545141	DN592B LED25/930 PSD C D150 WH WB GC	1%
911401540641	DN590B LED15/830 POE C D125 WH WB GC	30%	911401545241	DN592B LED25/940 PSD C D150 WH WB GC	1%
911401540741	DN590B LED15/840 POE C D125 WH WB GC	30%	911401545341	DN592B LED25/830 PSD C D150 WH MB GC	1%
911401540941	DN591B LED20/830 PSU C D125 WH WB GC	Not applicable	911401545441	DN592B LED25/840 PSD C D150 WH MB GC	1%
911401541041	DN591B LED20/840 PSU C D125 WH WB GC	Not applicable	911401545541	DN592B LED25/930 PSD C D150 WH MB GC	1%
911401541141	DN591B LED20/930 PSU C D125 WH WB GC	Not applicable	911401545641	DN592B LED25/940 PSD C D150 WH MB GC	1%
911401541241	DN591B LED20/940 PSU C D125 WH WB GC	Not applicable	911401545741	DN592B LED25/830 POE C D150 WH WB GC	30%
911401541341	DN591B LED20/830 PSU C D125 WH MB GC	Not applicable	911401545841	DN592B LED25/840 POE C D150 WH WB GC	30%
911401541441	DN591B LED20/840 PSU C D125 WH MB GC	Not applicable	911401545941	DN593B LED30/830 PSU C D200 WH WB GC	Not applicable
911401541541	DN591B LED20/930 PSU C D125 WH MB GC	Not applicable	911401546041	DN593B LED30/840 PSU C D200 WH WB GC	Not applicable
911401541641	DN591B LED20/940 PSU C D125 WH MB GC	Not applicable	911401546141	DN593B LED30/930 PSU C D200 WH WB GC	Not applicable
911401541741	DN591B LED20/830 PSD C D125 WH WB GC	1%	911401546241	DN593B LED30/940 PSU C D200 WH WB GC	Not applicable
911401541841	DN591B LED20/840 PSD C D125 WH WB GC	1%	911401546341	DN593B LED30/830 PSU C D200 WH MB GC	Not applicable
911401541941	DN591B LED20/930 PSD C D125 WH WB GC	1%	911401546441	DN593B LED30/840 PSU C D200 WH MB GC	Not applicable
911401542041	DN591B LED20/940 PSD C D125 WH WB GC	1%	911401546541	DN593B LED30/930 PSU C D200 WH MB GC	Not applicable
911401542141	DN591B LED20/830 PSD C D125 WH MB GC	1%	911401546641	DN593B LED30/940 PSU C D200 WH MB GC	Not applicable
911401542241	DN591B LED20/840 PSD C D125 WH MB GC	1%	911401546741	DN594B LED40/830 PSU C D200 WH WB GC	Not applicable
911401542341	DN591B LED20/930 PSD C D125 WH MB GC	1%	911401546841	DN594B LED40/840 PSU C D200 WH WB GC	Not applicable
911401542441	DN591B LED20/940 PSD C D125 WH MB GC	1%	911401546941	DN594B LED40/930 PSU C D200 WH WB GC	Not applicable
911401547541	DN588B LED6/830 PSU C D125 C WH WB GM	Not applicable	911401547041	DN594B LED40/940 PSU C D200 WH WB GC	Not applicable
911401547641	DN588B LED6/840 PSU C D125 C WH WB GM	Not applicable	911401547141	DN594B LED40/830 PSU C D200 WH MB GC	Not applicable
911401548741	DN588B LED6/840 PSD C D125 WH WB GM	1%	911401547241	DN594B LED40/840 PSU C D200 WH MB GC	Not applicable
911401549541	DN588B LED6/830 PSU C D125 WH WB WP GM	Not applicable	911401547341	DN594B LED40/930 PSU C D200 WH MB GC	Not applicable
911401549641	DN588B LED6/840 PSU C D125 WH WB WP GM	Not applicable	911401547441	DN594B LED40/940 PSU C D200 WH MB GC	Not applicable
911401550541	DN588B LED6/840 PSD C D125 WH WB WP GM	1%	911401547741	DN589B LED10/830 PSU C D150 WH WB GM	Not applicable
911401540841	DN590B LED20/TWH PSD C D150 WH WB GC	1%	911401547841	DN589B LED10/840 PSU C D150 WH WB GM	Not applicable
911401542541	DN591B LED20/830 PSU C D150 WH WB GC	Not applicable	911401547941	DN590B LED15/830 PSU C D150 WH WB GM	Not applicable
911401542641	DN591B LED20/840 PSU C D150 WH WB GC	Not applicable	911401548041	DN590B LED15/840 PSU C D150 WH WB GM	Not applicable
911401542741	DN591B LED20/930 PSU C D150 WH WB GC	Not applicable	911401548141	DN591B LED20/830 PSU C D200 WH WB GM	Not applicable
911401542841	DN591B LED20/940 PSU C D150 WH WB GC	Not applicable	911401548241	DN591B LED20/840 PSU C D200 WH WB GM	Not applicable
911401542941	DN591B LED20/830 PSU C D150 WH MB GC	Not applicable	911401548341	DN593B LED30/830 PSU C D200 WH WB GM	Not applicable
911401543041	DN591B LED20/840 PSU C D150 WH MB GC	Not applicable	911401548441	DN593B LED30/840 PSU C D200 WH WB GM	Not applicable
911401543141	DN591B LED20/930 PSU C D150 WH MB GC	Not applicable	911401548541	DN594B LED40/830 PSU C D200 WH WB GM	Not applicable
911401543241	DN591B LED20/940 PSU C D150 WH MB GC	Not applicable	911401548641	DN594B LED40/840 PSU C D200 WH WB GM	Not applicable
911401543341	DN591B LED20/830 PSD C D150 WH WB GC	1%	911401548841	DN589B LED10/830 PSD C D150 WH WB GM	1%
911401543441	DN591B LED20/840 PSD C D150 WH WB GC	1%	911401548941	DN589B LED10/840 PSD C D150 WH WB GM	1%
911401543541	DN591B LED20/930 PSD C D150 WH WB GC	1%	911401549041	DN590B LED15/840 PSD C D150 WH WB GM	1%
911401543641	DN591B LED20/940 PSD C D150 WH WB GC	1%	911401549141	DN591B LED20/830 PSD C D200 WH WB GM	1%
911401543741	DN591B LED20/830 PSD C D150 WH MB GC	1%	911401549241	DN591B LED20/840 PSD C D200 WH WB GM	1%

Order Code	Full Product Name	Maximum dim level
911401549341	DN593B LED30/840 PSD C D200 WH WB GM	1%
911401549441	DN594B LED40/840 PSD C D200 WH WB GM	1%
911401549741	DN589B LED10/830 PSU C D150 WH WB WP GM	Not applicable
911401549841	DN589B LED10/840 PSU C D150 WH WB WP GM	Not applicable
911401549941	DN590B LED15/830 PSU C D150 WH WB WP GM	Not applicable
911401550041	DN590B LED15/840 PSU C D150 WH WB WP GM	Not applicable
911401550141	DN591B LED20/830 PSU C D200 WH WB WP GM	Not applicable
911401550241	DN591B LED20/840 PSU C D200 WH WB WP GM	Not applicable
911401550341	DN593B LED30/840 PSU C D200 WH WB WP GM	Not applicable
911401550441	DN594B LED40/840 PSU C D200 WH WB WP GM	Not applicable
911401550641	DN589B LED10/830 PSD C D150 WH WB WP GM	1%
911401550741	DN589B LED10/840 PSD C D150 WH WB WP GM	1%
911401550841	DN590B LED15/840 PSD C D150 WH WB WP GM	1%
911401550941	DN591B LED20/830 PSD C D200 WH WB WP GM	1%
911401551041	DN591B LED20/840 PSD C D200 WH WB WP GM	1%
911401551141	DN593B LED30/840 PSD C D200 WH WB WP GM	1%
911401551241	DN594B LED40/840 PSD C D200 WH WB WP GM	1%
911401551341	DN589B LED10/830 PSU C D150 WH WB CAU	Not applicable
911401551441	DN589B LED10/840 PSU C D150 WH WB CAU	Not applicable
911401551541	DN590B LED15/840 PSU C D150 WH WB CAU	Not applicable
911401551641	DN591B LED20/830 PSU C D200 WH WB CAU	Not applicable
911401551741	DN591B LED20/840 PSU C D200 WH WB CAU	Not applicable
911401551841	DN593B LED30/840 PSU C D200 WH WB CAU	Not applicable
911401551941	DN594B LED40/840 PSU C D200 WH WB CAU	Not applicable
911401552041	DN589B LED10/830 PSD C D150 WH WB CAU	1%
911401552141	DN589B LED10/840 PSD C D150 WH WB CAU	1%
911401552241	DN590B LED15/840 PSD C D150 WH WB CAU	1%
911401552341	DN591B LED20/830 PSD C D200 WH WB CAU	1%
911401552441	DN591B LED20/840 PSD C D200 WH WB CAU	1%
911401552541	DN593B LED30/840 PSD C D200 WH WB CAU	1%
911401552641	DN594B LED40/840 PSD C D200 WH WB CAU	1%
911401552741	DN589B LED10/830 PSU C D150 WH WB WP CAU	Not applicable
911401552841	DN589B LED10/840 PSU C D150 WH WB WP CAU	Not applicable
911401552941	DN590B LED15/840 PSU C D150 WH WB WP CAU	Not applicable
911401553041	DN591B LED20/830 PSU C D200 WH WB WP CAU	Not applicable

Order Code	Full Product Name	Maximum dim level
911401553141	DN591B LED20/840 PSU C D200 WH WB WP CAU	Not applicable
911401553241	DN593B LED30/840 PSU C D200 WH WB WP CAU	Not applicable
911401553341	DN594B LED40/840 PSU C D200 WH WB WP CAU	Not applicable
911401553441	DN589B LED10/830 PSD C D150 WH WB WP CAU	1%
911401553541	DN589B LED10/840 PSD C D150 WH WB WP CAU	1%
911401553641	DN590B LED15/840 PSD C D150 WH WB WP CAU	1%
911401553741	DN591B LED20/830 PSD C D200 WH WB WP CAU	1%
911401553841	DN591B LED20/840 PSD C D200 WH WB WP CAU	1%
911401553941	DN593B LED30/840 PSD C D200 WH WB WP CAU	1%
911401554041	DN594B LED40/840 PSD C D200 WH WB WP CAU	1%
911401554141	DN590B LED15/830 POE C D150 WH WB GM	30%
911401554241	DN590B LED15/840 POE C D150 WH WB GM	30%
911401554341	DN592B LED25/830 POE C D200 WH WB GM	30%
911401554441	DN592B LED25/840 POE C D200 WH WB GM	30%
911401542251	DN591B LED20/TWH PSD C D150 WH MB GM	1%
911401542351	DN591B LED20/TWH PSD C D150 WH WB GC	1%
911401542451	DN591B LED20/TWH PSD C D150 WH MB GC	1%
911401542551	DN591B LED20/TWH PSD C D150 WH WB GM	1%
911401567271	DN588B LED6/940 PSD C D100 WH CAU	-
911401567371	DN589B LED10/940 PSD C D125 WH CAU	-
911401567571	DN590B LED15/940 PSD C D125 WH CAU	-
911401567771	DN589B LED10/940 PSD C D125 WH WP CAU	-
911401567471	DN589B LED10/940 PSD C D150 WH CAU	-
911401567671	DN590B LED15/940 PSD C D150 WH CAU	-
911401567871	DN590B LED15/940 PSD C D150 WH WP CAU	-
911401567971	DN591B LED15/940 PSD C D200 WH CAU	-
911401568071	DN591B LED20/940 PSD C D200 WH CAU	-

Approval and application

Order Code	Full Product Name	Mech. impact protection code	Ingress protection code
911401536641	DN588B LED6/830 PSU C D100 WH WB GC	IK03	IP20
911401536741	DN588B LED6/840 PSU C D100 WH WB GC	IK03	IP20
911401536841	DN588B LED6/930 PSU C D100 WH WB GC	IK03	IP20
911401536941	DN588B LED6/940 PSU C D100 WH WB GC	IK03	IP20
911401537041	DN588B LED6/830 PSU C D100 WH MB GC	IK03	IP20

Order Code	Full Product Name	Mech. impact protection code	Ingress protection code
911401537141	DN588B LED6/840 PSU C D100 WH MB GC	IK03	IP20
911401537241	DN588B LED6/930 PSU C D100 WH MB GC	IK03	IP20
911401537341	DN588B LED6/940 PSU C D100 WH MB GC	IK03	IP20
911401537441	DN589B LED10/830 PSU C D125 WH WB GC	IK03	IP20
911401537541	DN589B LED10/840 PSU C D125 WH WB GC	IK03	IP20

Order Code	Full Product Name	Mech. impact protection code	Ingress protection code
911401537641	DN589B LED10/930 PSU C D125 WH WB GC	IK03	IP20
911401537741	DN589B LED10/940 PSU C D125 WH WB GC	IK03	IP20
911401537841	DN589B LED10/830 PSU C D125 WH MB GC	IK03	IP20
911401537941	DN589B LED10/840 PSU C D125 WH MB GC	IK03	IP20
911401538041	DN589B LED10/930 PSU C D125 WH MB GC	IK03	IP20
911401538141	DN589B LED10/940 PSU C D125 WH MB GC	IK03	IP20
911401538241	DN589B LED10/830 PSD C D125 WH WB GC	IK03	IP20
911401538341	DN589B LED10/840 PSD C D125 WH WB GC	IK03	IP20
911401538441	DN589B LED10/930 PSD C D125 WH WB GC	IK03	IP20
911401538541	DN589B LED10/940 PSD C D125 WH WB GC	IK03	IP20
911401538641	DN589B LED10/830 PSD C D125 WH MB GC	IK03	IP20
911401538741	DN589B LED10/840 PSD C D125 WH MB GC	IK03	IP20
911401538841	DN589B LED10/930 PSD C D125 WH MB GC	IK03	IP20
911401538941	DN589B LED10/940 PSD C D125 WH MB GC	IK03	IP20
911401539041	DN590B LED15/830 PSU C D125 WH WB GC	IK03	IP20
911401539141	DN590B LED15/840 PSU C D125 WH WB GC	IK03	IP20
911401539241	DN590B LED15/930 PSU C D125 WH WB GC	IK03	IP20
911401539341	DN590B LED15/940 PSU C D125 WH WB GC	IK03	IP20
911401539441	DN590B LED15/830 PSU C D125 WH MB GC	IK03	IP20
911401539541	DN590B LED15/840 PSU C D125 WH MB GC	IK03	IP20
911401539641	DN590B LED15/930 PSU C D125 WH MB GC	IK03	IP20
911401539741	DN590B LED15/940 PSU C D125 WH MB GC	IK03	IP20
911401539841	DN590B LED15/830 PSD C D125 WH WB GC	IK03	IP20
911401539941	DN590B LED15/840 PSD C D125 WH WB GC	IK03	IP20
911401540041	DN590B LED15/930 PSD C D125 WH WB GC	IK03	IP20

Order Code	Full Product Name	Mech. impact protection code	Ingress protection code
911401540141	DN590B LED15/940 PSD C D125 WH WB GC	IK03	IP20
911401540241	DN590B LED15/830 PSD C D125 WH MB GC	IK03	IP20
911401540341	DN590B LED15/840 PSD C D125 WH MB GC	IK03	IP20
911401540441	DN590B LED15/930 PSD C D125 WH MB GC	IK03	IP20
911401540541	DN590B LED15/940 PSD C D125 WH MB GC	IK03	IP20
911401540641	DN590B LED15/830 POE C D125 WH WB GC	IK03	IP20
911401540741	DN590B LED15/840 POE C D125 WH WB GC	IK03	IP20
911401540941	DN591B LED20/830 PSU C D125 WH WB GC	IK03	IP20
911401541041	DN591B LED20/840 PSU C D125 WH WB GC	IK03	IP20
911401541141	DN591B LED20/930 PSU C D125 WH WB GC	IK03	IP20
911401541241	DN591B LED20/940 PSU C D125 WH WB GC	IK03	IP20
911401541341	DN591B LED20/830 PSU C D125 WH MB GC	IK03	IP20
911401541441	DN591B LED20/840 PSU C D125 WH MB GC	IK03	IP20
911401541541	DN591B LED20/930 PSU C D125 WH MB GC	IK03	IP20
911401541641	DN591B LED20/940 PSU C D125 WH MB GC	IK03	IP20
911401541741	DN591B LED20/830 PSD C D125 WH WB GC	IK03	IP20
911401541841	DN591B LED20/840 PSD C D125 WH WB GC	IK03	IP20
911401541941	DN591B LED20/930 PSD C D125 WH WB GC	IK03	IP20
911401542041	DN591B LED20/940 PSD C D125 WH WB GC	IK03	IP20
911401542141	DN591B LED20/830 PSD C D125 WH MB GC	IK03	IP20
911401542241	DN591B LED20/840 PSD C D125 WH MB GC	IK03	IP20
911401542341	DN591B LED20/930 PSD C D125 WH MB GC	IK03	IP20
911401542441	DN591B LED20/940 PSD C D125 WH MB GC	IK03	IP20
911401547541	DN588B LED6/830 PSU C D125 C WH WB GM	IK03	IP20
911401547641	DN588B LED6/840 PSU C D125 C WH WB GM	IK03	IP20

Order Code	Full Product Name	Mech. impact protection code	Ingress protection code
911401548741	DN588B LED6/840 PSD C D125 WH WB GM	IK03	IP20
911401549541	DN588B LED6/830 PSU C D125 WH WB WP GM	IK03	IP54/20
911401549641	DN588B LED6/840 PSU C D125 WH WB WP GM	IK03	IP54/20
911401550541	DN588B LED6/840 PSD C D125 WH WB WP GM	IK03	IP54/20
911401540841	DN590B LED20/TWH PSD C D150 WH WB GC	IK03	IP20
911401542541	DN591B LED20/830 PSU C D150 WH WB GC	IK03	IP20
911401542641	DN591B LED20/840 PSU C D150 WH WB GC	IK03	IP20
911401542741	DN591B LED20/930 PSU C D150 WH WB GC	IK03	IP20
911401542841	DN591B LED20/940 PSU C D150 WH WB GC	IK03	IP20
911401542941	DN591B LED20/830 PSU C D150 WH MB GC	IK03	IP20
911401543041	DN591B LED20/840 PSU C D150 WH MB GC	IK03	IP20
911401543141	DN591B LED20/930 PSU C D150 WH MB GC	IK03	IP20
911401543241	DN591B LED20/940 PSU C D150 WH MB GC	IK03	IP20
911401543341	DN591B LED20/830 PSD C D150 WH WB GC	IK03	IP20
911401543441	DN591B LED20/840 PSD C D150 WH WB GC	IK03	IP20
911401543541	DN591B LED20/930 PSD C D150 WH WB GC	IK03	IP20
911401543641	DN591B LED20/940 PSD C D150 WH WB GC	IK03	IP20
911401543741	DN591B LED20/830 PSD C D150 WH MB GC	IK03	IP20
911401543841	DN591B LED20/840 PSD C D150 WH MB GC	IK03	IP20
911401543941	DN591B LED20/930 PSD C D150 WH MB GC	IK03	IP20
911401544041	DN591B LED20/940 PSD C D150 WH MB GC	IK03	IP20
911401544141	DN592B LED25/830 PSU C D150 WH WB GC	IK03	IP20
911401544241	DN592B LED25/840 PSU C D150 WH WB GC	IK03	IP20
911401544341	DN592B LED25/930 PSU C D150 WH WB GC	IK03	IP20
911401544441	DN592B LED25/940 PSU C D150 WH WB GC	IK03	IP20

Order Code	Full Product Name	Mech. impact protection code	Ingress protection code
911401544541	DN592B LED25/830 PSU C D150 WH MB GC	IK03	IP20
911401544641	DN592B LED25/840 PSU C D150 WH MB GC	IK03	IP20
911401544741	DN592B LED25/930 PSU C D150 WH MB GC	IK03	IP20
911401544841	DN592B LED25/940 PSU C D150 WH MB GC	IK03	IP20
911401544941	DN592B LED25/830 PSD C D150 WH WB GC	IK03	IP20
911401545041	DN592B LED25/840 PSD C D150 WH WB GC	IK03	IP20
911401545141	DN592B LED25/930 PSD C D150 WH WB GC	IK03	IP20
911401545241	DN592B LED25/940 PSD C D150 WH WB GC	IK03	IP20
911401545341	DN592B LED25/830 PSD C D150 WH MB GC	IK03	IP20
911401545441	DN592B LED25/840 PSD C D150 WH MB GC	IK03	IP20
911401545541	DN592B LED25/930 PSD C D150 WH MB GC	IK03	IP20
911401545641	DN592B LED25/940 PSD C D150 WH MB GC	IK03	IP20
911401545741	DN592B LED25/830 POE C D150 WH WB GC	IK03	IP20
911401545841	DN592B LED25/840 POE C D150 WH WB GC	IK03	IP20
911401545941	DN593B LED30/830 PSU C D200 WH WB GC	IK03	IP20
911401546041	DN593B LED30/840 PSU C D200 WH WB GC	IK03	IP20
911401546141	DN593B LED30/930 PSU C D200 WH WB GC	IK03	IP20
911401546241	DN593B LED30/940 PSU C D200 WH WB GC	IK03	IP20
911401546341	DN593B LED30/830 PSU C D200 WH MB GC	IK03	IP20
911401546441	DN593B LED30/840 PSU C D200 WH MB GC	IK03	IP20
911401546541	DN593B LED30/930 PSU C D200 WH MB GC	IK03	IP20
911401546641	DN593B LED30/940 PSU C D200 WH MB GC	IK03	IP20
911401546741	DN594B LED40/830 PSU C D200 WH WB GC	IK03	IP20
911401546841	DN594B LED40/840 PSU C D200 WH WB GC	IK03	IP20
911401546941	DN594B LED40/930 PSU C D200 WH WB GC	IK03	IP20

Order Code	Full Product Name	Mech. impact protection code	Ingress protection code
911401547041	DN594B LED40/940 PSU C D200 WH WB GC	IK03	IP20
911401547141	DN594B LED40/830 PSU C D200 WH MB GC	IK03	IP20
911401547241	DN594B LED40/840 PSU C D200 WH MB GC	IK03	IP20
911401547341	DN594B LED40/930 PSU C D200 WH MB GC	IK03	IP20
911401547441	DN594B LED40/940 PSU C D200 WH MB GC	IK03	IP20
911401547741	DN589B LED10/830 PSU C D150 WH WB GM	IK03	IP20
911401547841	DN589B LED10/840 PSU C D150 WH WB GM	IK03	IP20
911401547941	DN590B LED15/830 PSU C D150 WH WB GM	IK03	IP20
911401548041	DN590B LED15/840 PSU C D150 WH WB GM	IK03	IP20
911401548141	DN591B LED20/830 PSU C D200 WH WB GM	IK03	IP20
911401548241	DN591B LED20/840 PSU C D200 WH WB GM	IK03	IP20
911401548341	DN593B LED30/830 PSU C D200 WH WB GM	IK03	IP20
911401548441	DN593B LED30/840 PSU C D200 WH WB GM	IK03	IP20
911401548541	DN594B LED40/830 PSU C D200 WH WB GM	IK03	IP20
911401548641	DN594B LED40/840 PSU C D200 WH WB GM	IK03	IP20
911401548841	DN589B LED10/830 PSD C D150 WH WB GM	IK03	IP20
911401548941	DN589B LED10/840 PSD C D150 WH WB GM	IK03	IP20
911401549041	DN590B LED15/840 PSD C D150 WH WB GM	IK03	IP20
911401549141	DN591B LED20/830 PSD C D200 WH WB GM	IK03	IP20
911401549241	DN591B LED20/840 PSD C D200 WH WB GM	IK03	IP20
911401549341	DN593B LED30/840 PSD C D200 WH WB GM	IK03	IP20
911401549441	DN594B LED40/840 PSD C D200 WH WB GM	IK03	IP20
911401549741	DN589B LED10/830 PSU C D150 WH WB WP GM	IK03	IP54/20
911401549841	DN589B LED10/840 PSU C D150 WH WB WP GM	IK03	IP54/20
911401549941	DN590B LED15/830 PSU C D150 WH WB WP GM	IK03	IP54/20

Order Code	Full Product Name	Mech. impact protection code	Ingress protection code
911401550041	DN590B LED15/840 PSU C D150 WH WB WP GM	IK03	IP54/20
911401550141	DN591B LED20/830 PSU C D200 WH WB WP GM	IK03	IP54/20
911401550241	DN591B LED20/840 PSU C D200 WH WB WP GM	IK03	IP54/20
911401550341	DN593B LED30/840 PSU C D200 WH WB WP GM	IK03	IP54/20
911401550441	DN594B LED40/840 PSU C D200 WH WB WP GM	IK03	IP54/20
911401550641	DN589B LED10/830 PSD C D150 WH WB WP GM	IK03	IP54/20
911401550741	DN589B LED10/840 PSD C D150 WH WB WP GM	IK03	IP54/20
911401550841	DN590B LED15/840 PSD C D150 WH WB WP GM	IK03	IP54/20
911401550941	DN591B LED20/830 PSD C D200 WH WB WP GM	IK03	IP54/20
911401551041	DN591B LED20/840 PSD C D200 WH WB WP GM	IK03	IP54/20
911401551141	DN593B LED30/840 PSD C D200 WH WB WP GM	IK03	IP54/20
911401551241	DN594B LED40/840 PSD C D200 WH WB WP GM	IK03	IP54/20
911401551341	DN589B LED10/830 PSU C D150 WH WB CAU	IK03	IP20
911401551441	DN589B LED10/840 PSU C D150 WH WB CAU	IK03	IP20
911401551541	DN590B LED15/840 PSU C D150 WH WB CAU	IK03	IP20
911401551641	DN591B LED20/830 PSU C D200 WH WB CAU	IK03	IP20
911401551741	DN591B LED20/840 PSU C D200 WH WB CAU	IK03	IP20
911401551841	DN593B LED30/840 PSU C D200 WH WB CAU	IK03	IP20
911401551941	DN594B LED40/840 PSU C D200 WH WB CAU	IK03	IP20
911401552041	DN589B LED10/830 PSD C D150 WH WB CAU	IK03	IP20
911401552141	DN589B LED10/840 PSD C D150 WH WB CAU	IK03	IP20
911401552241	DN590B LED15/840 PSD C D150 WH WB CAU	IK03	IP20
911401552341	DN591B LED20/830 PSD C D200 WH WB CAU	IK03	IP20
911401552441	DN591B LED20/840 PSD C D200 WH WB CAU	IK03	IP20
911401552541	DN593B LED30/840 PSD C D200 WH WB CAU	IK03	IP20

Order Code	Full Product Name	Mech. impact protection code	Ingress protection code
911401552641	DN594B LED40/840 PSD C D200 WH WB CAU	IK03	IP20
911401552741	DN589B LED10/830 PSU C D150 WH WB WP CAU	IK03	IP54/20
911401552841	DN589B LED10/840 PSU C D150 WH WB WP CAU	IK03	IP54/20
911401552941	DN590B LED15/840 PSU C D150 WH WB WP CAU	IK03	IP54/20
911401553041	DN591B LED20/830 PSU C D200 WH WB WP CAU	IK03	IP54/20
911401553141	DN591B LED20/840 PSU C D200 WH WB WP CAU	IK03	IP54/20
911401553241	DN593B LED30/840 PSU C D200 WH WB WP CAU	IK03	IP54/20
911401553341	DN594B LED40/840 PSU C D200 WH WB WP CAU	IK03	IP54/20
911401553441	DN589B LED10/830 PSD C D150 WH WB WP CAU	IK03	IP54/20
911401553541	DN589B LED10/840 PSD C D150 WH WB WP CAU	IK03	IP54/20
911401553641	DN590B LED15/840 PSD C D150 WH WB WP CAU	IK03	IP54/20
911401553741	DN591B LED20/830 PSD C D200 WH WB WP CAU	IK03	IP54/20
911401553841	DN591B LED20/840 PSD C D200 WH WB WP CAU	IK03	IP54/20
911401553941	DN593B LED30/840 PSD C D200 WH WB WP CAU	IK03	IP54/20
911401554041	DN594B LED40/840 PSD C D200 WH WB WP CAU	IK03	IP54/20
911401554141	DN590B LED15/830 POE C D150 WH WB GM	IK03	IP20

Order Code	Full Product Name	Mech. impact protection code	Ingress protection code
911401554241	DN590B LED15/840 POE C D150 WH WB GM	IK03	IP20
911401554341	DN592B LED25/830 POE C D200 WH WB GM	IK03	IP20
911401554441	DN592B LED25/840 POE C D200 WH WB GM	IK03	IP20
911401542251	DN591B LED20/TWH PSD C D150 WH MB GM	IK03	IP20
911401542351	DN591B LED20/TWH PSD C D150 WH WB GC	IK03	IP20
911401542451	DN591B LED20/TWH PSD C D150 WH MB GC	IK03	IP20
911401542551	DN591B LED20/TWH PSD C D150 WH WB GM	IK03	IP20
911401567271	DN588B LED6/940 PSD C D100 WH CAU	IK02	IP20
911401567371	DN589B LED10/940 PSD C D125 WH CAU	IK02	IP20
911401567571	DN590B LED15/940 PSD C D125 WH CAU	IK02	IP20
911401567771	DN589B LED10/940 PSD C D125 WH WP CAU	IK02	IP20/54
911401567471	DN589B LED10/940 PSD C D150 WH CAU	IK02	IP20
911401567671	DN590B LED15/940 PSD C D150 WH CAU	IK02	IP20
911401567871	DN590B LED15/940 PSD C D150 WH WP CAU	IK02	IP20/54
911401567971	DN591B LED15/940 PSD C D200 WH CAU	IK02	IP20
911401568071	DN591B LED20/940 PSD C D200 WH CAU	IK02	IP20

Controls and dimming

Order Code	Full Product Name	Dimmable
911401536641	DN588B LED6/830 PSU C D100 WH WB GC	No
911401536741	DN588B LED6/840 PSU C D100 WH WB GC	No
911401536841	DN588B LED6/930 PSU C D100 WH WB GC	No
911401536941	DN588B LED6/940 PSU C D100 WH WB GC	No
911401537041	DN588B LED6/830 PSU C D100 WH MB GC	No
911401537141	DN588B LED6/840 PSU C D100 WH MB GC	No
911401537241	DN588B LED6/930 PSU C D100 WH MB GC	No
911401537341	DN588B LED6/940 PSU C D100 WH MB GC	No
911401537441	DN589B LED10/830 PSU C D125 WH WB GC	No
911401537541	DN589B LED10/840 PSU C D125 WH WB GC	No
911401537641	DN589B LED10/930 PSU C D125 WH WB GC	No
911401537741	DN589B LED10/940 PSU C D125 WH WB GC	No
911401537841	DN589B LED10/830 PSU C D125 WH MB GC	No
911401537941	DN589B LED10/840 PSU C D125 WH MB GC	No

Order Code	Full Product Name	Dimmable
911401538041	DN589B LED10/930 PSU C D125 WH MB GC	No
911401538141	DN589B LED10/940 PSU C D125 WH MB GC	No
911401538241	DN589B LED10/830 PSD C D125 WH WB GC	Yes
911401538341	DN589B LED10/840 PSD C D125 WH WB GC	Yes
911401538441	DN589B LED10/930 PSD C D125 WH WB GC	Yes
911401538541	DN589B LED10/940 PSD C D125 WH WB GC	Yes
911401538641	DN589B LED10/830 PSD C D125 WH MB GC	Yes
911401538741	DN589B LED10/840 PSD C D125 WH MB GC	Yes
911401538841	DN589B LED10/930 PSD C D125 WH MB GC	Yes
911401538941	DN589B LED10/940 PSD C D125 WH MB GC	Yes
911401539041	DN590B LED15/830 PSU C D125 WH WB GC	No
911401539141	DN590B LED15/840 PSU C D125 WH WB GC	No
911401539241	DN590B LED15/930 PSU C D125 WH WB GC	No
911401539341	DN590B LED15/940 PSU C D125 WH WB GC	No



Order Code	Full Product Name	Dimmable	Order Code	Full Product Name	Dimmable
911401539441	DN590B LED15/830 PSU C D125 WH MB GC	No	911401544041	DN591B LED20/940 PSD C D150 WH MB GC	Yes
911401539541	DN590B LED15/840 PSU C D125 WH MB GC	No	911401544141	DN592B LED25/830 PSU C D150 WH WB GC	No
911401539641	DN590B LED15/930 PSU C D125 WH MB GC	No	911401544241	DN592B LED25/840 PSU C D150 WH WB GC	No
911401539741	DN590B LED15/940 PSU C D125 WH MB GC	No	911401544341	DN592B LED25/930 PSU C D150 WH WB GC	No
911401539841	DN590B LED15/830 PSD C D125 WH WB GC	Yes	911401544441	DN592B LED25/940 PSU C D150 WH WB GC	No
911401539941	DN590B LED15/840 PSD C D125 WH WB GC	Yes	911401544541	DN592B LED25/830 PSU C D150 WH MB GC	No
911401540041	DN590B LED15/930 PSD C D125 WH WB GC	Yes	911401544641	DN592B LED25/840 PSU C D150 WH MB GC	No
911401540141	DN590B LED15/940 PSD C D125 WH WB GC	Yes	911401544741	DN592B LED25/930 PSU C D150 WH MB GC	No
911401540241	DN590B LED15/830 PSD C D125 WH MB GC	Yes	911401544841	DN592B LED25/940 PSU C D150 WH MB GC	No
911401540341	DN590B LED15/840 PSD C D125 WH MB GC	Yes	911401544941	DN592B LED25/830 PSD C D150 WH WB GC	Yes
911401540441	DN590B LED15/930 PSD C D125 WH MB GC	Yes	911401545041	DN592B LED25/840 PSD C D150 WH WB GC	Yes
911401540541	DN590B LED15/940 PSD C D125 WH MB GC	Yes	911401545141	DN592B LED25/930 PSD C D150 WH WB GC	Yes
911401540641	DN590B LED15/830 POE C D125 WH WB GC	Yes	911401545241	DN592B LED25/940 PSD C D150 WH WB GC	Yes
911401540741	DN590B LED15/840 POE C D125 WH WB GC	Yes	911401545341	DN592B LED25/830 PSD C D150 WH MB GC	Yes
911401540941	DN591B LED20/830 PSU C D125 WH WB GC	No	911401545441	DN592B LED25/840 PSD C D150 WH MB GC	Yes
911401541041	DN591B LED20/840 PSU C D125 WH WB GC	No	911401545541	DN592B LED25/930 PSD C D150 WH MB GC	Yes
911401541141	DN591B LED20/930 PSU C D125 WH WB GC	No	911401545641	DN592B LED25/940 PSD C D150 WH MB GC	Yes
911401541241	DN591B LED20/940 PSU C D125 WH WB GC	No	911401545741	DN592B LED25/830 POE C D150 WH WB GC	Yes
911401541341	DN591B LED20/830 PSU C D125 WH MB GC	No	911401545841	DN592B LED25/840 POE C D150 WH WB GC	Yes
911401541441	DN591B LED20/840 PSU C D125 WH MB GC	No	911401545941	DN593B LED30/830 PSU C D200 WH WB GC	No
911401541541	DN591B LED20/930 PSU C D125 WH MB GC	No	911401546041	DN593B LED30/840 PSU C D200 WH WB GC	No
911401541641	DN591B LED20/940 PSU C D125 WH MB GC	No	911401546141	DN593B LED30/930 PSU C D200 WH WB GC	No
911401541741	DN591B LED20/830 PSD C D125 WH WB GC	Yes	911401546241	DN593B LED30/940 PSU C D200 WH WB GC	No
911401541841	DN591B LED20/840 PSD C D125 WH WB GC	Yes	911401546341	DN593B LED30/830 PSU C D200 WH MB GC	No
911401541941	DN591B LED20/930 PSD C D125 WH WB GC	Yes	911401546441	DN593B LED30/840 PSU C D200 WH MB GC	No
911401542041	DN591B LED20/940 PSD C D125 WH WB GC	Yes	911401546541	DN593B LED30/930 PSU C D200 WH MB GC	No
911401542141	DN591B LED20/830 PSD C D125 WH MB GC	Yes	911401546641	DN593B LED30/940 PSU C D200 WH MB GC	No
911401542241	DN591B LED20/840 PSD C D125 WH MB GC	Yes	911401546741	DN594B LED40/830 PSU C D200 WH WB GC	No
911401542341	DN591B LED20/930 PSD C D125 WH MB GC	Yes	911401546841	DN594B LED40/840 PSU C D200 WH WB GC	No
911401542441	DN591B LED20/940 PSD C D125 WH MB GC	Yes	911401546941	DN594B LED40/930 PSU C D200 WH WB GC	No
911401547541	DN588B LED6/830 PSU C D125 C WH WB GM	No	911401547041	DN594B LED40/940 PSU C D200 WH WB GC	No
911401547641	DN588B LED6/840 PSU C D125 C WH WB GM	No	911401547141	DN594B LED40/830 PSU C D200 WH MB GC	No
911401547841	DN588B LED6/840 PSD C D125 WH WB GM	Yes	911401547241	DN594B LED40/840 PSU C D200 WH MB GC	No
911401549541	DN588B LED6/830 PSU C D125 WH WB WP GM	No	911401547341	DN594B LED40/930 PSU C D200 WH MB GC	No
911401549641	DN588B LED6/840 PSU C D125 WH WB WP GM	No	911401547441	DN594B LED40/940 PSU C D200 WH MB GC	No
911401550541	DN588B LED6/840 PSD C D125 WH WB WP GM	Yes	911401547741	DN589B LED10/830 PSU C D150 WH WB GM	No
911401540841	DN590B LED20/TWH PSD C D150 WH WB GC	Yes	911401547841	DN589B LED10/840 PSU C D150 WH WB GM	No
911401542541	DN591B LED20/830 PSU C D150 WH WB GC	No	911401547941	DN590B LED15/830 PSU C D150 WH WB GM	No
911401542641	DN591B LED20/840 PSU C D150 WH WB GC	No	911401548041	DN590B LED15/840 PSU C D150 WH WB GM	No
911401542741	DN591B LED20/930 PSU C D150 WH WB GC	No	911401548141	DN591B LED20/830 PSU C D200 WH WB GM	No
911401542841	DN591B LED20/940 PSU C D150 WH WB GC	No	911401548241	DN591B LED20/840 PSU C D200 WH WB GM	No
911401542941	DN591B LED20/830 PSU C D150 WH MB GC	No	911401548341	DN593B LED30/830 PSU C D200 WH WB GM	No
911401543041	DN591B LED20/840 PSU C D150 WH MB GC	No	911401548441	DN593B LED30/840 PSU C D200 WH WB GM	No
911401543141	DN591B LED20/930 PSU C D150 WH MB GC	No	911401548541	DN594B LED40/830 PSU C D200 WH WB GM	No
911401543241	DN591B LED20/940 PSU C D150 WH MB GC	No	911401548641	DN594B LED40/840 PSU C D200 WH WB GM	No
911401543341	DN591B LED20/830 PSD C D150 WH WB GC	Yes	911401548841	DN589B LED10/830 PSD C D150 WH WB GM	Yes
911401543441	DN591B LED20/840 PSD C D150 WH WB GC	Yes	911401548941	DN589B LED10/840 PSD C D150 WH WB GM	Yes
911401543541	DN591B LED20/930 PSD C D150 WH WB GC	Yes	911401549041	DN590B LED15/840 PSD C D150 WH WB GM	Yes
911401543641	DN591B LED20/940 PSD C D150 WH WB GC	Yes	911401549141	DN591B LED20/830 PSD C D200 WH WB GM	Yes
911401543741	DN591B LED20/830 PSD C D150 WH MB GC	Yes	911401549241	DN591B LED20/840 PSD C D200 WH WB GM	Yes
911401543841	DN591B LED20/840 PSD C D150 WH MB GC	Yes	911401549341	DN593B LED30/840 PSD C D200 WH WB GM	Yes
911401543941	DN591B LED20/930 PSD C D150 WH MB GC	Yes	911401549441	DN594B LED40/840 PSD C D200 WH WB GM	Yes

Order Code	Full Product Name	Dimmable	Order Code	Full Product Name	Dimmable
911401549741	DN589B LED10/830 PSU C D150 WH WB WP GM	No	911401552841	DN589B LED10/840 PSU C D150 WH WB WP CAU	No
911401549841	DN589B LED10/840 PSU C D150 WH WB WP GM	No	911401552941	DN590B LED15/840 PSU C D150 WH WB WP CAU	No
911401549941	DN590B LED15/830 PSU C D150 WH WB WP GM	No	911401553041	DN591B LED20/830 PSU C D200 WH WB WP CAU	No
911401550041	DN590B LED15/840 PSU C D150 WH WB WP GM	No	911401553141	DN591B LED20/840 PSU C D200 WH WB WP CAU	No
911401550141	DN591B LED20/830 PSU C D200 WH WB WP GM	No	911401553241	DN593B LED30/840 PSU C D200 WH WB WP CAU	No
911401550241	DN591B LED20/840 PSU C D200 WH WB WP GM	No	911401553341	DN594B LED40/840 PSU C D200 WH WB WP CAU	No
911401550341	DN593B LED30/840 PSU C D200 WH WB WP GM	No	911401553441	DN589B LED10/830 PSD C D150 WH WB WP CAU	Yes
911401550441	DN594B LED40/840 PSU C D200 WH WB WP GM	No	911401553541	DN589B LED10/840 PSD C D150 WH WB WP CAU	Yes
911401550641	DN589B LED10/830 PSD C D150 WH WB WP GM	Yes	911401553641	DN590B LED15/840 PSD C D150 WH WB WP CAU	Yes
911401550741	DN589B LED10/840 PSD C D150 WH WB WP GM	Yes	911401553741	DN591B LED20/830 PSD C D200 WH WB WP CAU	Yes
911401550841	DN590B LED15/840 PSD C D150 WH WB WP GM	Yes	911401553841	DN591B LED20/840 PSD C D200 WH WB WP CAU	Yes
911401550941	DN591B LED20/830 PSD C D200 WH WB WP GM	Yes	911401553941	DN593B LED30/840 PSD C D200 WH WB WP CAU	Yes
911401551041	DN591B LED20/840 PSD C D200 WH WB WP GM	Yes	911401554041	DN594B LED40/840 PSD C D200 WH WB WP CAU	Yes
911401551141	DN593B LED30/840 PSD C D200 WH WB WP GM	Yes	911401554141	DN590B LED15/830 POE C D150 WH WB GM	Yes
911401551241	DN594B LED40/840 PSD C D200 WH WB WP GM	Yes	911401554241	DN590B LED15/840 POE C D150 WH WB GM	Yes
911401551341	DN589B LED10/830 PSU C D150 WH WB CAU	No	911401554341	DN592B LED25/830 POE C D200 WH WB GM	Yes
911401551441	DN589B LED10/840 PSU C D150 WH WB CAU	No	911401554441	DN592B LED25/840 POE C D200 WH WB GM	Yes
911401551541	DN590B LED15/840 PSU C D150 WH WB CAU	No	911401542251	DN591B LED20/TWH PSD C D150 WH MB GM	Yes
911401551641	DN591B LED20/830 PSU C D200 WH WB CAU	No	911401542351	DN591B LED20/TWH PSD C D150 WH WB GC	Yes
911401551741	DN591B LED20/840 PSU C D200 WH WB CAU	No	911401542451	DN591B LED20/TWH PSD C D150 WH MB GC	Yes
911401551841	DN593B LED30/840 PSU C D200 WH WB CAU	No	911401542551	DN591B LED20/TWH PSD C D150 WH WB GM	Yes
911401551941	DN594B LED40/840 PSU C D200 WH WB CAU	No	911401567271	DN588B LED6/940 PSD C D100 WH CAU	Yes
911401552041	DN589B LED10/830 PSD C D150 WH WB CAU	Yes	911401567371	DN589B LED10/940 PSD C D125 WH CAU	Yes
911401552141	DN589B LED10/840 PSD C D150 WH WB CAU	Yes	911401567571	DN590B LED15/940 PSD C D125 WH CAU	Yes
911401552241	DN590B LED15/840 PSD C D150 WH WB CAU	Yes	911401567771	DN589B LED10/940 PSD C D125 WH WP CAU	Yes
911401552341	DN591B LED20/830 PSD C D200 WH WB CAU	Yes	911401567471	DN589B LED10/940 PSD C D150 WH CAU	Yes
911401552441	DN591B LED20/840 PSD C D200 WH WB CAU	Yes	911401567671	DN590B LED15/940 PSD C D150 WH CAU	Yes
911401552541	DN593B LED30/840 PSD C D200 WH WB CAU	Yes	911401567871	DN590B LED15/940 PSD C D150 WH WP CAU	Yes
911401552641	DN594B LED40/840 PSD C D200 WH WB CAU	Yes	911401567971	DN591B LED15/940 PSD C D200 WH CAU	Yes
911401552741	DN589B LED10/830 PSU C D150 WH WB WP CAU	No	911401568071	DN591B LED20/940 PSD C D200 WH CAU	Yes

General information (1/2)

Order Code	Full Product Name	Beam angle of light		Protection class IEC	Optical			Flammability mark	Glow-wire test
		source	IEC		cover/lens type	Driver included	ENEC mark		
911401536641	DN588B LED6/830 PSU C D100 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401536741	DN588B LED6/840 PSU C D100 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401536841	DN588B LED6/930 PSU C D100 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401536941	DN588B LED6/940 PSU C D100 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401537041	DN588B LED6/830 PSU C D100 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401537141	DN588B LED6/840 PSU C D100 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401537241	DN588B LED6/930 PSU C D100 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	

Order Code	Full Product Name	Beam	Protection class	Optical			ENEC	Flammability mark	Glow-wire test
		angle of light source		IEC	cover/lens type	Driver included			
911401537341	DN588B LED6/940 PSU C D100 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401537441	DN589B LED10/830 PSU C D125 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401537541	DN589B LED10/840 PSU C D125 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401537641	DN589B LED10/930 PSU C D125 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401537741	DN589B LED10/940 PSU C D125 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401537841	DN589B LED10/830 PSU C D125 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401537941	DN589B LED10/840 PSU C D125 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401538041	DN589B LED10/930 PSU C D125 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401538141	DN589B LED10/940 PSU C D125 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401538241	DN589B LED10/830 PSD C D125 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401538341	DN589B LED10/840 PSD C D125 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401538441	DN589B LED10/930 PSD C D125 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401538541	DN589B LED10/940 PSD C D125 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401538641	DN589B LED10/830 PSD C D125 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401538741	DN589B LED10/840 PSD C D125 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401538841	DN589B LED10/930 PSD C D125 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401538941	DN589B LED10/940 PSD C D125 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401539041	DN590B LED15/830 PSU C D125 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401539141	DN590B LED15/840 PSU C D125 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401539241	DN590B LED15/930 PSU C D125 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401539341	DN590B LED15/940 PSU C D125 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401539441	DN590B LED15/830 PSU C D125 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401539541	DN590B LED15/840 PSU C D125 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401539641	DN590B LED15/930 PSU C D125 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	

Order Code	Full Product Name	Beam	Protection class	Optical			ENEC	Flammability mark	Glow-wire test
		angle of light source		IEC	cover/lens type	Driver included			
911401539741	DN590B LED15/940 PSU C D125 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401539841	DN590B LED15/830 PSD C D125 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401539941	DN590B LED15/840 PSD C D125 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401540041	DN590B LED15/930 PSD C D125 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401540141	DN590B LED15/940 PSD C D125 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401540241	DN590B LED15/830 PSD C D125 WH MB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401540341	DN590B LED15/840 PSD C D125 WH MB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401540441	DN590B LED15/930 PSD C D125 WH MB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401540541	DN590B LED15/940 PSD C D125 WH MB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401540641	DN590B LED15/830 POE C D125 WH WB GC	-	Safety class III	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401540741	DN590B LED15/840 POE C D125 WH WB GC	-	Safety class III	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401540941	DN591B LED20/830 PSU C D125 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401541041	DN591B LED20/840 PSU C D125 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401541141	DN591B LED20/930 PSU C D125 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401541241	DN591B LED20/940 PSU C D125 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401541341	DN591B LED20/830 PSU C D125 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401541441	DN591B LED20/840 PSU C D125 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401541541	DN591B LED20/930 PSU C D125 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401541641	DN591B LED20/940 PSU C D125 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401541741	DN591B LED20/830 PSD C D125 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401541841	DN591B LED20/840 PSD C D125 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401541941	DN591B LED20/930 PSD C D125 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401542041	DN591B LED20/940 PSD C D125 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401542141	DN591B LED20/830 PSD C D125 WH MB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	

Order Code	Full Product Name	Beam angle of light source	Protection class IEC	Optical			ENEC mark	Flammability mark	Glow-wire test
				cover/lens type	Driver included				
911401542241	DN591B LED20/840 PSD C D125 WH MB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401542341	DN591B LED20/930 PSD C D125 WH MB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401542441	DN591B LED20/940 PSD C D125 WH MB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401547541	DN588B LED6/830 PSU C D125 C WH WB GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401547641	DN588B LED6/840 PSU C D125 C WH WB GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401548741	DN588B LED6/840 PSD C D125 WH WB GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401549541	DN588B LED6/830 PSU C D125 WH WB WP GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401549641	DN588B LED6/840 PSU C D125 WH WB WP GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401550541	DN588B LED6/840 PSD C D125 WH WB WP GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401540841	DN590B LED20/TWH PSD C D150 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401542541	DN591B LED20/830 PSU C D150 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401542641	DN591B LED20/840 PSU C D150 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401542741	DN591B LED20/930 PSU C D150 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401542841	DN591B LED20/940 PSU C D150 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401542941	DN591B LED20/830 PSU C D150 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401543041	DN591B LED20/840 PSU C D150 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401543141	DN591B LED20/930 PSU C D150 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401543241	DN591B LED20/940 PSU C D150 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401543341	DN591B LED20/830 PSD C D150 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401543441	DN591B LED20/840 PSD C D150 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401543541	DN591B LED20/930 PSD C D150 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401543641	DN591B LED20/940 PSD C D150 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401543741	DN591B LED20/830 PSD C D150 WH MB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401543841	DN591B LED20/840 PSD C D150 WH MB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	

Order Code	Full Product Name	Beam	Protection class	Optical			ENEC	Flammability mark	Glow-wire test
		angle of light source		IEC	cover/lens type	Driver included			
911401543941	DN591B LED20/930 PSD C D150 WH MB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401544041	DN591B LED20/940 PSD C D150 WH MB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401544141	DN592B LED25/830 PSU C D150 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401544241	DN592B LED25/840 PSU C D150 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401544341	DN592B LED25/930 PSU C D150 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401544441	DN592B LED25/940 PSU C D150 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401544541	DN592B LED25/830 PSU C D150 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401544641	DN592B LED25/840 PSU C D150 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401544741	DN592B LED25/930 PSU C D150 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401544841	DN592B LED25/940 PSU C D150 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401544941	DN592B LED25/830 PSD C D150 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401545041	DN592B LED25/840 PSD C D150 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401545141	DN592B LED25/930 PSD C D150 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401545241	DN592B LED25/940 PSD C D150 WH WB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401545341	DN592B LED25/830 PSD C D150 WH MB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401545441	DN592B LED25/840 PSD C D150 WH MB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401545541	DN592B LED25/930 PSD C D150 WH MB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401545641	DN592B LED25/940 PSD C D150 WH MB GC	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401545741	DN592B LED25/830 POE C D150 WH WB GC	-	Safety class III	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401545841	DN592B LED25/840 POE C D150 WH WB GC	-	Safety class III	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401545941	DN593B LED30/830 PSU C D200 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401546041	DN593B LED30/840 PSU C D200 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401546141	DN593B LED30/930 PSU C D200 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401546241	DN593B LED30/940 PSU C D200 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	

Order Code	Full Product Name	Beam	Protection class	Optical			ENEC	Flammability mark	Glow-wire test
		angle of light source		IEC	cover/lens type	Driver included			
911401546341	DN593B LED30/830 PSU C D200 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401546441	DN593B LED30/840 PSU C D200 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401546541	DN593B LED30/930 PSU C D200 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401546641	DN593B LED30/940 PSU C D200 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401546741	DN594B LED40/830 PSU C D200 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401546841	DN594B LED40/840 PSU C D200 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401546941	DN594B LED40/930 PSU C D200 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401547041	DN594B LED40/940 PSU C D200 WH WB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401547141	DN594B LED40/830 PSU C D200 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401547241	DN594B LED40/840 PSU C D200 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401547341	DN594B LED40/930 PSU C D200 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401547441	DN594B LED40/940 PSU C D200 WH MB GC	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401547741	DN589B LED10/830 PSU C D150 WH WB GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401547841	DN589B LED10/840 PSU C D150 WH WB GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401547941	DN590B LED15/830 PSU C D150 WH WB GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401548041	DN590B LED15/840 PSU C D150 WH WB GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401548141	DN591B LED20/830 PSU C D200 WH WB GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401548241	DN591B LED20/840 PSU C D200 WH WB GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401548341	DN593B LED30/830 PSU C D200 WH WB GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401548441	DN593B LED30/840 PSU C D200 WH WB GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401548541	DN594B LED40/830 PSU C D200 WH WB GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401548641	DN594B LED40/840 PSU C D200 WH WB GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401548841	DN589B LED10/830 PSD C D150 WH WB GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401548941	DN589B LED10/840 PSD C D150 WH WB GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	

Order Code	Full Product Name	Beam angle of light source	Protection class IEC	Optical			ENEC mark	Flammability mark	Glow-wire test
				cover/lens type	Driver included				
911401549041	DN590B LED15/840 PSD C D150 WH WB GM	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401549141	DN591B LED20/830 PSD C D200 WH WB GM	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401549241	DN591B LED20/840 PSD C D200 WH WB GM	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401549341	DN593B LED30/840 PSD C D200 WH WB GM	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401549441	DN594B LED40/840 PSD C D200 WH WB GM	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401549741	DN589B LED10/830 PSU C D150 WH WB WP GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401549841	DN589B LED10/840 PSU C D150 WH WB WP GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401549941	DN590B LED15/830 PSU C D150 WH WB WP GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401550041	DN590B LED15/840 PSU C D150 WH WB WP GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401550141	DN591B LED20/830 PSU C D200 WH WB WP GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401550241	DN591B LED20/840 PSU C D200 WH WB WP GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401550341	DN593B LED30/840 PSU C D200 WH WB WP GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401550441	DN594B LED40/840 PSU C D200 WH WB WP GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401550641	DN589B LED10/830 PSD C D150 WH WB WP GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401550741	DN589B LED10/840 PSD C D150 WH WB WP GM	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401550841	DN590B LED15/840 PSD C D150 WH WB WP GM	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401550941	DN591B LED20/830 PSD C D200 WH WB WP GM	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401551041	DN591B LED20/840 PSD C D200 WH WB WP GM	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401551141	DN593B LED30/840 PSD C D200 WH WB WP GM	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401551241	DN594B LED40/840 PSD C D200 WH WB WP GM	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401551341	DN589B LED10/830 PSU C D150 WH WB CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401551441	DN589B LED10/840 PSU C D150 WH WB CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401551541	DN590B LED15/840 PSU C D150 WH WB CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401551641	DN591B LED20/830 PSU C D200 WH WB CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	



Order Code	Full Product Name	Beam angle of light source	Protection class IEC	Optical			ENEC mark	Flammability mark	Glow-wire test
				cover/lens type	Driver included				
911401551741	DN591B LED20/840 PSU C D200 WH WB CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401551841	DN593B LED30/840 PSU C D200 WH WB CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401551941	DN594B LED40/840 PSU C D200 WH WB CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401552041	DN589B LED10/830 PSD C D150 WH WB CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401552141	DN589B LED10/840 PSD C D150 WH WB CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401552241	DN590B LED15/840 PSD C D150 WH WB CAU	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401552341	DN591B LED20/830 PSD C D200 WH WB CAU	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401552441	DN591B LED20/840 PSD C D200 WH WB CAU	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401552541	DN593B LED30/840 PSD C D200 WH WB CAU	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401552641	DN594B LED40/840 PSD C D200 WH WB CAU	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401552741	DN589B LED10/830 PSU C D150 WH WB WP CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401552841	DN589B LED10/840 PSU C D150 WH WB WP CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401552941	DN590B LED15/840 PSU C D150 WH WB WP CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401553041	DN591B LED20/830 PSU C D200 WH WB WP CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401553141	DN591B LED20/840 PSU C D200 WH WB WP CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401553241	DN593B LED30/840 PSU C D200 WH WB WP CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401553341	DN594B LED40/840 PSU C D200 WH WB WP CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401553441	DN589B LED10/830 PSD C D150 WH WB WP CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401553541	DN589B LED10/840 PSD C D150 WH WB WP CAU	-	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401553641	DN590B LED15/840 PSD C D150 WH WB WP CAU	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401553741	DN591B LED20/830 PSD C D200 WH WB WP CAU	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401553841	DN591B LED20/840 PSD C D200 WH WB WP CAU	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401553941	DN593B LED30/840 PSD C D200 WH WB WP CAU	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	
911401554041	DN594B LED40/840 PSD C D200 WH WB WP CAU	-	Safety class I	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s	

Order Code	Full Product Name	Beam angle of light source	Protection class IEC	Optical cover/lens type	Driver included	ENEC mark	Flammability mark	Glow-wire test
911401554141	DN590B LED15/830 POE C D150 WH WB GM	-	Safety class III	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s
911401554241	DN590B LED15/840 POE C D150 WH WB GM	-	Safety class III	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s
911401554341	DN592B LED25/830 POE C D200 WH WB GM	-	Safety class III	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s
911401554441	DN592B LED25/840 POE C D200 WH WB GM	-	Safety class III	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s
911401542251	DN591B LED20/TWH PSD C D150 WH MB GM	32 °	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s
911401542351	DN591B LED20/TWH PSD C D150 WH WB GC	62 °	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s
911401542451	DN591B LED20/TWH PSD C D150 WH MB GC	32 °	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s
911401542551	DN591B LED20/TWH PSD C D150 WH WB GM	62 °	Safety class II	Reflector	Yes	-	For mounting on normally flammable surfaces	Temperature 650 °C, duration 30 s
911401567271	DN588B LED6/940 PSD C D100 WH CAU	-	Safety class II	-	-	-	-	-
911401567371	DN589B LED10/940 PSD C D125 WH CAU	-	Safety class II	-	-	-	-	-
911401567571	DN590B LED15/940 PSD C D125 WH CAU	-	Safety class II	-	-	-	-	-
911401567771	DN589B LED10/940 PSD C D125 WH WP CAU	-	Safety class II	-	-	-	-	-
911401567471	DN589B LED10/940 PSD C D150 WH CAU	-	Safety class II	-	-	-	-	-
911401567671	DN590B LED15/940 PSD C D150 WH CAU	-	Safety class II	-	-	-	-	-
911401567871	DN590B LED15/940 PSD C D150 WH WP CAU	-	Safety class II	-	-	-	-	-
911401567971	DN591B LED15/940 PSD C D200 WH CAU	-	Safety class II	-	-	-	-	-
911401568071	DN591B LED20/940 PSD C D200 WH CAU	-	Safety class II	-	-	-	-	-

General information (2/2)

Order Code	Full Product Name	Light source replaceable	Number of gear units	Optic type	Order Code	Full Product Name	Light source replaceable	Number of gear units	Optic type
911401536641	DN588B LED6/830 PSU C D100 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°	911401536941	DN588B LED6/940 PSU C D100 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401536741	DN588B LED6/840 PSU C D100 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°	911401537041	DN588B LED6/830 PSU C D100 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401536841	DN588B LED6/930 PSU C D100 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°	911401537141	DN588B LED6/840 PSU C D100 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°

Order Code	Full Product Name	Light source replaceable	Number of gear units	Optic type
911401537241	DN588B LED6/930 PSU C D100 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401537341	DN588B LED6/940 PSU C D100 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401537441	DN589B LED10/830 PSU C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401537541	DN589B LED10/840 PSU C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401537641	DN589B LED10/930 PSU C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401537741	DN589B LED10/940 PSU C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401537841	DN589B LED10/830 PSU C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401537941	DN589B LED10/840 PSU C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401538041	DN589B LED10/930 PSU C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401538141	DN589B LED10/940 PSU C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401538241	DN589B LED10/830 PSD C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401538341	DN589B LED10/840 PSD C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401538441	DN589B LED10/930 PSD C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401538541	DN589B LED10/940 PSD C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401538641	DN589B LED10/830 PSD C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401538741	DN589B LED10/840 PSD C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401538841	DN589B LED10/930 PSD C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°

Order Code	Full Product Name	Light source replaceable	Number of gear units	Optic type
911401538941	DN589B LED10/940 PSD C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401539041	DN590B LED15/830 PSU C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401539141	DN590B LED15/840 PSU C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401539241	DN590B LED15/930 PSU C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401539341	DN590B LED15/940 PSU C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401539441	DN590B LED15/830 PSU C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401539541	DN590B LED15/840 PSU C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401539641	DN590B LED15/930 PSU C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401539741	DN590B LED15/940 PSU C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401539841	DN590B LED15/830 PSD C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401539941	DN590B LED15/840 PSD C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401540041	DN590B LED15/930 PSD C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401540141	DN590B LED15/940 PSD C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401540241	DN590B LED15/830 PSD C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401540341	DN590B LED15/840 PSD C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401540441	DN590B LED15/930 PSD C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401540541	DN590B LED15/940 PSD C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°

Order Code	Full Product Name	Light source replaceable	Number of gear units	Optic type
911401540641	DN590B LED15/830 POE C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401540741	DN590B LED15/840 POE C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401540941	DN591B LED20/830 PSU C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401541041	DN591B LED20/840 PSU C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401541141	DN591B LED20/930 PSU C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401541241	DN591B LED20/940 PSU C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401541341	DN591B LED20/830 PSU C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401541441	DN591B LED20/840 PSU C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401541541	DN591B LED20/930 PSU C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401541641	DN591B LED20/940 PSU C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401541741	DN591B LED20/830 PSD C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401541841	DN591B LED20/840 PSD C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401541941	DN591B LED20/930 PSD C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401542041	DN591B LED20/940 PSD C D125 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401542141	DN591B LED20/830 PSD C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401542241	DN591B LED20/840 PSD C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401542341	DN591B LED20/930 PSD C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°

Order Code	Full Product Name	Light source replaceable	Number of gear units	Optic type
911401542441	DN591B LED20/940 PSD C D125 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401547541	DN588B LED6/830 PSU C D125 C WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401547641	DN588B LED6/840 PSU C D125 C WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401548741	DN588B LED6/840 PSD C D125 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401549541	DN588B LED6/830 PSU C D125 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401549641	DN588B LED6/840 PSU C D125 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401550541	DN588B LED6/840 PSD C D125 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401540841	DN590B LED20/TWH PSD C D150 WH WB GC	No	2 units	Facetted reflector with beam angle 60°
911401542541	DN591B LED20/830 PSU C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401542641	DN591B LED20/840 PSU C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401542741	DN591B LED20/930 PSU C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401542841	DN591B LED20/940 PSU C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401542941	DN591B LED20/830 PSU C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401543041	DN591B LED20/840 PSU C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401543141	DN591B LED20/930 PSU C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401543241	DN591B LED20/940 PSU C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401543341	DN591B LED20/830 PSD C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°

Order Code	Full Product Name	Light source replaceable	Number of gear units	Optic type
911401543441	DN591B LED20/840 PSD C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401543541	DN591B LED20/930 PSD C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401543641	DN591B LED20/940 PSD C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401543741	DN591B LED20/830 PSD C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401543841	DN591B LED20/840 PSD C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401543941	DN591B LED20/930 PSD C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401544041	DN591B LED20/940 PSD C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401544141	DN592B LED25/830 PSU C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401544241	DN592B LED25/840 PSU C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401544341	DN592B LED25/930 PSU C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401544441	DN592B LED25/940 PSU C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401544541	DN592B LED25/830 PSU C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401544641	DN592B LED25/840 PSU C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401544741	DN592B LED25/930 PSU C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401544841	DN592B LED25/940 PSU C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401544941	DN592B LED25/830 PSD C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401545041	DN592B LED25/840 PSD C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°

Order Code	Full Product Name	Light source replaceable	Number of gear units	Optic type
911401545141	DN592B LED25/930 PSD C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401545241	DN592B LED25/940 PSD C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401545341	DN592B LED25/830 PSD C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401545441	DN592B LED25/840 PSD C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401545541	DN592B LED25/930 PSD C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401545641	DN592B LED25/940 PSD C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401545741	DN592B LED25/830 POE C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401545841	DN592B LED25/840 POE C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401545941	DN593B LED30/830 PSU C D200 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401546041	DN593B LED30/840 PSU C D200 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401546141	DN593B LED30/930 PSU C D200 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401546241	DN593B LED30/940 PSU C D200 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401546341	DN593B LED30/830 PSU C D200 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401546441	DN593B LED30/840 PSU C D200 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401546541	DN593B LED30/930 PSU C D200 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401546641	DN593B LED30/940 PSU C D200 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401546741	DN594B LED40/830 PSU C D200 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°

Order Code	Full Product Name	Light source replaceable	Number of gear units	Optic type
911401546841	DN594B LED40/840 PSU C D200 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401546941	DN594B LED40/930 PSU C D200 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401547041	DN594B LED40/940 PSU C D200 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401547141	DN594B LED40/830 PSU C D200 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401547241	DN594B LED40/840 PSU C D200 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401547341	DN594B LED40/930 PSU C D200 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401547441	DN594B LED40/940 PSU C D200 WH MB GC	No	1 unit	Facetted reflector with beam angle 30°
911401547741	DN589B LED10/830 PSU C D150 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401547841	DN589B LED10/840 PSU C D150 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401547941	DN590B LED15/830 PSU C D150 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401548041	DN590B LED15/840 PSU C D150 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401548141	DN591B LED20/830 PSU C D200 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401548241	DN591B LED20/840 PSU C D200 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401548341	DN593B LED30/830 PSU C D200 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401548441	DN593B LED30/840 PSU C D200 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401548541	DN594B LED40/830 PSU C D200 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401548641	DN594B LED40/840 PSU C D200 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°

Order Code	Full Product Name	Light source replaceable	Number of gear units	Optic type
911401548841	DN589B LED10/830 PSD C D150 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401548941	DN589B LED10/840 PSD C D150 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401549041	DN590B LED15/840 PSD C D150 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401549141	DN591B LED20/830 PSD C D200 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401549241	DN591B LED20/840 PSD C D200 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401549341	DN593B LED30/840 PSD C D200 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401549441	DN594B LED40/840 PSD C D200 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401549741	DN589B LED10/830 PSU C D150 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401549841	DN589B LED10/840 PSU C D150 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401549941	DN590B LED15/830 PSU C D150 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401550041	DN590B LED15/840 PSU C D150 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401550141	DN591B LED20/830 PSU C D200 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401550241	DN591B LED20/840 PSU C D200 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401550341	DN593B LED30/840 PSU C D200 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401550441	DN594B LED40/840 PSU C D200 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401550641	DN589B LED10/830 PSD C D150 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401550741	DN589B LED10/840 PSD C D150 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°

Order Code	Full Product Name	Light source replaceable	Number of gear units	Optic type
911401550841	DN590B LED15/840 PSD C D150 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401550941	DN591B LED20/830 PSD C D200 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401551041	DN591B LED20/840 PSD C D200 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401551141	DN593B LED30/840 PSD C D200 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401551241	DN594B LED40/840 PSD C D200 WH WB WP GM	No	1 unit	Facetted reflector with beam angle 60°
911401551341	DN589B LED10/830 PSU C D150 WH WB CAU	No	1 unit	Facetted reflector with beam angle 60°
911401551441	DN589B LED10/840 PSU C D150 WH WB CAU	No	1 unit	Facetted reflector with beam angle 60°
911401551541	DN590B LED15/840 PSU C D150 WH WB CAU	No	1 unit	Facetted reflector with beam angle 60°
911401551641	DN591B LED20/830 PSU C D200 WH WB CAU	No	1 unit	Facetted reflector with beam angle 60°
911401551741	DN591B LED20/840 PSU C D200 WH WB CAU	No	1 unit	Facetted reflector with beam angle 60°
911401551841	DN593B LED30/840 PSU C D200 WH WB CAU	No	1 unit	Facetted reflector with beam angle 60°
911401551941	DN594B LED40/840 PSU C D200 WH WB CAU	No	1 unit	Facetted reflector with beam angle 60°
911401552041	DN589B LED10/830 PSD C D150 WH WB CAU	No	1 unit	Facetted reflector with beam angle 60°
911401552141	DN589B LED10/840 PSD C D150 WH WB CAU	No	1 unit	Facetted reflector with beam angle 60°
911401552241	DN590B LED15/840 PSD C D150 WH WB CAU	No	1 unit	Facetted reflector with beam angle 60°
911401552341	DN591B LED20/830 PSD C D200 WH WB CAU	No	1 unit	Facetted reflector with beam angle 60°
911401552441	DN591B LED20/840 PSD C D200 WH WB CAU	No	1 unit	Facetted reflector with beam angle 60°

Order Code	Full Product Name	Light source replaceable	Number of gear units	Optic type
911401552541	DN593B LED30/840 PSD C D200 WH WB CAU	No	1 unit	Facetted reflector with beam angle 60°
911401552641	DN594B LED40/840 PSD C D200 WH WB CAU	No	1 unit	Facetted reflector with beam angle 60°
911401552741	DN589B LED10/830 PSU C D150 WH WB WP CAU	No	1 unit	Facetted reflector with beam angle 60°
911401552841	DN589B LED10/840 PSU C D150 WH WB WP CAU	No	1 unit	Facetted reflector with beam angle 60°
911401552941	DN590B LED15/840 PSU C D150 WH WB WP CAU	No	1 unit	Facetted reflector with beam angle 60°
911401553041	DN591B LED20/830 PSU C D200 WH WB WP CAU	No	1 unit	Facetted reflector with beam angle 60°
911401553141	DN591B LED20/840 PSU C D200 WH WB WP CAU	No	1 unit	Facetted reflector with beam angle 60°
911401553241	DN593B LED30/840 PSU C D200 WH WB WP CAU	No	1 unit	Facetted reflector with beam angle 60°
911401553341	DN594B LED40/840 PSU C D200 WH WB WP CAU	No	1 unit	Facetted reflector with beam angle 60°
911401553441	DN589B LED10/830 PSD C D150 WH WB WP CAU	No	1 unit	Facetted reflector with beam angle 60°
911401553541	DN589B LED10/840 PSD C D150 WH WB WP CAU	No	1 unit	Facetted reflector with beam angle 60°
911401553641	DN590B LED15/840 PSD C D150 WH WB WP CAU	No	1 unit	Facetted reflector with beam angle 60°
911401553741	DN591B LED20/830 PSD C D200 WH WB WP CAU	No	1 unit	Facetted reflector with beam angle 60°
911401553841	DN591B LED20/840 PSD C D200 WH WB WP CAU	No	1 unit	Facetted reflector with beam angle 60°
911401553941	DN593B LED30/840 PSD C D200 WH WB WP CAU	No	1 unit	Facetted reflector with beam angle 60°
911401554041	DN594B LED40/840 PSD C D200 WH WB WP CAU	No	1 unit	Facetted reflector with beam angle 60°
911401554141	DN590B LED15/830 POE C D150 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°

Order Code	Full Product Name	Light source replaceable	Number of gear units	Optic type
911401554241	DN590B LED15/840 POE C D150 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401554341	DN592B LED25/830 POE C D200 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401554441	DN592B LED25/840 POE C D200 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°
911401542251	DN591B LED20/TWH PSD C D150 WH MB GM	No	1 unit	Facetted reflector with beam angle 36°
911401542351	DN591B LED20/TWH PSD C D150 WH WB GC	No	1 unit	Facetted reflector with beam angle 60°
911401542451	DN591B LED20/TWH PSD C D150 WH MB GC	No	1 unit	Facetted reflector with beam angle 36°
911401542551	DN591B LED20/TWH PSD C D150 WH WB GM	No	1 unit	Facetted reflector with beam angle 60°

Order Code	Full Product Name	Light source replaceable	Number of gear units	Optic type
911401567271	DN588B LED6/940 PSD C D100 WH CAU	-	-	-
911401567371	DN589B LED10/940 PSD C D125 WH CAU	-	-	-
911401567571	DN590B LED15/940 PSD C D125 WH CAU	-	-	-
911401567771	DN589B LED10/940 PSD C D125 WH WP CAU	-	-	-
911401567471	DN589B LED10/940 PSD C D150 WH CAU	-	-	-
911401567671	DN590B LED15/940 PSD C D150 WH CAU	-	-	-
911401567871	DN590B LED15/940 PSD C D150 WH WP CAU	-	-	-
911401567971	DN591B LED15/940 PSD C D200 WH CAU	-	-	-
911401568071	DN591B LED20/940 PSD C D200 WH CAU	-	-	-

Initial performance (IEC compliant)

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial LED luminaire efficacy	Initial luminous flux	Luminous flux tolerance	Initial input power
911401536641	DN588B LED6/830 PSU C D100 WH WB GC	-	3000 K	>80	102 lm/W	670 lm	+/-10%	6.6 W
911401536741	DN588B LED6/840 PSU C D100 WH WB GC	-	4000 K	>90	112 lm/W	740 lm	+/-10%	6.6 W
911401536841	DN588B LED6/930 PSU C D100 WH WB GC	-	3000 K	>80	88 lm/W	580 lm	+/-10%	6.6 W
911401536941	DN588B LED6/940 PSU C D100 WH WB GC	-	4000 K	>90	95 lm/W	630 lm	+/-10%	6.6 W
911401537041	DN588B LED6/830 PSU C D100 WH MB GC	-	3000 K	>80	102 lm/W	670 lm	+/-10%	6.6 W
911401537141	DN588B LED6/840 PSU C D100 WH MB GC	-	4000 K	>90	112 lm/W	740 lm	+/-10%	6.6 W
911401537241	DN588B LED6/930 PSU C D100 WH MB GC	-	3000 K	>80	88 lm/W	580 lm	+/-10%	6.6 W
911401537341	DN588B LED6/940 PSU C D100 WH MB GC	-	4000 K	>90	95 lm/W	630 lm	+/-10%	6.6 W
911401537441	DN589B LED10/830 PSU C D125 WH WB GC	-	3000 K	>80	103 lm/W	960 lm	+/-10%	9.3 W
911401537541	DN589B LED10/840 PSU C D125 WH WB GC	-	4000 K	>90	108 lm/W	1000 lm	+/-10%	9.3 W
911401537641	DN589B LED10/930 PSU C D125 WH WB GC	-	3000 K	>80	86 lm/W	800 lm	+/-10%	9.3 W
911401537741	DN589B LED10/940 PSU C D125 WH WB GC	-	4000 K	>90	92 lm/W	860 lm	+/-10%	9.3 W



Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial LED luminaire efficacy	Initial luminous flux	Luminous flux tolerance	Initial input power
911401537841	DN589B LED10/830 PSU C D125 WH MB GC	-	3000 K	>80	103 lm/W	960 lm	+/-10%	9.3 W
911401537941	DN589B LED10/840 PSU C D125 WH MB GC	-	4000 K	>90	108 lm/W	1000 lm	+/-10%	9.3 W
911401538041	DN589B LED10/930 PSU C D125 WH MB GC	-	3000 K	>80	86 lm/W	800 lm	+/-10%	9.3 W
911401538141	DN589B LED10/940 PSU C D125 WH MB GC	-	4000 K	>90	92 lm/W	860 lm	+/-10%	9.3 W
911401538241	DN589B LED10/830 PSD C D125 WH WB GC	-	3000 K	>80	103 lm/W	960 lm	+/-10%	9.3 W
911401538341	DN589B LED10/840 PSD C D125 WH WB GC	-	4000 K	>90	108 lm/W	1000 lm	+/-10%	9.3 W
911401538441	DN589B LED10/930 PSD C D125 WH WB GC	-	3000 K	>80	86 lm/W	800 lm	+/-10%	9.3 W
911401538541	DN589B LED10/940 PSD C D125 WH WB GC	-	4000 K	>90	92 lm/W	860 lm	+/-10%	9.3 W
911401538641	DN589B LED10/830 PSD C D125 WH MB GC	-	3000 K	>80	103 lm/W	960 lm	+/-10%	9.3 W
911401538741	DN589B LED10/840 PSD C D125 WH MB GC	-	4000 K	>90	108 lm/W	1000 lm	+/-10%	9.3 W
911401538841	DN589B LED10/930 PSD C D125 WH MB GC	-	3000 K	>80	86 lm/W	800 lm	+/-10%	9.3 W
911401538941	DN589B LED10/940 PSD C D125 WH MB GC	-	4000 K	>90	92 lm/W	860 lm	+/-10%	9.3 W
911401539041	DN590B LED15/830 PSU C D125 WH WB GC	-	3000 K	>80	104 lm/W	1410 lm	+/-10%	13.5 W
911401539141	DN590B LED15/840 PSU C D125 WH WB GC	-	4000 K	>90	111 lm/W	1500 lm	+/-10%	13.5 W
911401539241	DN590B LED15/930 PSU C D125 WH WB GC	-	3000 K	>80	88 lm/W	1190 lm	+/-10%	13.5 W
911401539341	DN590B LED15/940 PSU C D125 WH WB GC	-	4000 K	>90	94 lm/W	1270 lm	+/-10%	13.5 W
911401539441	DN590B LED15/830 PSU C D125 WH MB GC	-	3000 K	>80	104 lm/W	1410 lm	+/-10%	13.5 W
911401539541	DN590B LED15/840 PSU C D125 WH MB GC	-	4000 K	>90	111 lm/W	1500 lm	+/-10%	13.5 W
911401539641	DN590B LED15/930 PSU C D125 WH MB GC	-	3000 K	>80	88 lm/W	1190 lm	+/-10%	13.5 W
911401539741	DN590B LED15/940 PSU C D125 WH MB GC	-	4000 K	>90	94 lm/W	1270 lm	+/-10%	13.5 W
911401539841	DN590B LED15/830 PSD C D125 WH WB GC	-	3000 K	>80	104 lm/W	1410 lm	+/-10%	13.5 W
911401539941	DN590B LED15/840 PSD C D125 WH WB GC	-	4000 K	>90	111 lm/W	1500 lm	+/-10%	13.5 W
911401540041	DN590B LED15/930 PSD C D125 WH WB GC	-	3000 K	>80	88 lm/W	1190 lm	+/-10%	13.5 W
911401540141	DN590B LED15/940 PSD C D125 WH WB GC	-	4000 K	>90	94 lm/W	1270 lm	+/-10%	13.5 W
911401540241	DN590B LED15/830 PSD C D125 WH MB GC	-	3000 K	>80	104 lm/W	1410 lm	+/-10%	13.5 W

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial LED luminaire efficacy	Initial luminous flux	Luminous flux tolerance	Initial input power
911401540341	DN590B LED15/840 PSD C D125 WH MB GC	-	4000 K	>90	111 lm/W	1500 lm	+/-10%	13.5 W
911401540441	DN590B LED15/930 PSD C D125 WH MB GC	-	3000 K	>80	88 lm/W	1190 lm	+/-10%	13.5 W
911401540541	DN590B LED15/940 PSD C D125 WH MB GC	-	4000 K	>90	94 lm/W	1270 lm	+/-10%	13.5 W
911401540641	DN590B LED15/830 POE C D125 WH WB GC	-	3000 K	>80	104 lm/W	1410 lm	+/-10%	13.5 W
911401540741	DN590B LED15/840 POE C D125 WH WB GC	-	4000 K	>90	111 lm/W	1500 lm	+/-10%	13.5 W
911401540941	DN591B LED20/830 PSU C D125 WH WB GC	-	3000 K	>80	104 lm/W	2000 lm	+/-10%	19.3 W
911401541041	DN591B LED20/840 PSU C D125 WH WB GC	-	4000 K	>90	109 lm/W	2100 lm	+/-10%	19.3 W
911401541141	DN591B LED20/930 PSU C D125 WH WB GC	-	3000 K	>80	87 lm/W	1670 lm	+/-10%	19.3 W
911401541241	DN591B LED20/940 PSU C D125 WH WB GC	-	4000 K	>90	93 lm/W	1800 lm	+/-10%	19.3 W
911401541341	DN591B LED20/830 PSU C D125 WH MB GC	-	3000 K	>80	104 lm/W	2000 lm	+/-10%	19.3 W
911401541441	DN591B LED20/840 PSU C D125 WH MB GC	-	4000 K	>90	109 lm/W	2100 lm	+/-10%	19.3 W
911401541541	DN591B LED20/930 PSU C D125 WH MB GC	-	3000 K	>80	87 lm/W	1670 lm	+/-10%	19.3 W
911401541641	DN591B LED20/940 PSU C D125 WH MB GC	-	4000 K	>90	93 lm/W	1800 lm	+/-10%	19.3 W
911401541741	DN591B LED20/830 PSD C D125 WH WB GC	-	3000 K	>80	104 lm/W	2000 lm	+/-10%	19.3 W
911401541841	DN591B LED20/840 PSD C D125 WH WB GC	-	4000 K	>90	109 lm/W	2100 lm	+/-10%	19.3 W
911401541941	DN591B LED20/930 PSD C D125 WH WB GC	-	3000 K	>80	87 lm/W	1670 lm	+/-10%	19.3 W
911401542041	DN591B LED20/940 PSD C D125 WH WB GC	-	4000 K	>90	93 lm/W	1800 lm	+/-10%	19.3 W
911401542141	DN591B LED20/830 PSD C D125 WH MB GC	-	3000 K	>80	104 lm/W	2000 lm	+/-10%	19.3 W
911401542241	DN591B LED20/840 PSD C D125 WH MB GC	-	4000 K	>90	109 lm/W	2100 lm	+/-10%	19.3 W
911401542341	DN591B LED20/930 PSD C D125 WH MB GC	-	3000 K	>80	87 lm/W	1670 lm	+/-10%	19.3 W
911401542441	DN591B LED20/940 PSD C D125 WH MB GC	-	4000 K	>90	93 lm/W	1800 lm	+/-10%	19.3 W
911401547541	DN588B LED6/830 PSU C D125 C WH WB GM	-	3000 K	>80	109 lm/W	720 lm	+/-10%	6.6 W
911401547641	DN588B LED6/840 PSU C D125 C WH WB GM	-	4000 K	>80	114 lm/W	750 lm	+/-10%	6.6 W
911401548741	DN588B LED6/840 PSD C D125 WH WB GM	-	4000 K	>80	114 lm/W	750 lm	+/-10%	6.6 W
911401549541	DN588B LED6/830 PSU C D125 WH WB WP GM	-	3000 K	>80	103 lm/W	680 lm	+/-10%	6.6 W

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial LED luminaire efficacy	Initial luminous flux	Luminous flux tolerance	Initial input power
911401549641	DN588B LED6/840 PSU C D125 WH WB WP GM	-	4000 K	>80	108 lm/W	710 lm	+/-10%	6.6 W
911401550541	DN588B LED6/840 PSD C D125 WH WB WP GM	-	4000 K	>80	108 lm/W	710 lm	+/-10%	6.6 W
911401540841	DN590B LED20/TWH PSD C D150 WH WB GC	-	- K	>80	185 lm/W	2500 lm	+/-10%	13.5 W
911401542541	DN591B LED20/830 PSU C D150 WH WB GC	-	3000 K	>80	109 lm/W	2100 lm	+/-10%	19.3 W
911401542641	DN591B LED20/840 PSU C D150 WH WB GC	-	4000 K	>90	111 lm/W	2150 lm	+/-10%	19.3 W
911401542741	DN591B LED20/930 PSU C D150 WH WB GC	-	3000 K	>80	91 lm/W	1760 lm	+/-10%	19.3 W
911401542841	DN591B LED20/940 PSU C D150 WH WB GC	-	4000 K	>90	98 lm/W	1890 lm	+/-10%	19.3 W
911401542941	DN591B LED20/830 PSU C D150 WH MB GC	-	3000 K	>80	109 lm/W	2100 lm	+/-10%	19.3 W
911401543041	DN591B LED20/840 PSU C D150 WH MB GC	-	4000 K	>90	111 lm/W	2150 lm	+/-10%	19.3 W
911401543141	DN591B LED20/930 PSU C D150 WH MB GC	-	3000 K	>80	91 lm/W	1760 lm	+/-10%	19.3 W
911401543241	DN591B LED20/940 PSU C D150 WH MB GC	-	4000 K	>90	98 lm/W	1890 lm	+/-10%	19.3 W
911401543341	DN591B LED20/830 PSD C D150 WH WB GC	-	3000 K	>80	109 lm/W	2100 lm	+/-10%	19.3 W
911401543441	DN591B LED20/840 PSD C D150 WH WB GC	-	4000 K	>90	111 lm/W	2150 lm	+/-10%	19.3 W
911401543541	DN591B LED20/930 PSD C D150 WH WB GC	-	3000 K	>80	91 lm/W	1760 lm	+/-10%	19.3 W
911401543641	DN591B LED20/940 PSD C D150 WH WB GC	-	4000 K	>90	98 lm/W	1890 lm	+/-10%	19.3 W
911401543741	DN591B LED20/830 PSD C D150 WH MB GC	-	3000 K	>80	109 lm/W	2100 lm	+/-10%	19.3 W
911401543841	DN591B LED20/840 PSD C D150 WH MB GC	-	4000 K	>90	111 lm/W	2150 lm	+/-10%	19.3 W
911401543941	DN591B LED20/930 PSD C D150 WH MB GC	-	3000 K	>80	91 lm/W	1760 lm	+/-10%	19.3 W
911401544041	DN591B LED20/940 PSD C D150 WH MB GC	-	4000 K	>90	98 lm/W	1890 lm	+/-10%	19.3 W
911401544141	DN592B LED25/830 PSU C D150 WH WB GC	-	3000 K	>80	109 lm/W	2510 lm	+/-10%	23 W
911401544241	DN592B LED25/840 PSU C D150 WH WB GC	-	4000 K	>90	113 lm/W	2600 lm	+/-10%	23 W
911401544341	DN592B LED25/930 PSU C D150 WH WB GC	-	3000 K	>80	92 lm/W	2110 lm	+/-10%	23 W
911401544441	DN592B LED25/940 PSU C D150 WH WB GC	-	4000 K	>90	98 lm/W	2260 lm	+/-10%	23 W
911401544541	DN592B LED25/830 PSU C D150 WH MB GC	-	3000 K	>80	109 lm/W	2510 lm	+/-10%	23 W
911401544641	DN592B LED25/840 PSU C D150 WH MB GC	-	4000 K	>90	113 lm/W	2600 lm	+/-10%	23 W

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial LED luminaire efficacy	Initial luminous flux	Luminous flux tolerance	Initial input power
911401544741	DN592B LED25/930 PSU C D150 WH MB GC	-	3000 K	>80	92 lm/W	2110 lm	+/-10%	23 W
911401544841	DN592B LED25/940 PSU C D150 WH MB GC	-	4000 K	>90	98 lm/W	2260 lm	+/-10%	23 W
911401544941	DN592B LED25/830 PSD C D150 WH WB GC	-	3000 K	>80	109 lm/W	2510 lm	+/-10%	23 W
911401545041	DN592B LED25/840 PSD C D150 WH WB GC	-	4000 K	>90	113 lm/W	2600 lm	+/-10%	23 W
911401545141	DN592B LED25/930 PSD C D150 WH WB GC	-	3000 K	>80	92 lm/W	2110 lm	+/-10%	23 W
911401545241	DN592B LED25/940 PSD C D150 WH WB GC	-	4000 K	>90	98 lm/W	2260 lm	+/-10%	23 W
911401545341	DN592B LED25/830 PSD C D150 WH MB GC	-	3000 K	>80	109 lm/W	2510 lm	+/-10%	23 W
911401545441	DN592B LED25/840 PSD C D150 WH MB GC	-	4000 K	>90	113 lm/W	2600 lm	+/-10%	23 W
911401545541	DN592B LED25/930 PSD C D150 WH MB GC	-	3000 K	>80	92 lm/W	2110 lm	+/-10%	23 W
911401545641	DN592B LED25/940 PSD C D150 WH MB GC	-	4000 K	>90	98 lm/W	2260 lm	+/-10%	23 W
911401545741	DN592B LED25/830 POE C D150 WH WB GC	-	3000 K	>80	113 lm/W	2600 lm	+/-10%	23 W
911401545841	DN592B LED25/840 POE C D150 WH WB GC	-	4000 K	>80	113 lm/W	2600 lm	+/-10%	23 W
911401545941	DN593B LED30/830 PSU C D200 WH WB GC	-	3000 K	>80	102 lm/W	3300 lm	+/-10%	32.5 W
911401546041	DN593B LED30/840 PSU C D200 WH WB GC	-	4000 K	>80	105 lm/W	3400 lm	+/-10%	32.5 W
911401546141	DN593B LED30/930 PSU C D200 WH WB GC	-	3000 K	>90	85 lm/W	2770 lm	+/-10%	32.5 W
911401546241	DN593B LED30/940 PSU C D200 WH WB GC	-	4000 K	>90	91 lm/W	2970 lm	+/-10%	32.5 W
911401546341	DN593B LED30/830 PSU C D200 WH MB GC	-	3000 K	>80	102 lm/W	3300 lm	+/-10%	32.5 W
911401546441	DN593B LED30/840 PSU C D200 WH MB GC	-	4000 K	>80	105 lm/W	3400 lm	+/-10%	32.5 W
911401546541	DN593B LED30/930 PSU C D200 WH MB GC	-	3000 K	>90	85 lm/W	2770 lm	+/-10%	32.5 W
911401546641	DN593B LED30/940 PSU C D200 WH MB GC	-	4000 K	>90	91 lm/W	2970 lm	+/-10%	32.5 W
911401546741	DN594B LED40/830 PSU C D200 WH WB GC	-	3000 K	>80	103 lm/W	4100 lm	+/-10%	39.7 W
911401546841	DN594B LED40/840 PSU C D200 WH WB GC	-	4000 K	>80	108 lm/W	4300 lm	+/-10%	39.7 W
911401546941	DN594B LED40/930 PSU C D200 WH WB GC	-	3000 K	>90	87 lm/W	3440 lm	+/-10%	39.7 W
911401547041	DN594B LED40/940 PSU C D200 WH WB GC	-	4000 K	>90	93 lm/W	3700 lm	+/-10%	39.7 W
911401547141	DN594B LED40/830 PSU C D200 WH MB GC	-	3000 K	>80	103 lm/W	4100 lm	+/-10%	39.7 W

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial LED luminaire efficacy	Initial luminous flux	Luminous flux tolerance	Initial input power
911401547241	DN594B LED40/840 PSU C D200 WH MB GC	-	4000 K	>80	108 lm/W	4300 lm	+/-10%	39.7 W
911401547341	DN594B LED40/930 PSU C D200 WH MB GC	-	3000 K	>90	87 lm/W	3440 lm	+/-10%	39.7 W
911401547441	DN594B LED40/940 PSU C D200 WH MB GC	-	4000 K	>90	93 lm/W	3700 lm	+/-10%	39.7 W
911401547741	DN589B LED10/830 PSU C D150 WH WB GM	-	3000 K	>80	118 lm/W	990 lm	+/-10%	8.4 W
911401547841	DN589B LED10/840 PSU C D150 WH WB GM	-	4000 K	>80	125 lm/W	1050 lm	+/-10%	8.4 W
911401547941	DN590B LED15/830 PSU C D150 WH WB GM	-	3000 K	>80	176 lm/W	1480 lm	+/-10%	8.4 W
911401548041	DN590B LED15/840 PSU C D150 WH WB GM	-	4000 K	>80	185 lm/W	1550 lm	+/-10%	8.4 W
911401548141	DN591B LED20/830 PSU C D200 WH WB GM	-	3000 K	>80	113 lm/W	2030 lm	+/-10%	18 W
911401548241	DN591B LED20/840 PSU C D200 WH WB GM	-	4000 K	>80	119 lm/W	2150 lm	+/-10%	18 W
911401548341	DN593B LED30/830 PSU C D200 WH WB GM	-	3000 K	>80	102 lm/W	3300 lm	+/-10%	32.5 W
911401548441	DN593B LED30/840 PSU C D200 WH WB GM	-	4000 K	>80	105 lm/W	3400 lm	+/-10%	32.5 W
911401548541	DN594B LED40/830 PSU C D200 WH WB GM	-	3000 K	>80	103 lm/W	4100 lm	+/-10%	39.7 W
911401548641	DN594B LED40/840 PSU C D200 WH WB GM	-	4000 K	>80	108 lm/W	4300 lm	+/-10%	39.7 W
911401548841	DN589B LED10/830 PSD C D150 WH WB GM	-	3000 K	>80	118 lm/W	990 lm	+/-10%	8.4 W
911401548941	DN589B LED10/840 PSD C D150 WH WB GM	-	4000 K	>80	125 lm/W	1050 lm	+/-10%	8.4 W
911401549041	DN590B LED15/840 PSD C D150 WH WB GM	-	4000 K	>80	115 lm/W	1550 lm	+/-10%	13.5 W
911401549141	DN591B LED20/830 PSD C D200 WH WB GM	-	3000 K	>80	105 lm/W	2030 lm	+/-10%	19.3 W
911401549241	DN591B LED20/840 PSD C D200 WH WB GM	-	4000 K	>80	111 lm/W	2150 lm	+/-10%	19.3 W
911401549341	DN593B LED30/840 PSD C D200 WH WB GM	-	4000 K	>80	105 lm/W	3400 lm	+/-10%	32.5 W
911401549441	DN594B LED40/840 PSD C D200 WH WB GM	-	4000 K	>80	108 lm/W	4300 lm	+/-10%	39.7 W
911401549741	DN589B LED10/830 PSU C D150 WH WB WP GM	-	3000 K	>80	112 lm/W	940 lm	+/-10%	8.4 W
911401549841	DN589B LED10/840 PSU C D150 WH WB WP GM	-	4000 K	>80	119 lm/W	1000 lm	+/-10%	8.4 W
911401549941	DN590B LED15/830 PSU C D150 WH WB WP GM	-	3000 K	>80	104 lm/W	1410 lm	+/-10%	13.5 W
911401550041	DN590B LED15/840 PSU C D150 WH WB WP GM	-	4000 K	>80	109 lm/W	1470 lm	+/-10%	13.5 W
911401550141	DN591B LED20/830 PSU C D200 WH WB WP GM	-	3000 K	>80	107 lm/W	1930 lm	+/-10%	18 W

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial LED luminaire efficacy	Initial luminous flux	Luminous flux tolerance	Initial input power
911401550241	DN591B LED20/840 PSU C D200 WH WB WP GM	-	4000 K	>80	113 lm/W	2040 lm	+/-10%	18 W
911401550341	DN593B LED30/840 PSU C D200 WH WB WP GM	-	4000 K	>80	99 lm/W	3230 lm	+/-10%	32.5 W
911401550441	DN594B LED40/840 PSU C D200 WH WB WP GM	-	4000 K	>80	103 lm/W	4090 lm	+/-10%	39.7 W
911401550641	DN589B LED10/830 PSD C D150 WH WB WP GM	-	3000 K	>80	112 lm/W	940 lm	+/-10%	8.4 W
911401550741	DN589B LED10/840 PSD C D150 WH WB WP GM	-	4000 K	>80	119 lm/W	1000 lm	+/-10%	8.4 W
911401550841	DN590B LED15/840 PSD C D150 WH WB WP GM	-	4000 K	>80	109 lm/W	1470 lm	+/-10%	13.5 W
911401550941	DN591B LED20/830 PSD C D200 WH WB WP GM	-	3000 K	>80	107 lm/W	1930 lm	+/-10%	18 W
911401551041	DN591B LED20/840 PSD C D200 WH WB WP GM	-	4000 K	>80	113 lm/W	2040 lm	+/-10%	18 W
911401551141	DN593B LED30/840 PSD C D200 WH WB WP GM	-	4000 K	>80	99 lm/W	3230 lm	+/-10%	32.5 W
911401551241	DN594B LED40/840 PSD C D200 WH WB WP GM	-	4000 K	>80	103 lm/W	4090 lm	+/-10%	39.7 W
911401551341	DN589B LED10/830 PSU C D150 WH WB CAU	-	3000 K	>80	118 lm/W	990 lm	+/-10%	8.4 W
911401551441	DN589B LED10/840 PSU C D150 WH WB CAU	-	4000 K	>80	125 lm/W	1050 lm	+/-10%	8.4 W
911401551541	DN590B LED15/840 PSU C D150 WH WB CAU	-	4000 K	>80	115 lm/W	1550 lm	+/-10%	13.5 W
911401551641	DN591B LED20/830 PSU C D200 WH WB CAU	-	3000 K	>80	150 lm/W	2030 lm	+/-10%	13.5 W
911401551741	DN591B LED20/840 PSU C D200 WH WB CAU	-	4000 K	>80	119 lm/W	2150 lm	+/-10%	18 W
911401551841	DN593B LED30/840 PSU C D200 WH WB CAU	-	4000 K	>80	189 lm/W	3400 lm	+/-10%	18 W
911401551941	DN594B LED40/840 PSU C D200 WH WB CAU	-	4000 K	>80	132 lm/W	4300 lm	+/-10%	32.5 W
911401552041	DN589B LED10/830 PSD C D150 WH WB CAU	-	3000 K	>80	25 lm/W	990 lm	+/-10%	39.7 W
911401552141	DN589B LED10/840 PSD C D150 WH WB CAU	-	4000 K	>80	125 lm/W	1050 lm	+/-10%	8.4 W
911401552241	DN590B LED15/840 PSD C D150 WH WB CAU	-	4000 K	>80	115 lm/W	1550 lm	+/-10%	13.5 W
911401552341	DN591B LED20/830 PSD C D200 WH WB CAU	-	3000 K	>80	113 lm/W	2030 lm	+/-10%	18 W
911401552441	DN591B LED20/840 PSD C D200 WH WB CAU	-	4000 K	>80	119 lm/W	2150 lm	+/-10%	18 W
911401552541	DN593B LED30/840 PSD C D200 WH WB CAU	-	4000 K	>80	105 lm/W	3400 lm	+/-10%	32.5 W
911401552641	DN594B LED40/840 PSD C D200 WH WB CAU	-	4000 K	>80	108 lm/W	4300 lm	+/-10%	39.7 W
911401552741	DN589B LED10/830 PSU C D150 WH WB WP CAU	-	3000 K	>80	112 lm/W	940 lm	+/-10%	8.4 W

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial LED luminaire efficacy	Initial luminous flux	Luminous flux tolerance	Initial input power
911401552841	DN589B LED10/840 PSU C D150 WH WB WP CAU	-	4000 K	>80	119 lm/W	1000 lm	+/-10%	8.4 W
911401552941	DN590B LED15/840 PSU C D150 WH WB WP CAU	-	4000 K	>80	109 lm/W	1470 lm	+/-10%	13.5 W
911401553041	DN591B LED20/830 PSU C D200 WH WB WP CAU	-	3000 K	>80	107 lm/W	1930 lm	+/-10%	18 W
911401553141	DN591B LED20/840 PSU C D200 WH WB WP CAU	-	4000 K	>80	113 lm/W	2040 lm	+/-10%	18 W
911401553241	DN593B LED30/840 PSU C D200 WH WB WP CAU	-	4000 K	>80	105 lm/W	3400 lm	+/-10%	32.5 W
911401553341	DN594B LED40/840 PSU C D200 WH WB WP CAU	-	4000 K	>80	108 lm/W	4300 lm	+/-10%	39.7 W
911401553441	DN589B LED10/830 PSD C D150 WH WB WP CAU	-	3000 K	>80	112 lm/W	940 lm	+/-10%	8.4 W
911401553541	DN589B LED10/840 PSD C D150 WH WB WP CAU	-	4000 K	>80	119 lm/W	1000 lm	+/-10%	8.4 W
911401553641	DN590B LED15/840 PSD C D150 WH WB WP CAU	-	4000 K	>80	109 lm/W	1470 lm	+/-10%	13.5 W
911401553741	DN591B LED20/830 PSD C D200 WH WB WP CAU	-	3000 K	>80	107 lm/W	1930 lm	+/-10%	18 W
911401553841	DN591B LED20/840 PSD C D200 WH WB WP CAU	-	4000 K	>80	113 lm/W	2040 lm	+/-10%	18 W
911401553941	DN593B LED30/840 PSD C D200 WH WB WP CAU	-	4000 K	>80	105 lm/W	3400 lm	+/-10%	32.5 W
911401554041	DN594B LED40/840 PSD C D200 WH WB WP CAU	-	4000 K	>80	108 lm/W	4300 lm	+/-10%	39.7 W
911401554141	DN590B LED15/830 POE C D150 WH WB GM	-	3000 K	>80	103 lm/W	1480 lm	+/-10%	14.3 W
911401554241	DN590B LED15/840 POE C D150 WH WB GM	-	4000 K	>80	108 lm/W	1550 lm	+/-10%	14.3 W
911401554341	DN592B LED25/830 POE C D200 WH WB GM	-	3000 K	>80	109 lm/W	2510 lm	+/-10%	23 W
911401554441	DN592B LED25/840 POE C D200 WH WB GM	-	4000 K	>80	113 lm/W	2600 lm	+/-10%	23 W
911401542251	DN591B LED20/TWH PSD C D150 WH MB GM	-	6500 K	>80	88 lm/W	2200 lm	+/-15%	25 W
911401542351	DN591B LED20/TWH PSD C D150 WH WB GC	-	2700 K	>80	88 lm/W	2200 lm	+/-15%	25 W
911401542451	DN591B LED20/TWH PSD C D150 WH MB GC	-	6500 K	>80	88 lm/W	2200 lm	+/-15%	25 W
911401542551	DN591B LED20/TWH PSD C D150 WH WB GM	-	2700 K	>80	88 lm/W	2200 lm	+/-15%	25 W
911401567271	DN588B LED6/940 PSD C D100 WH CAU	-	4000 K	>90	84.11423376623377 lm/W	647.6796 lm	+/-10%	7.7 W
911401567371	DN589B LED10/940 PSD C D125 WH CAU	-	4000 K	>90	94.69000000000000 lm/W	1107.873 lm	+/-10%	11.7 W
911401567571	DN590B LED15/940 PSD C D125 WH CAU	-	4000 K	>90	98.16596202531646 lm/W	1551.0222 lm	+/-10%	15.8 W
911401567771	DN589B LED10/940 PSD C D125 WH WP CAU	-	4000 K	>90	87.40615384615384 lm/W	1022.6519999999 9999 lm	+/-10%	11.7 W

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial LED luminaire efficacy	Initial luminous flux	Luminous flux tolerance	Initial input power
911401567471	DN589B LED10/940 PSD C D150 WH CAU	-	4000 K	>90	98.33192307692309 lm/W	1150.4835 lm	+/-10%	11.7 W
911401567671	DN590B LED15/940 PSD C D150 WH CAU	-	4000 K	>90	101.9415759493670 9 lm/W	1610.676900000 00002 lm	+/-10%	15.8 W
911401567871	DN590B LED15/940 PSD C D150 WH WP CAU	-	4000 K	>90	95.48674698795179 lm/W	1585.08 lm	+/-10%	16.6 W
911401567971	DN591B LED15/940 PSD C D200 WH CAU	-	4000 K	>90	111.13142857142859 lm/W	1633.632 lm	+/-10%	14.7 W
911401568071	DN591B LED20/940 PSD C D200 WH CAU	-	4000 K	>90	106.9286399999999 97 lm/W	2138.572799999 9995 lm	+/-10%	20 W

**Mechanical and housing**

Order Code	Full Product Name	Color	Order Code	Full Product Name	Color
911401536641	DN588B LED6/830 PSU C D100 WH WB GC	White and black	911401540241	DN590B LED15/830 PSD C D125 WH MB GC	White and black
911401536741	DN588B LED6/840 PSU C D100 WH WB GC	White and black	911401540341	DN590B LED15/840 PSD C D125 WH MB GC	White and black
911401536841	DN588B LED6/930 PSU C D100 WH WB GC	White and black	911401540441	DN590B LED15/930 PSD C D125 WH MB GC	White and black
911401536941	DN588B LED6/940 PSU C D100 WH WB GC	White and black	911401540541	DN590B LED15/940 PSD C D125 WH MB GC	White and black
911401537041	DN588B LED6/830 PSU C D100 WH MB GC	White and black	911401540641	DN590B LED15/830 POE C D125 WH WB GC	White and black
911401537141	DN588B LED6/840 PSU C D100 WH MB GC	White and black	911401540741	DN590B LED15/840 POE C D125 WH WB GC	White and black
911401537241	DN588B LED6/930 PSU C D100 WH MB GC	White and black	911401540941	DN591B LED20/830 PSU C D125 WH WB GC	White and black
911401537341	DN588B LED6/940 PSU C D100 WH MB GC	White and black	911401541041	DN591B LED20/840 PSU C D125 WH WB GC	White and black
911401537441	DN589B LED10/830 PSU C D125 WH WB GC	White and black	911401541141	DN591B LED20/930 PSU C D125 WH WB GC	White and black
911401537541	DN589B LED10/840 PSU C D125 WH WB GC	White and black	911401541241	DN591B LED20/940 PSU C D125 WH WB GC	White and black
911401537641	DN589B LED10/930 PSU C D125 WH WB GC	White and black	911401541341	DN591B LED20/830 PSU C D125 WH MB GC	White and black
911401537741	DN589B LED10/940 PSU C D125 WH WB GC	White and black	911401541441	DN591B LED20/840 PSU C D125 WH MB GC	White and black
911401537841	DN589B LED10/830 PSU C D125 WH MB GC	White and black	911401541541	DN591B LED20/930 PSU C D125 WH MB GC	White and black
911401537941	DN589B LED10/840 PSU C D125 WH MB GC	White and black	911401541641	DN591B LED20/940 PSU C D125 WH MB GC	White and black
911401538041	DN589B LED10/930 PSU C D125 WH MB GC	White and black	911401541741	DN591B LED20/830 PSD C D125 WH WB GC	White and black
911401538141	DN589B LED10/940 PSU C D125 WH MB GC	White and black	911401541841	DN591B LED20/840 PSD C D125 WH WB GC	White and black
911401538241	DN589B LED10/830 PSD C D125 WH WB GC	White and black	911401541941	DN591B LED20/930 PSD C D125 WH WB GC	White and black
911401538341	DN589B LED10/840 PSD C D125 WH WB GC	White and black	911401542041	DN591B LED20/940 PSD C D125 WH WB GC	White and black
911401538441	DN589B LED10/930 PSD C D125 WH WB GC	White and black	911401542141	DN591B LED20/830 PSD C D125 WH MB GC	White and black
911401538541	DN589B LED10/940 PSD C D125 WH WB GC	White and black	911401542241	DN591B LED20/840 PSD C D125 WH MB GC	White and black
911401538641	DN589B LED10/830 PSD C D125 WH MB GC	White and black	911401542341	DN591B LED20/930 PSD C D125 WH MB GC	White and black
911401538741	DN589B LED10/840 PSD C D125 WH MB GC	White and black	911401542441	DN591B LED20/940 PSD C D125 WH MB GC	White and black
911401538841	DN589B LED10/930 PSD C D125 WH MB GC	White and black	911401547541	DN588B LED6/830 PSU C D125 C WH WB GM	White and black
911401538941	DN589B LED10/940 PSD C D125 WH MB GC	White and black	911401547641	DN588B LED6/840 PSU C D125 C WH WB GM	White and black
911401539041	DN590B LED15/830 PSU C D125 WH WB GC	White and black	911401548741	DN588B LED6/840 PSD C D125 WH WB GM	White and black
911401539141	DN590B LED15/840 PSU C D125 WH WB GC	White and black	911401549541	DN588B LED6/830 PSU C D125 WH WB WP GM	White and black
911401539241	DN590B LED15/930 PSU C D125 WH WB GC	White and black	911401549641	DN588B LED6/840 PSU C D125 WH WB WP GM	White and black
911401539341	DN590B LED15/940 PSU C D125 WH WB GC	White and black	911401550541	DN588B LED6/840 PSD C D125 WH WB WP GM	White and black
911401539441	DN590B LED15/830 PSU C D125 WH MB GC	White and black	911401540841	DN590B LED20/TWH PSD C D150 WH WB GC	White and black
911401539541	DN590B LED15/840 PSU C D125 WH MB GC	White and black	911401542541	DN591B LED20/830 PSU C D150 WH WB GC	White and black
911401539641	DN590B LED15/930 PSU C D125 WH MB GC	White and black	911401542641	DN591B LED20/840 PSU C D150 WH WB GC	White and black
911401539741	DN590B LED15/940 PSU C D125 WH MB GC	White and black	911401542741	DN591B LED20/930 PSU C D150 WH WB GC	White and black
911401539841	DN590B LED15/830 PSD C D125 WH WB GC	White and black	911401542841	DN591B LED20/940 PSU C D150 WH WB GC	White and black
911401539941	DN590B LED15/840 PSD C D125 WH WB GC	White and black	911401542941	DN591B LED20/830 PSU C D150 WH MB GC	White and black
911401540041	DN590B LED15/930 PSD C D125 WH WB GC	White and black	911401543041	DN591B LED20/840 PSU C D150 WH MB GC	White and black
911401540141	DN590B LED15/940 PSD C D125 WH WB GC	White and black	911401543141	DN591B LED20/930 PSU C D150 WH MB GC	White and black





Order Code	Full Product Name	Color
911401554241	DN590B LED15/840 POE C D150 WH WB GM	White and black
911401554341	DN592B LED25/830 POE C D200 WH WB GM	White and black
911401554441	DN592B LED25/840 POE C D200 WH WB GM	White and black
911401542251	DN591B LED20/TWH PSD C D150 WH MB GM	White and black
911401542351	DN591B LED20/TWH PSD C D150 WH WB GC	White and black
911401542451	DN591B LED20/TWH PSD C D150 WH MB GC	White and black
911401542551	DN591B LED20/TWH PSD C D150 WH WB GM	White and black
911401567271	DN588B LED6/940 PSD C D100 WH CAU	-

Order Code	Full Product Name	Color
911401567371	DN589B LED10/940 PSD C D125 WH CAU	-
911401567571	DN590B LED15/940 PSD C D125 WH CAU	-
911401567771	DN589B LED10/940 PSD C D125 WH WP CAU	-
911401567471	DN589B LED10/940 PSD C D150 WH CAU	-
911401567671	DN590B LED15/940 PSD C D150 WH CAU	-
911401567871	DN590B LED15/940 PSD C D150 WH WP CAU	-
911401567971	DN591B LED15/940 PSD C D200 WH CAU	-
911401568071	DN591B LED20/940 PSD C D200 WH CAU	-

Over time performance (IEC compliant)

Order Code	Full Product Name	Driver failure rate at 5000 h	Median useful life L80B50	Median useful life L90B50
911401536641	DN588B LED6/830 PSU C D100 WH WB GC	1%	50000 h	21000 h
911401536741	DN588B LED6/840 PSU C D100 WH WB GC	1%	50000 h	21000 h
911401536841	DN588B LED6/930 PSU C D100 WH WB GC	1%	50000 h	21000 h
911401536941	DN588B LED6/940 PSU C D100 WH WB GC	1%	50000 h	21000 h
911401537041	DN588B LED6/830 PSU C D100 WH MB GC	1%	50000 h	21000 h
911401537141	DN588B LED6/840 PSU C D100 WH MB GC	1%	50000 h	21000 h
911401537241	DN588B LED6/930 PSU C D100 WH MB GC	1%	50000 h	21000 h
911401537341	DN588B LED6/940 PSU C D100 WH MB GC	1%	50000 h	21000 h
911401537441	DN589B LED10/830 PSU C D125 WH WB GC	1%	50000 h	21000 h
911401537541	DN589B LED10/840 PSU C D125 WH WB GC	1%	50000 h	21000 h
911401537641	DN589B LED10/930 PSU C D125 WH WB GC	1%	50000 h	21000 h
911401537741	DN589B LED10/940 PSU C D125 WH WB GC	1%	50000 h	21000 h
911401537841	DN589B LED10/830 PSU C D125 WH MB GC	1%	50000 h	21000 h
911401537941	DN589B LED10/840 PSU C D125 WH MB GC	1%	50000 h	21000 h
911401538041	DN589B LED10/930 PSU C D125 WH MB GC	1%	50000 h	21000 h
911401538141	DN589B LED10/940 PSU C D125 WH MB GC	1%	50000 h	21000 h
911401538241	DN589B LED10/830 PSD C D125 WH WB GC	1%	50000 h	21000 h
911401538341	DN589B LED10/840 PSD C D125 WH WB GC	1%	50000 h	21000 h
911401538441	DN589B LED10/930 PSD C D125 WH WB GC	1%	50000 h	21000 h

Order Code	Full Product Name	Driver failure rate at 5000 h	Median useful life L80B50	Median useful life L90B50
911401538541	DN589B LED10/940 PSD C D125 WH WB GC	1%	50000 h	21000 h
911401538641	DN589B LED10/830 PSD C D125 WH MB GC	1%	50000 h	21000 h
911401538741	DN589B LED10/840 PSD C D125 WH MB GC	1%	50000 h	21000 h
911401538841	DN589B LED10/930 PSD C D125 WH MB GC	1%	50000 h	21000 h
911401538941	DN589B LED10/940 PSD C D125 WH MB GC	1%	50000 h	21000 h
911401539041	DN590B LED15/830 PSU C D125 WH WB GC	1%	50000 h	21000 h
911401539141	DN590B LED15/840 PSU C D125 WH WB GC	1%	50000 h	21000 h
911401539241	DN590B LED15/930 PSU C D125 WH WB GC	1%	50000 h	21000 h
911401539341	DN590B LED15/940 PSU C D125 WH WB GC	1%	50000 h	21000 h
911401539441	DN590B LED15/830 PSU C D125 WH MB GC	1%	50000 h	21000 h
911401539541	DN590B LED15/840 PSU C D125 WH MB GC	1%	50000 h	21000 h
911401539641	DN590B LED15/930 PSU C D125 WH MB GC	1%	50000 h	21000 h
911401539741	DN590B LED15/940 PSU C D125 WH MB GC	1%	50000 h	21000 h
911401539841	DN590B LED15/830 PSD C D125 WH WB GC	1%	50000 h	21000 h
911401539941	DN590B LED15/840 PSD C D125 WH WB GC	1%	50000 h	21000 h
911401540041	DN590B LED15/930 PSD C D125 WH WB GC	1%	50000 h	21000 h
911401540141	DN590B LED15/940 PSD C D125 WH WB GC	1%	50000 h	21000 h
911401540241	DN590B LED15/830 PSD C D125 WH MB GC	1%	50000 h	21000 h
911401540341	DN590B LED15/840 PSD C D125 WH MB GC	1%	50000 h	21000 h

Order Code	Full Product Name	Driver failure rate at 5000 h	Median useful life L80B50	Median useful life L90B50
911401540441	DN590B LED15/930 PSD C D125 WH MB GC	1%	50000 h	21000 h
911401540541	DN590B LED15/940 PSD C D125 WH MB GC	1%	50000 h	21000 h
911401540641	DN590B LED15/830 POE C D125 WH WB GC	1%	50000 h	21000 h
911401540741	DN590B LED15/840 POE C D125 WH WB GC	1%	50000 h	21000 h
911401540941	DN591B LED20/830 PSU C D125 WH WB GC	1%	50000 h	21000 h
911401541041	DN591B LED20/840 PSU C D125 WH WB GC	1%	50000 h	21000 h
911401541141	DN591B LED20/930 PSU C D125 WH WB GC	1%	50000 h	21000 h
911401541241	DN591B LED20/940 PSU C D125 WH WB GC	1%	50000 h	21000 h
911401541341	DN591B LED20/830 PSU C D125 WH MB GC	1%	50000 h	21000 h
911401541441	DN591B LED20/840 PSU C D125 WH MB GC	1%	50000 h	21000 h
911401541541	DN591B LED20/930 PSU C D125 WH MB GC	1%	50000 h	21000 h
911401541641	DN591B LED20/940 PSU C D125 WH MB GC	1%	50000 h	21000 h
911401541741	DN591B LED20/830 PSD C D125 WH WB GC	1%	50000 h	21000 h
911401541841	DN591B LED20/840 PSD C D125 WH WB GC	1%	50000 h	21000 h
911401541941	DN591B LED20/930 PSD C D125 WH WB GC	1%	50000 h	21000 h
911401542041	DN591B LED20/940 PSD C D125 WH WB GC	1%	50000 h	21000 h
911401542141	DN591B LED20/830 PSD C D125 WH MB GC	1%	50000 h	21000 h
911401542241	DN591B LED20/840 PSD C D125 WH MB GC	1%	50000 h	21000 h
911401542341	DN591B LED20/930 PSD C D125 WH MB GC	1%	50000 h	21000 h
911401542441	DN591B LED20/940 PSD C D125 WH MB GC	1%	50000 h	21000 h
911401547541	DN588B LED6/830 PSU C D125 C WH WB GM	1%	50000 h	21000 h
911401547641	DN588B LED6/840 PSU C D125 C WH WB GM	1%	50000 h	21000 h
911401548741	DN588B LED6/840 PSD C D125 WH WB GM	1%	50000 h	21000 h
911401549541	DN588B LED6/830 PSU C D125 WH WB WP GM	1%	50000 h	21000 h
911401549641	DN588B LED6/840 PSU C D125 WH WB WP GM	1%	50000 h	21000 h

Order Code	Full Product Name	Driver failure rate at 5000 h	Median useful life L80B50	Median useful life L90B50
911401550541	DN588B LED6/840 PSD C D125 WH WB WP GM	1%	50000 h	21000 h
911401540841	DN590B LED20/TWH PSD C D150 WH WB GC	1%	50000 h	21000 h
911401542541	DN591B LED20/830 PSU C D150 WH WB GC	1%	50000 h	21000 h
911401542641	DN591B LED20/840 PSU C D150 WH WB GC	1%	50000 h	21000 h
911401542741	DN591B LED20/930 PSU C D150 WH WB GC	1%	50000 h	21000 h
911401542841	DN591B LED20/940 PSU C D150 WH WB GC	1%	50000 h	21000 h
911401542941	DN591B LED20/830 PSU C D150 WH MB GC	1%	50000 h	21000 h
911401543041	DN591B LED20/840 PSU C D150 WH MB GC	1%	50000 h	21000 h
911401543141	DN591B LED20/930 PSU C D150 WH MB GC	1%	50000 h	21000 h
911401543241	DN591B LED20/940 PSU C D150 WH MB GC	1%	50000 h	21000 h
911401543341	DN591B LED20/830 PSD C D150 WH WB GC	1%	50000 h	21000 h
911401543441	DN591B LED20/840 PSD C D150 WH WB GC	1%	50000 h	21000 h
911401543541	DN591B LED20/930 PSD C D150 WH WB GC	1%	50000 h	21000 h
911401543641	DN591B LED20/940 PSD C D150 WH WB GC	1%	50000 h	21000 h
911401543741	DN591B LED20/830 PSD C D150 WH MB GC	1%	50000 h	21000 h
911401543841	DN591B LED20/840 PSD C D150 WH MB GC	1%	50000 h	21000 h
911401543941	DN591B LED20/930 PSD C D150 WH MB GC	1%	50000 h	21000 h
911401544041	DN591B LED20/940 PSD C D150 WH MB GC	1%	50000 h	21000 h
911401544141	DN592B LED25/830 PSU C D150 WH WB GC	1%	50000 h	21000 h
911401544241	DN592B LED25/840 PSU C D150 WH WB GC	1%	50000 h	21000 h
911401544341	DN592B LED25/930 PSU C D150 WH WB GC	1%	50000 h	21000 h
911401544441	DN592B LED25/940 PSU C D150 WH WB GC	1%	50000 h	21000 h
911401544541	DN592B LED25/830 PSU C D150 WH MB GC	1%	50000 h	21000 h
911401544641	DN592B LED25/840 PSU C D150 WH MB GC	1%	50000 h	21000 h
911401544741	DN592B LED25/930 PSU C D150 WH MB GC	1%	50000 h	21000 h

Order Code	Full Product Name	Driver failure rate at 5000 h	Median useful life L80B50	Median useful life L90B50
911401544841	DN592B LED25/940 PSU C D150 WH MB GC	1%	50000 h	21000 h
911401544941	DN592B LED25/830 PSD C D150 WH WB GC	1%	50000 h	21000 h
911401545041	DN592B LED25/840 PSD C D150 WH WB GC	1%	50000 h	21000 h
911401545141	DN592B LED25/930 PSD C D150 WH WB GC	1%	50000 h	21000 h
911401545241	DN592B LED25/940 PSD C D150 WH WB GC	1%	50000 h	21000 h
911401545341	DN592B LED25/830 PSD C D150 WH MB GC	1%	50000 h	21000 h
911401545441	DN592B LED25/840 PSD C D150 WH MB GC	1%	50000 h	21000 h
911401545541	DN592B LED25/930 PSD C D150 WH MB GC	1%	50000 h	21000 h
911401545641	DN592B LED25/940 PSD C D150 WH MB GC	1%	50000 h	21000 h
911401545741	DN592B LED25/830 POE C D150 WH WB GC	1%	50000 h	21000 h
911401545841	DN592B LED25/840 POE C D150 WH WB GC	1%	50000 h	21000 h
911401545941	DN593B LED30/830 PSU C D200 WH WB GC	1%	50000 h	21000 h
911401546041	DN593B LED30/840 PSU C D200 WH WB GC	1%	50000 h	21000 h
911401546141	DN593B LED30/930 PSU C D200 WH WB GC	1%	50000 h	21000 h
911401546241	DN593B LED30/940 PSU C D200 WH WB GC	1%	50000 h	21000 h
911401546341	DN593B LED30/830 PSU C D200 WH MB GC	1%	50000 h	21000 h
911401546441	DN593B LED30/840 PSU C D200 WH MB GC	1%	50000 h	21000 h
911401546541	DN593B LED30/930 PSU C D200 WH MB GC	1%	50000 h	21000 h
911401546641	DN593B LED30/940 PSU C D200 WH MB GC	1%	50000 h	21000 h
911401546741	DN594B LED40/830 PSU C D200 WH WB GC	1%	50000 h	21000 h
911401546841	DN594B LED40/840 PSU C D200 WH WB GC	1%	50000 h	21000 h
911401546941	DN594B LED40/930 PSU C D200 WH WB GC	1%	50000 h	21000 h
911401547041	DN594B LED40/940 PSU C D200 WH WB GC	1%	50000 h	21000 h
911401547141	DN594B LED40/830 PSU C D200 WH MB GC	1%	50000 h	21000 h
911401547241	DN594B LED40/840 PSU C D200 WH MB GC	1%	50000 h	21000 h

Order Code	Full Product Name	Driver failure rate at 5000 h	Median useful life L80B50	Median useful life L90B50
911401547341	DN594B LED40/930 PSU C D200 WH MB GC	1%	50000 h	21000 h
911401547441	DN594B LED40/940 PSU C D200 WH MB GC	1%	50000 h	21000 h
911401547741	DN589B LED10/830 PSU C D150 WH WB GM	1%	50000 h	21000 h
911401547841	DN589B LED10/840 PSU C D150 WH WB GM	1%	50000 h	21000 h
911401547941	DN590B LED15/830 PSU C D150 WH WB GM	1%	50000 h	21000 h
911401548041	DN590B LED15/840 PSU C D150 WH WB GM	1%	50000 h	21000 h
911401548141	DN591B LED20/830 PSU C D200 WH WB GM	1%	50000 h	21000 h
911401548241	DN591B LED20/840 PSU C D200 WH WB GM	1%	50000 h	21000 h
911401548341	DN593B LED30/830 PSU C D200 WH WB GM	1%	50000 h	21000 h
911401548441	DN593B LED30/840 PSU C D200 WH WB GM	1%	50000 h	21000 h
911401548541	DN594B LED40/830 PSU C D200 WH WB GM	1%	50000 h	21000 h
911401548641	DN594B LED40/840 PSU C D200 WH WB GM	1%	50000 h	21000 h
911401548841	DN589B LED10/830 PSD C D150 WH WB GM	1%	50000 h	21000 h
911401548941	DN589B LED10/840 PSD C D150 WH WB GM	1%	50000 h	21000 h
911401549041	DN590B LED15/840 PSD C D150 WH WB GM	1%	50000 h	21000 h
911401549141	DN591B LED20/830 PSD C D200 WH WB GM	1%	50000 h	21000 h
911401549241	DN591B LED20/840 PSD C D200 WH WB GM	1%	50000 h	21000 h
911401549341	DN593B LED30/840 PSD C D200 WH WB GM	1%	50000 h	21000 h
911401549441	DN594B LED40/840 PSD C D200 WH WB GM	1%	50000 h	21000 h
911401549741	DN589B LED10/830 PSU C D150 WH WB WP GM	1%	50000 h	21000 h
911401549841	DN589B LED10/840 PSU C D150 WH WB WP GM	1%	50000 h	21000 h
911401549941	DN590B LED15/830 PSU C D150 WH WB WP GM	1%	50000 h	21000 h
911401550041	DN590B LED15/840 PSU C D150 WH WB WP GM	1%	50000 h	21000 h
911401550141	DN591B LED20/830 PSU C D200 WH WB WP GM	1%	50000 h	21000 h
911401550241	DN591B LED20/840 PSU C D200 WH WB WP GM	1%	50000 h	21000 h

Order Code	Full Product Name	Driver failure rate at 5000 h	Median useful life L80B50	Median useful life L90B50
911401550341	DN593B LED30/840 PSU C D200 WH WB WP GM	1%	50000 h	21000 h
911401550441	DN594B LED40/840 PSU C D200 WH WB WP GM	1%	50000 h	21000 h
911401550641	DN589B LED10/830 PSD C D150 WH WB WP GM	1%	50000 h	21000 h
911401550741	DN589B LED10/840 PSD C D150 WH WB WP GM	1%	50000 h	21000 h
911401550841	DN590B LED15/840 PSD C D150 WH WB WP GM	1%	50000 h	21000 h
911401550941	DN591B LED20/830 PSD C D200 WH WB WP GM	1%	50000 h	21000 h
911401551041	DN591B LED20/840 PSD C D200 WH WB WP GM	1%	50000 h	21000 h
911401551141	DN593B LED30/840 PSD C D200 WH WB WP GM	1%	50000 h	21000 h
911401551241	DN594B LED40/840 PSD C D200 WH WB WP GM	1%	50000 h	21000 h
911401551341	DN589B LED10/830 PSU C D150 WH WB CAU	1%	50000 h	21000 h
911401551441	DN589B LED10/840 PSU C D150 WH WB CAU	1%	50000 h	21000 h
911401551541	DN590B LED15/840 PSU C D150 WH WB CAU	1%	50000 h	21000 h
911401551641	DN591B LED20/830 PSU C D200 WH WB CAU	1%	50000 h	21000 h
911401551741	DN591B LED20/840 PSU C D200 WH WB CAU	1%	50000 h	21000 h
911401551841	DN593B LED30/840 PSU C D200 WH WB CAU	1%	50000 h	21000 h
911401551941	DN594B LED40/840 PSU C D200 WH WB CAU	1%	50000 h	21000 h
911401552041	DN589B LED10/830 PSD C D150 WH WB CAU	1%	50000 h	21000 h
911401552141	DN589B LED10/840 PSD C D150 WH WB CAU	1%	50000 h	21000 h
911401552241	DN590B LED15/840 PSD C D150 WH WB CAU	1%	50000 h	21000 h
911401552341	DN591B LED20/830 PSD C D200 WH WB CAU	1%	50000 h	21000 h
911401552441	DN591B LED20/840 PSD C D200 WH WB CAU	1%	50000 h	21000 h
911401552541	DN593B LED30/840 PSD C D200 WH WB CAU	1%	50000 h	21000 h
911401552641	DN594B LED40/840 PSD C D200 WH WB CAU	1%	50000 h	21000 h
911401552741	DN589B LED10/830 PSU C D150 WH WB WP CAU	1%	50000 h	21000 h
911401552841	DN589B LED10/840 PSU C D150 WH WB WP CAU	1%	50000 h	21000 h

Order Code	Full Product Name	Driver failure rate at 5000 h	Median useful life L80B50	Median useful life L90B50
911401552941	DN590B LED15/840 PSU C D150 WH WB WP CAU	1%	50000 h	21000 h
911401553041	DN591B LED20/830 PSU C D200 WH WB WP CAU	1%	50000 h	21000 h
911401553141	DN591B LED20/840 PSU C D200 WH WB WP CAU	1%	50000 h	21000 h
911401553241	DN593B LED30/840 PSU C D200 WH WB WP CAU	1%	50000 h	21000 h
911401553341	DN594B LED40/840 PSU C D200 WH WB WP CAU	1%	50000 h	21000 h
911401553441	DN589B LED10/830 PSD C D150 WH WB WP CAU	1%	50000 h	21000 h
911401553541	DN589B LED10/840 PSD C D150 WH WB WP CAU	1%	50000 h	21000 h
911401553641	DN590B LED15/840 PSD C D150 WH WB WP CAU	1%	50000 h	21000 h
911401553741	DN591B LED20/830 PSD C D200 WH WB WP CAU	1%	50000 h	21000 h
911401553841	DN591B LED20/840 PSD C D200 WH WB WP CAU	1%	50000 h	21000 h
911401553941	DN593B LED30/840 PSD C D200 WH WB WP CAU	1%	50000 h	21000 h
911401554041	DN594B LED40/840 PSD C D200 WH WB WP CAU	1%	50000 h	21000 h
911401554141	DN590B LED15/830 POE C D150 WH WB GM	1%	50000 h	21000 h
911401554241	DN590B LED15/840 POE C D150 WH WB GM	1%	50000 h	21000 h
911401554341	DN592B LED25/830 POE C D200 WH WB GM	1%	50000 h	21000 h
911401554441	DN592B LED25/840 POE C D200 WH WB GM	1%	50000 h	21000 h
911401542251	DN591B LED20/TWH PSD C D150 WH MB GM	1%	50000 h	21000 h
911401542351	DN591B LED20/TWH PSD C D150 WH WB GC	1%	50000 h	21000 h
911401542451	DN591B LED20/TWH PSD C D150 WH MB GC	1%	50000 h	21000 h
911401542551	DN591B LED20/TWH PSD C D150 WH WB GM	1%	50000 h	21000 h
911401567271	DN588B LED6/940 PSD C D100 WH CAU	-	-	-
911401567371	DN589B LED10/940 PSD C D125 WH CAU	-	-	-
911401567571	DN590B LED15/940 PSD C D125 WH CAU	-	-	-
911401567771	DN589B LED10/940 PSD C D125 WH WP CAU	-	-	-
911401567471	DN589B LED10/940 PSD C D150 WH CAU	-	-	-

Order Code	Full Product Name	Driver failure rate at 5000 h	Median useful life L80B50	Median useful life L90B50
911401567671	DN590B LED15/940 PSD C D150 WH CAU	-	-	-
911401567871	DN590B LED15/940 PSD C D150 WH WP CAU	-	-	-

Order Code	Full Product Name	Driver failure rate at 5000 h	Median useful life L80B50	Median useful life L90B50
911401567971	DN591B LED15/940 PSD C D200 WH CAU	-	-	-
911401568071	DN591B LED20/940 PSD C D200 WH CAU	-	-	-

