



Robust Design, superior performance, Unparallel strength and Durability with Superior aesthetics suitable for versatile road applications

Skyline BRP340

Skyline is sleek and elegant design innovative streetlight with best in class energy efficiency. Ease of maintenance with integrated optics makes it unique and differentiated from others. Skyline uses High efficacy driver and LED platform to ensure higher energy saving and reliable operation over committed lifetime. Skyline LED Luminaire is a solid LM 6 alloy Pressure die-cast IK 09 rated housing, ensuring high strength and safety on the pole. The solid die-cast aluminum also has excellent heat dissipation, extending the life of the components inside. The multiple lumen packs with dedicated street optics makes it optimum for the A1 and A2 category of Roads.

Benefits

- Maximize the Energy savings
- Unparallel Strength and Durability with excellent thermal management leads to longer life class for luminaire
- Option of multiple optics and lumen packages providing application flexibility
- Easy serviceability with simple tools

Skyline BRP340

Features

- Ingress Protection -IP66
- Impact Resistance IK08
- Inbuilt encapsulated Potted Driver
- Designed for operations under diverse environment from -10°C to 35°C
- Life class is 50000 hours (L70B50 @ Ta35°C)
- Pressure die-cast housing offers excellent corrosion-resistance and robustness
- System efficiency >110 lm/W
- System lumen 14000lm, 16000lm, & 18000lm options
- High Voltage Cutoff @ 325 ± 15V with Auto Restart feature
- 440V Protection for 8 Hrs. (Phase to Phase)
- Internal Surge Protection 4KV
- Mounting Pole Diameter: 48mm to 60mm
- Class B Serviceability with Top openable cover

Application

- Road and Street
- Highways and Express ways
- City main traffic roads
- City shopping & commercial roads
- Residential streets
- Industrial roads

Warnings and Safety

- Meant for use in Outdoor Environment only

Versions



BRP 340 LED

Skyline BRP340

Application conditions

Ambient temperature range	0 to +35 °C
---------------------------	-------------

Approval and application

Mech. impact protection code	IK08
Ingress protection code	IP65

Controls and dimming

Dimmable	No
----------	----

General information

Luminaire light beam spread	60°
Light source color	857 daylight
Optical cover/lens type	Polycarbonate
Driver included	Yes
Flammability mark	For mounting on normally flammable surfaces
Optic type	Asymmetrical axis angle 60° wide beam

Initial performance (IEC compliant)

Init. Corr. Color Temperature	5700 K
Init. Color Rendering Index	>70

Mechanical and housing

Color	Gray
-------	------

Approval and application

Order Code	Full Product Name	Surge Protection (Common/Differential)
919515812407	BRP 340 LED 184 CW HO SLC S1 PSU GR	Surge protection level until 4 kV
919515812535	BRP 340 LED 138 CW HO SLC S1 PSU GR	Surge protection level until 4 kV
919515812537	BRP 340 LED 161 CW HO SLC S1 PSU GR	Surge protection level until 4 kV
919515812539	BRP 340 LED 138 CW HO SLC S1 PSU GR SPD	Surge protection level until 10 kV differential mode
919515812541	BRP 340 LED 161 CW HO SLC S1 PSU GR SPD	Surge protection level until 10 kV differential mode
919515812543	BRP 340 LED 184 CW HO SLC S1 PSU GR SPD	Surge protection level until 10 kV differential mode

Initial performance (IEC compliant)

Order Code	Full Product Name	Initial luminous flux	System Power	Order Code	Full Product Name	Initial luminous flux	System Power
919515812407	BRP 340 LED 184 CW HO SLC S1 PSU GR	18000 lm	160 W	919515812539	BRP 340 LED 138 CW HO SLC S1 PSU GR SPD	14000 lm	120 W
919515812535	BRP 340 LED 138 CW HO SLC S1 PSU GR	14000 lm	120 W	919515812541	BRP 340 LED 161 CW HO SLC S1 PSU GR SPD	16000 lm	140 W
919515812537	BRP 340 LED 161 CW HO SLC S1 PSU GR	16000 lm	140 W	919515812543	BRP 340 LED 184 CW HO SLC S1 PSU GR SPD	18000 lm	160 W

