



TrueLine, suspended - True line of light: elegant, energy- efficient and compliant with office lighting norms

TrueLine, suspended

Architects need a lighting solution that matches the interior architecture of the property they are working on. They want a light line with an elegant design and very high light levels. Specifiers need luminaires that enable them to save energy while at the same time providing the right level of light, in compliance with office lighting norms. TrueLine, suspended is able to meet both sets of requirements. TrueLine is also available in recessed and surface-mounted versions.

Benefits

- The most uniform exit window
- Extremely high efficacy for a line luminaire
- Luminaire housing dimensions most favored by architects

TrueLine, suspended

Features

- Luminous efficacy > 100 lm/W
- Complies with office lighting norms
- Stand-alone and continuous lines
- Recessed version also available
- Direct and indirect light
- Homogeneous exit window
- Future-proof: PoE

Application

- General lighting for mid- and high-end office buildings

Warnings and Safety

- The product is IPX0 & as such is not protected against water ingress & as such we strongly recommend that The environment in which The luminaire is to be installed is suitably checked
- If The above advice is not taken and The luminaires are subject to water ingress, Philips / Signify cannot guarantee safe failure & product warranty will become void

Specifications

Type	SP530P (office compliant direct-light version)
	SP531P (non-office compliant direct-light version)
	SP532P (office compliant direct/indirect-light version)
	SP533P (non-office compliant direct/indirect-light version)
Light source	Non-replaceable LED module


Power	Office compliant (OC), 1130 and 1170 mm, 4000 K versions:
	10 W (direct 1500 lm)
	17.5 W (direct 2500 lm)
	24 W (direct 3400 lm)
	29 W (direct 4000 lm)
	15.2 W (direct 1500 lm, indirect 660 lm, total 2160 lm)
	25.5 W (direct 2500 lm, indirect 1100 lm, total 3600 lm)
	35.5 W (direct 3400 lm, indirect 1550 lm, total 4950 lm)
	42.5 W (direct 4000 lm, indirect 1850 lm, total 5850 lm)
	Non-office compliant (NOC) 1130 and 1170 mm, 4000 K versions:
	14.6 W (direct 1500 lm)
	24.5 W (direct 2500 lm)
	21 W (direct 1500 lm, indirect 940 lm, total 2440 lm)
	36 W (direct 2500 lm, indirect 1600 lm, total 4100 lm)
	Office compliant (OC) 1410 and 1450 mm, 4000 K versions:
	12.4 W (direct 1900 lm)
	21.5 W (direct 3100 lm)
	32 W (direct 4300 lm)
	38.5 W (direct 5000 lm)
	19.2 W (direct 1900 lm, indirect 1000 lm, total 2900 lm)
	34 W (direct 3100 lm, indirect 1650 lm, total 4750 lm)
	50 W (direct 4300 lm, indirect 2300 lm, total 6600 lm)
	60 W (direct 5000 lm, indirect 2700 lm, total 7700 lm)
	Non-office compliant (OC) 1410 and 1450 mm, 4000 K versions:
	17.8 W (direct 1900 lm)
	32 W (direct 3100 lm)
	29 W (direct 1900 lm, indirect 1400 lm, total 3300 lm)
	51 W (direct 3100 lm, indirect 2300 lm, total 5400 lm)
	Office compliant (OC) 1130 and 1170 mm, 3000 K versions:
	10.6 W (direct 1500 lm)
	18.2W (direct 2500 lm)

TrueLine, suspended

25.5 W (direct 3400 lm)
30.5 W (direct 4000 lm)
16 W (direct 1500, indirect 660, total 2160 lm)
26.5 W (direct 2500, indirect 1100, total 3600 lm)
37.5 W (direct 3400, indirect 1550, total 4950 lm)
44.5 W (direct 4000, indirect 1850, total 5850 lm)
Non-office compliant (NOC) 1130 and 1170mm, 3000 K:
15.6 W (direct 1500 lm)
26 W (direct 2500 lm)
22 W (direct 1500 lm, indirect 940 lm, total 2440 lm)
38.5 W (direct 2500 lm, indirect 1600 lm, total 4100 lm)
Office compliant (OC) 1410 and 1450 mm, 3000 K versions:
13 W (direct 1900 lm)
23 W (direct 3100 lm)
34 W (direct 4300 lm)
40.5 W (direct 5000 lm)
20 W (direct 1900 lm, indirect 1000 lm, total 2900 lm)
36 W (direct 3100 lm, indirect 1650 lm, total 4750 lm)
53 W (direct 4300 lm, indirect 2300 lm, total 6600 lm)
64 W (direct 5000 lm, indirect 2700 lm, total 7700 lm)
Non-office compliant (OC) 1410 and 1450 mm, 3000 K versions:
18.8 W (direct 1900 lm)
34 W (direct 3100 lm)
31 W (direct 1900 lm, indirect 1400 lm, total 3300 lm)
55 W (direct 3100 lm, indirect 2300 lm, total 5400 lm)
Beam angle 80 ° (OC), 110 ° (NOC)
Luminous flux 1500 to 7700 lm (4000 K)
Correlated Color 3000 or 4000 K
Temperature
Color Rendering Index >80
Lumen maintenance at median useful life L90
50000 h

Control gear failure rate 5%
at median useful life
50000 h
Average ambient temperature +25 °C
Operating temperature range +10 to +40 °C
Driver Built-in
Power/Data supply PDS-60 24 V; supply for indoor and outdoor applications
Mains voltage 220-240 V / 50-60 Hz
Dimming Compatible with many commercial available ELV dimmers
Controls system input 0-16 V, DALI
Options Central battery
Material Housing: anodized aluminum Driver box: steel Cover: PMMA or polycarbonate
Color Aluminum (ALU)
Optical cover Office compliant: PMMA, semi-transparent Non-office compliant: polycarbonate, opal
Connection Push-in connector (PI) or with pull relief (PIP)
Maintenance Optical module replaceable, no internal cleaning required
Installation Fixation by means of brackets Individual or in line; suspended mounting with three different options: SM2 (one 2-wire bag, one Reutlinger for ceiling side, one ceiling cap) SW2 (one 2-wire bag, one (for LF1) or two (for BV/LE1) Reutlingers, one tool to fix the alignment profile (for LF1)) SMTT (one 2-wire bag, one (for LF1) or two (for BV/LE1) T-bar ceiling clips, one (for LF1) or two (for BV/LE1) Reutlingers, one tool to fix the alignment profile (for LF1)) Through-wiring possible
Remarks Suspension set to be delivered with the luminaire

Versions



Trueline suspended SP530B luminaire, office-compliant version with direct lighting, 1.2 m



TrueLine Suspended DIRECT Asym

TrueLine, suspended

Versions



TrueLine DIRECT/INDIRECT OC - 940 neutral white - Power supply unit with DALI interface - Push-in connector 5-pole - Black



TrueLine Suspended DIRECT Asym - 940 neutral white - Power supply unit with DALI interface - Push-in connector 5-pole - Aluminum



TrueLine DIRECT/INDIRECT OC - 940 neutral white - Power supply unit with DALI interface - Push-in connector 5-pole - Aluminum



TrueLine DIRECT OC - 940 neutral white - Power supply unit with SystemReady interface, InterAct ready - Push-in connector 3-pole - Aluminum



TrueLine DIRECT OC - 940 neutral white - Power supply unit with DALI interface - Push-in connector 5-pole - Aluminum



TrueLine DIRECT NOC - 940 neutral white - Power supply unit with DALI interface - Push-in connector 5-pole - White RAL 9003



TrueLine DIRECT OC - 940 neutral white - Power supply unit with DALI interface - Push-in connector 5-pole - Black RAL 9004



TrueLine DIRECT OC - 930 warm white - Power supply unit with DALI interface - Push-in connector 5-pole - Black RAL 9004



TrueLine DIRECT NOC - 930 warm white - Power supply unit with DALI and SystemReady interface, InterAct ready - Push-in connector 3-pole - Aluminum

TrueLine, suspended

Versions



TrueLine DIRECT OC - 940 neutral white - Power supply unit with DALI and SystemReady interface, InterAct ready - Push-in connector 3-pole - Black RAL 9004



TrueLine DIRECT OC - 930 warm white - Power supply unit with DALI interface - Push-in connector 5-pole - White RAL 9003



TrueLine DIRECT OC - Tunable white - Power supply unit with DALI and SystemReady interface, InterAct ready - Push-in connector 3-pole - Aluminum

Product details



TrueLine_Suspended-U3



TrueLine_Suspended-U0



TrueLine Suspended black housing



TrueLine Suspended black housing



TrueLine Suspended-SP530P-LF-power-cable-03



TrueLine_Suspended-line-side-view

TrueLine, suspended

Product details



TrueLine_Suspended-line-top-view



TrueLine_Suspended-top-view



TrueLine_SM_SP-line-connection-side-view-2



TrueLine_accessories_U5-DP

TrueLine_accessories_U6-DP



TrueLine_accessories_U4-DP



TrueLine-SP-line-U3



TrueLine, suspended

Accessories



TrueLine Accessories -- V -- Hz
----- White

Ordercode 910505101357



TrueLine Accessories -- V -- Hz
----- White

Ordercode 910505101358



TrueLine Accessories -- V -- Hz
----- White

Ordercode 910505101359



TrueLine Accessories -- V -- Hz
----- White

Ordercode 910505101665

Application conditions

Ambient temperature range	+10 to +40 °C
Maximum dim level	1%
Suitable for random switching	No

Approval and application

Mech. impact protection code	IK02
Ingress protection code	IP20

Controls and dimming

Dimmable	Yes
----------	-----

Operating and electrical

Input Voltage	220 to 240 V
---------------	--------------

General information

Beam angle of light source	120 °
CE mark	CE mark
Driver included	Yes
ENEC mark	ENEC mark
Flammability mark	For mounting on normally flammable surfaces
Glow-wire test	Temperature 650 °C, duration 30 s
Light source replaceable	No
Optic type	-

Initial performance (IEC compliant)

Initial chromaticy	(0.38, 0.38) SDCM <3
Init. Color Rendering Index	>90
Luminous flux tolerance	+/-10%

Light technical

Flickering	1
Stroboscopic effect	0.4

General information

Order Code	Full Product Name	Protection class IEC	Number of gear units	Product Family Code
910505103161	SP533P LED41S/940 PSD PI5 SM2 L1130 ALU	Safety class I	1 unit	SP533P
910505103162	SP532P LED29S/940 PSD PI5 SM2 L1410 WH	Safety class I	1 unit	SP532P
910505103163	SP530P LED50S/940 PSD PI5 SM2 L1410 ALU	Safety class I	1 unit	SP530P
910505103164	SP532P LED47S/940 PSD PI5 SM2 L1410 ALU	Safety class I	1 unit	SP532P
910505103165	SP530P LED25S/940 POE SW2 L1130 ALU	Safety class III	1 unit	SP530P
910505103166	SP531P LED15S/940 PSD PI5 SM2 L1130 ALU	Safety class I	1 unit	SP531P
910505103167	SP530P LED43S/940 PSD PI5 SM2 L1410 ALU	Safety class I	1 unit	SP530P
910505103168	SP532P LED77S/940 PSD PI5 SM2 L1410 ALU	Safety class I	1 unit	SP532P
910505103169	SP532P LED36S/940 PSD PI5 SM2 L1130 ALU	Safety class I	1 unit	SP532P
910505103170	SP532P LED58S/940 PSD PI5 SM2 L1130 ALU	Safety class I	1 unit	SP532P
910505103171	SP530P LED34S/940 PSD PI5 SM2 L1130 ALU	Safety class I	1 unit	SP530P
910505103172	SP533P LED33S/930 PSD PI5 SM2 L1410 ALU	Safety class I	1 unit	SP533P
910505103173	SP532P LED49S/930 PSD PI5 SM2 L1130 ALU	Safety class I	1 unit	SP532P
910505103174	SP532P LED77S/930 PSD PI5 SM2 L1410 ALU	Safety class I	1 unit	SP532P
910505103175	SP532P LED36S/940 PSD PI5 SM2 L1130 WH	Safety class I	1 unit	SP532P
910505103176	SP533P LED33S/930 PSD PI5 SM2 L1410 WH	Safety class I	1 unit	SP533P
910505103177	SP534P LED40S/940 PSD PI5 SM2 L1130 ALU	Safety class I	1 unit	SP534P
910505103180	SP533P LED24S/940 PSD PI5 SM2 L1130 ALU	Safety class I	1 unit	SP533P
910505103181	SP532P LED21S/940 PSD PI5 SM2 L1130 ALU	Safety class I	1 unit	SP532P
910505103182	SP533P LED33S/940 PSD PI5 SM2 L1410 ALU	Safety class I	1 unit	SP533P
910505103183	SP532P LED29S/940 PSD PI5 SM2 L1410 ALU	Safety class I	1 unit	SP532P
910505103185	SP532P LED66S/940 PSD PI5 SM2 L1410 ALU	Safety class I	1 unit	SP532P
910505103186	SP533P LED54S/940 PSD PI5 SM2 L1410 ALU	Safety class I	1 unit	SP533P
910505103187	SP532P LED49S/940 PSD PI5 SM2 L1130 ALU	Safety class I	1 unit	SP532P
910505103188	SP532P LED66S/940 PSD PI5 SM2 L1410 WH	Safety class I	1 unit	SP532P

Order Code	Full Product Name	Protection class IEC	Number of gear units	Product Family Code
910505103189	SP532P LED47S/940 PSD PI5 SM2 L1410 WH	Safety class I	1 unit	SP532P
910505103191	SP530P LED31S/940 POE U3 SW2 L1450 ALU	Safety class III	1 unit	SP530P
910505103192	SP530P LED40S/940 POE U3 SW2 L1170 ALU	Safety class III	1 unit	SP530P
910505103193	SP530P LED40S/940 POE U0 SW2 L1170 ALU	Safety class III	1 unit	SP530P
910505103194	SP530P LED43S/940 POE U0 SW2 L1450 ALU	Safety class III	1 unit	SP530P
910505103196	SP530P LED40S/940 PSD PI5 SM2 L1130 ALU	Safety class I	1 unit	SP530P
910505103184	SP534P LED50S/940 PSD PI5 SM2 L1410 ALU	Safety class I	1 unit	SP534P
910505103197	SP532P LED47S/940 PSD PI5 SM2 L1410 BK	Safety class I	1 unit	SP532P
910505103198	SP531P LED15S/940 PSD PI5 SM2 L1130 BK	Safety class I	1 unit	SP531P
910505103199	SP530P LED34S/940 PSD PI5 SM2 L1130 BK	Safety class I	1 unit	SP530P
910505103201	SP532P LED29S/930 PSD LF2 PI5 SM2L1410BK	Safety class I	1 unit	SP532P
910505103202	SP532P LED29S/940 PSD LF2 PI5 SM2L1410BK	Safety class I	1 unit	SP532P
910505103207	SP532P LED36S/940 PSD LF2 PI5SM2TL1130BK	Safety class I	1 unit	SP532P
910505103203	SP532P LED47S/940 PSD LE1 PI5SM2L1410ALU	Safety class I	1 unit	SP532P
910505103206	SP534P LED34S/940 PSD LE1 PI5SM2L1130ALU	Safety class I	1 unit	SP534P
910505103210	SP532P LED29S/940 PSD LE1 PI5SM2L1410ALU	Safety class I	1 unit	SP532P
910505103213	SP534P LED43S/940 PSD LE1 PI5SM2L1410ALU	Safety class I	1 unit	SP534P
910505103204	SP532P LED29S/940 PSD LF1 PI5SW2L1410ALU	Safety class I	1 unit	SP532P
910505103205	SP532P LED36S/940 PSD LF2 PI5SM2TL1130AL	Safety class I	1 unit	SP532P
910505103208	SP532P LED29S/940 PSD LF2 PI5 SM2L1410AL	Safety class I	1 unit	SP532P
910505103209	SP534P LED43S/940 PSD LF1 PI5SW2L1410ALU	Safety class I	1 unit	SP534P
910505103211	SP532P LED47S/940 PSD LF1 PI5SW2L1410ALU	Safety class I	1 unit	SP532P
910505103212	SP532P LED36S/940 PSD LF1 PI5SW2L1130ALU	Safety class I	1 unit	SP532P
910505103279	SP532P LED36S/TW9 DIA LF1 PI5 L1130 ALU	Safety class I	1 unit	SP532P
910505103280	SP533P LED33S/TW9 DIA LF1 PI5 L1410 ALU	Safety class I	2 units	SP533P

Order Code	Full Product Name	Protection class IEC	Number of gear units	Product Family Code
910505103214	SP532P LED47S/940 SRD U4 PI3 SM2L1450ALU	Safety class I	1 unit	SP532P
910505103215	SP530P LED40S/940 SRD U4 PI3 SM2L1170ALU	Safety class I	1 unit	SP530P
910505103216	SP532P LED66S/940 SRD U4 PI3 SM2L1450ALU	Safety class I	1 unit	SP532P
910505103244	SP530P LED7S/940 PSD LE2 PI5 SM2L570 ALU	Safety class I	1 unit	SP530P
910505103247	SP532P LED10S/930 PSD LE2 PI5 L570 ALU	Safety class I	1 unit	SP532P
910505103245	SP531P LED7S/940 PSD LE2 PI5 SM2 L570 WH	Safety class I	1 unit	SP531P
910505103249	SP533P LED12S/930 PSD LE2 PI5 SM2L570 WH	Safety class I	1 unit	SP533P
910505103246	SP530P LED17S/940 PSD LE2PI5 SM2 L570 BK	Safety class I	1 unit	SP530P
910505103248	SP532P LED24S/930 PSD LE2 PI5 SM2L570 BK	Safety class I	1 unit	SP532P
910505103256	SP530P LED30S/930 PSD LF1 PI5 L2250 BK	Safety class I	1 unit	SP530P
910505103257	SP531P LED30S/930 SRD U4LF1PI3 L2290 ALU	Safety class I	1 unit	SP531P
910505103260	SP532P LED72S/940 PSD PI5 SM2 L2250 ALU	Safety class I	1 unit	SP532P
910505103261	SP533P LED48S/940 PSD PI5 SM2 L2250 ALU	Safety class I	1 unit	SP533P
910505103263	SP533P LED82S/940 PSD PI5 SM2 L2250 ALU	Safety class I	1 unit	SP533P
910505103269	SP530P LED38S/930 PSD LF1 PI5 L2810 ALU	Safety class I	1 unit	SP530P
910505103273	SP532P LED58S/930 PSD LF1 PI5 L2810 ALU	Safety class I	1 unit	SP532P
910505103274	SP533P LED66S/930 PSD LF1 PI5 L2810 ALU	Safety class I	1 unit	SP533P
910505103258	SP530P LED50S/940 SRD U4 PI5 SM2L2290 BK	Safety class I	1 unit	SP530P
910505103262	SP532P LED98S/940 SRD U4 PI5 SM2L2290 BK	Safety class I	1 unit	SP532P
910505103270	SP530P LED62S/940 SRD U4 PI5 SM2L2850 BK	Safety class I	1 unit	SP530P
910505103281	SP532P LED66S/TW9 SIA PI3 U4 L1450 BK	Safety class I	2 units	SP532P
910505103259	SP530P LED50S/930 PSD PI5 SM2 L2250 WH	Safety class I	1 unit	SP530P
910505103271	SP531P LED62S/930 PSD PI5 SM2L2810 WH	Safety class I	1 unit	SP531P
910505103272	SP532P LED94S/940 PSD PI5 SM2L2810 WH	Safety class I	1 unit	SP532P
910505103282	SP530P LED50S/TW9 SIA SM2 U4 L2290 ALU	Safety class I	2 units	SP530P
910505103283	SP530P LED86S/TW9 SIA SM2 U4 L2850 ALU	Safety class I	2 units	SP532P

Initial performance (IEC compliant)

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
910505103161	SP533P LED41S/940 PSD Pi5 SM2 L1130 ALU	4000 K	115 lm/W	4100 lm	35.5 W
910505103162	SP532P LED29S/940 PSD Pi5 SM2 L1410 WH	4000 K	138 lm/W	2900 lm	21 W
910505103163	SP530P LED50S/940 PSD Pi5 SM2 L1410 ALU	4000 K	139 lm/W	5000 lm	36 W
910505103164	SP532P LED47S/940 PSD Pi5 SM2 L1410 ALU	4000 K	138 lm/W	4700 lm	34 W
910505103165	SP530P LED25S/940 POE SW2 L1130 ALU	4000 K	149 lm/W	2500 lm	16.8 W
910505103166	SP531P LED15S/940 PSD Pi5 SM2 L1130 ALU	4000 K	104 lm/W	1500 lm	14.4 W
910505103167	SP530P LED43S/940 PSD Pi5 SM2 L1410 ALU	4000 K	141 lm/W	4300 lm	30.5 W
910505103168	SP532P LED77S/940 PSD Pi5 SM2 L1410 ALU	4000 K	135 lm/W	7700 lm	57 W
910505103169	SP532P LED36S/940 PSD Pi5 SM2 L1130 ALU	4000 K	136 lm/W	3600 lm	26.5 W
910505103170	SP532P LED58S/940 PSD Pi5 SM2 L1130 ALU	4000 K	133 lm/W	5850 lm	44 W
910505103171	SP530P LED34S/940 PSD Pi5 SM2 L1130 ALU	4000 K	139 lm/W	3400 lm	24.5 W
910505103172	SP533P LED33S/930 PSD Pi5 SM2 L1410 ALU	3000 K	112 lm/W	3300 lm	29.5 W
910505103173	SP532P LED49S/930 PSD Pi5 SM2 L1130 ALU	3000 K	129 lm/W	4950 lm	38.5 W
910505103174	SP532P LED77S/930 PSD Pi5 SM2 L1410 ALU	3000 K	128 lm/W	7700 lm	60 W
910505103175	SP532P LED36S/940 PSD Pi5 SM2 L1130 WH	4000 K	136 lm/W	3600 lm	26.5 W
910505103176	SP533P LED33S/930 PSD Pi5 SM2 L1410 WH	3000 K	112 lm/W	3300 lm	29.5 W

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
910505103177	SP534P LED40S/940 PSD Pi5 SM2 L1130 ALU	4000 K	129 lm/W	4000 lm	31 W
910505103180	SP533P LED24S/940 PSD Pi5 SM2 L1130 ALU	4000 K	116 lm/W	2440 lm	21 W
910505103181	SP532P LED21S/940 PSD Pi5 SM2 L1130 ALU	4000 K	132 lm/W	2160 lm	16.4 W
910505103182	SP533P LED33S/940 PSD Pi5 SM2 L1410 ALU	4000 K	118 lm/W	3300 lm	28 W
910505103183	SP532P LED29S/940 PSD Pi5 SM2 L1410 ALU	4000 K	138 lm/W	2900 lm	21 W
910505103185	SP532P LED66S/940 PSD Pi5 SM2 L1410 ALU	4000 K	138 lm/W	6600 lm	48 W
910505103186	SP533P LED54S/940 PSD Pi5 SM2 L1410 ALU	4000 K	116 lm/W	5400 lm	46.5 W
910505103187	SP532P LED49S/940 PSD Pi5 SM2 L1130 ALU	4000 K	136 lm/W	4950 lm	36.5 W
910505103188	SP532P LED66S/940 PSD Pi5 SM2 L1410 WH	4000 K	138 lm/W	6600 lm	48 W
910505103189	SP532P LED47S/940 PSD Pi5 SM2 L1410 WH	4000 K	138 lm/W	4700 lm	34 W
910505103191	SP530P LED31S/940 POE U3 SW2 L1450 ALU	4000 K	148 lm/W	3100 lm	21 W
910505103192	SP530P LED40S/940 POE U3 SW2 L1170 ALU	4000 K	143 lm/W	4000 lm	28 W
910505103193	SP530P LED40S/940 POE U0 SW2 L1170 ALU	4000 K	143 lm/W	4000 lm	28 W
910505103194	SP530P LED43S/940 POE U0 SW2 L1450 ALU	4000 K	143 lm/W	4300 lm	30 W
910505103196	SP530P LED40S/940 PSD Pi5 SM2 L1130 ALU	4000 K	140 lm/W	4000 lm	28.5 W
910505103184	SP534P LED50S/940 PSD Pi5 SM2 L1410 ALU	4000 K	130 lm/W	5000 lm	38.5 W

TrueLine, suspended

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
910505103197	SP532P LED47S/940 PSD PI5 SM2 L1410 BK	4000 K	138 lm/W	4700 lm	34 W
910505103198	SP531P LED15S/940 PSD PI5 SM2 L1130 BK	4000 K	104 lm/W	1500 lm	14.4 W
910505103199	SP530P LED34S/940 PSD PI5 SM2 L1130 BK	4000 K	139 lm/W	3400 lm	24.5 W
910505103201	SP532P LED29S/930 PSD LF2 PI5 SM2L1410BK	3000 K	132 lm/W	2900 lm	22 W
910505103202	SP532P LED29S/940 PSD LF2 PI5 SM2L1410BK	4000 K	138 lm/W	2900 lm	21 W
910505103207	SP532P LED36S/940 PSD LF2 PI5SM2TL1130BK	4000 K	136 lm/W	3600 lm	26.5 W
910505103203	SP532P LED47S/940 PSD LE1 PI5SM2L1410ALU	4000 K	138 lm/W	4700 lm	34 W
910505103206	SP534P LED34S/940 PSD LE1 PI5SM2L1130ALU	4000 K	131 lm/W	3400 lm	26 W
910505103210	SP532P LED29S/940 PSD LE1 PI5SM2L1410ALU	4000 K	138 lm/W	2900 lm	21 W
910505103213	SP534P LED43S/940 PSD LE1 PI5SM2L1410ALU	4000 K	132 lm/W	4300 lm	32.5 W
910505103204	SP532P LED29S/940 PSD LF1 PI5SW2L1410ALU	4000 K	138 lm/W	2900 lm	21 W
910505103205	SP532P LED36S/940 PSD LF2 PI5SM2TL1130AL	4000 K	136 lm/W	3600 lm	26.5 W
910505103208	SP532P LED29S/940 PSD LF2 PI5 SM2L1410AL	4000 K	138 lm/W	2900 lm	21 W
910505103209	SP534P LED43S/940 PSD LF1 PI5SW2L1410ALU	4000 K	132 lm/W	4300 lm	32.5 W
910505103211	SP532P LED47S/940 PSD LF1 PI5SW2L1410ALU	4000 K	138 lm/W	4700 lm	34 W
910505103212	SP532P LED36S/940 PSD LF1 PI5SW2L1130ALU	4000 K	136 lm/W	3600 lm	26.5 W
910505103279	SP532P LED36S/TW9 DIA LF1 PI5 L1130 ALU	Tunable white 2700-6500	124 lm/W	3600 lm	29 W

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
910505103280	SP533P LED33S/TW9 DIA LF1 PI5 L1410 ALU	Tunable white 2700-6500	100 lm/W	3300 lm	33 W
910505103214	SP532P LED47S/940 SRD U4 PI3 SM2L1450ALU	4000 K	138 lm/W	4700 lm	34 W
910505103215	SP530P LED40S/940 SRD U4 PI3 SM2L1170ALU	4000 K	143 lm/W	4000 lm	28 W
910505103216	SP532P LED66S/940 SRD U4 PI3 SM2L1450ALU	4000 K	139 lm/W	6600 lm	47.5 W
910505103244	SP530P LED7S/940 PSD LE2 PI5 SM2L570 ALU	4000 K	125 lm/W	750 lm	6 W
910505103247	SP532P LED10S/930 PSD LE2 PI5 L570 ALU	3000 K	124 lm/W	1050 lm	8.5 W
910505103245	SP531P LED7S/940 PSD LE2 PI5 SM2 L570 WH	4000 K	104 lm/W	750 lm	7.2 W
910505103249	SP533P LED12S/930 PSD LE2 PI5 SM2L570 WH	3000 K	109 lm/W	1200 lm	11 W
910505103246	SP530P LED17S/940 PSD LE2PI5 SM2 L570 BK	4000 K	139 lm/W	1700 lm	12.2 W
910505103248	SP532P LED24S/930 PSD LE2 PI5 SM2L570 BK	3000 K	132 lm/W	2450 lm	18.6 W
910505103256	SP530P LED30S/930 PSD LF1 PI5 L2250 BK	3000 K	130 lm/W	3000 lm	23 W
910505103257	SP531P LED30S/930 SRD U4LF1PI3 L2290 ALU	3000 K	103 lm/W	3000 lm	29 W
910505103260	SP532P LED72S/940 PSD PI5 SM2 L2250 ALU	4000 K	138 lm/W	7200 lm	52 W
910505103261	SP533P LED48S/940 PSD PI5 SM2 L2250 ALU	4000 K	122 lm/W	4800 lm	39.5 W
910505103263	SP533P LED82S/940 PSD PI5 SM2 L2250 ALU	4000 K	119 lm/W	8200 lm	69 W
910505103269	SP530P LED38S/930 PSD LF1 PI5 L2810 ALU	3000 K	136 lm/W	3800 lm	28 W
910505103273	SP532P LED58S/930 PSD LF1 PI5 L2810 ALU	3000 K	132 lm/W	5800 lm	44 W

TrueLine, suspended

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
910505103274	SP533P LED66S/930 PSD LF1 PI5 L2810 ALU	3000 K	114 lm/W	6600 lm	58 W
910505103258	SP530P LED50S/940 SRD U4 PI5 SM2L2290 BK	4000 K	139 lm/W	5000 lm	36 W
910505103262	SP532P LED98S/940 SRD U4 PI5 SM2L2290 BK	4000 K	138 lm/W	9800 lm	71 W
910505103270	SP530P LED62S/940 SRD U4 PI5 SM2L2850 BK	4000 K	141 lm/W	6200 lm	44 W
910505103281	SP532P LED66S/TW9 SIA PI3 U4 L1450 BK	Tunable white 2700-6500	116 lm/W	6600 lm	57 W
910505103259	SP530P LED50S/930 PSD PI5 SM2 L2250 WH	3000 K	133 lm/W	5000 lm	37.5 W

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
910505103271	SP531P LED62S/930 PSD PI5 SM2L2810 WH	3000 K	135 lm/W	6200 lm	46 W
910505103272	SP532P LED94S/940 PSD PI5 SM2L2810 WH	4000 K	140 lm/W	9400 lm	67 W
910505103282	SP530P LED50S/TW9 SIA SM2 U4 L2290 ALU	Tunable white 2700-6500	125 lm/W	5000 lm	40 W
910505103283	SP530P LED86S/TW9 SIA SM2 U4 L2850 ALU	Tunable white 2700-6500	121 lm/W	8600 lm	71 W

Mechanical and housing

Order Code	Full Product Name	Color
910505103161	SP533P LED41S/940 PSD PI5 SM2 L1130 ALU	Aluminum
910505103162	SP532P LED29S/940 PSD PI5 SM2 L1410 WH	White RAL 9003
910505103163	SP530P LED50S/940 PSD PI5 SM2 L1410 ALU	Aluminum
910505103164	SP532P LED47S/940 PSD PI5 SM2 L1410 ALU	Aluminum
910505103165	SP530P LED25S/940 POE SW2 L1130 ALU	Aluminum
910505103166	SP531P LED15S/940 PSD PI5 SM2 L1130 ALU	Aluminum
910505103167	SP530P LED43S/940 PSD PI5 SM2 L1410 ALU	Aluminum
910505103168	SP532P LED77S/940 PSD PI5 SM2 L1410 ALU	Aluminum
910505103169	SP532P LED36S/940 PSD PI5 SM2 L1130 ALU	Aluminum
910505103170	SP532P LED58S/940 PSD PI5 SM2 L1130 ALU	Aluminum
910505103171	SP530P LED34S/940 PSD PI5 SM2 L1130 ALU	Aluminum
910505103172	SP533P LED33S/930 PSD PI5 SM2 L1410 ALU	Aluminum
910505103173	SP532P LED49S/930 PSD PI5 SM2 L1130 ALU	Aluminum
910505103174	SP532P LED77S/930 PSD PI5 SM2 L1410 ALU	Aluminum
910505103175	SP532P LED36S/940 PSD PI5 SM2 L1130 WH	White RAL 9003
910505103176	SP533P LED33S/930 PSD PI5 SM2 L1410 WH	White RAL 9003
910505103177	SP534P LED40S/940 PSD PI5 SM2 L1130 ALU	Aluminum
910505103180	SP533P LED24S/940 PSD PI5 SM2 L1130 ALU	Aluminum
910505103181	SP532P LED21S/940 PSD PI5 SM2 L1130 ALU	Aluminum
910505103182	SP533P LED33S/940 PSD PI5 SM2 L1410 ALU	Aluminum
910505103183	SP532P LED29S/940 PSD PI5 SM2 L1410 ALU	Aluminum
910505103185	SP532P LED66S/940 PSD PI5 SM2 L1410 ALU	Aluminum
910505103186	SP533P LED54S/940 PSD PI5 SM2 L1410 ALU	Aluminum
910505103187	SP532P LED49S/940 PSD PI5 SM2 L1130 ALU	Aluminum
910505103188	SP532P LED66S/940 PSD PI5 SM2 L1410 WH	White RAL 9003
910505103189	SP532P LED47S/940 PSD PI5 SM2 L1410 WH	White RAL 9003
910505103191	SP530P LED31S/940 POE U3 SW2 L1450 ALU	Aluminum
910505103192	SP530P LED40S/940 POE U3 SW2 L1170 ALU	Aluminum
910505103193	SP530P LED40S/940 POE U0 SW2 L1170 ALU	Aluminum

Order Code	Full Product Name	Color
910505103194	SP530P LED43S/940 POE U0 SW2 L1450 ALU	Aluminum
910505103196	SP530P LED40S/940 PSD PI5 SM2 L1130 ALU	Aluminum
910505103184	SP534P LED50S/940 PSD PI5 SM2 L1410 ALU	Aluminum
910505103197	SP532P LED47S/940 PSD PI5 SM2 L1410 BK	Black RAL 9004
910505103198	SP531P LED15S/940 PSD PI5 SM2 L1130 BK	Black RAL 9004
910505103199	SP530P LED34S/940 PSD PI5 SM2 L1130 BK	Black RAL 9004
910505103201	SP532P LED29S/930 PSD LF2 PI5 SM2L1410BK	Black RAL 9004
910505103202	SP532P LED29S/940 PSD LF2 PI5 SM2L1410BK	Black RAL 9004
910505103207	SP532P LED36S/940 PSD LF2 PI5SM2TL1130BK	Black RAL 9004
910505103203	SP532P LED47S/940 PSD LE1 PI5SM2L1410ALU	Aluminum
910505103206	SP534P LED34S/940 PSD LE1 PI5SM2L1130ALU	Aluminum
910505103210	SP532P LED29S/940 PSD LE1 PI5SM2L1410ALU	Aluminum
910505103213	SP534P LED43S/940 PSD LE1 PI5SM2L1410ALU	Aluminum
910505103204	SP532P LED29S/940 PSD LF1 PI5SW2L1410ALU	Aluminum
910505103205	SP532P LED36S/940 PSD LF2 PI5SM2TL1130AL	Aluminum
910505103208	SP532P LED29S/940 PSD LF2 PI5 SM2L1410AL	Aluminum
910505103209	SP534P LED43S/940 PSD LF1 PI5SW2L1410ALU	Aluminum
910505103211	SP532P LED47S/940 PSD LF1 PI5SW2L1410ALU	Aluminum
910505103212	SP532P LED36S/940 PSD LF1 PI5SW2L1130ALU	Aluminum
910505103279	SP532P LED36S/TW9 DIA LF1 PI5 L1130 ALU	Aluminum
910505103280	SP533P LED33S/TW9 DIA LF1 PI5 L1410 ALU	Aluminum
910505103214	SP532P LED47S/940 SRD U4 PI3 SM2L1450ALU	Aluminum
910505103215	SP530P LED40S/940 SRD U4 PI3 SM2L1170ALU	Aluminum
910505103216	SP532P LED66S/940 SRD U4 PI3 SM2L1450ALU	Aluminum
910505103244	SP530P LED7S/940 PSD LE2 PI5 SM2L570 ALU	Aluminum
910505103247	SP532P LED10S/930 PSD LE2 PI5 L570 ALU	Aluminum
910505103245	SP531P LED7S/940 PSD LE2 PI5 SM2 L570 WH	White RAL 9003
910505103249	SP533P LED12S/930 PSD LE2 PI5 SM2L570 WH	White RAL 9003
910505103246	SP530P LED17S/940 PSD LE2PI5 SM2 L570 BK	Black RAL 9004

TrueLine, suspended

Order Code	Full Product Name	Color
910505103248	SP532P LED24S/930 PSD LE2 PI5 SM2L570 BK	Black RAL 9004
910505103256	SP530P LED30S/930 PSD LF1 PI5 L2250 BK	Black RAL 9004
910505103257	SP531P LED30S/930 SRD U4LF1PI3 L2290 ALU	Aluminum
910505103260	SP532P LED72S/940 PSD PI5 SM2 L2250 ALU	Aluminum
910505103261	SP533P LED48S/940 PSD PI5 SM2 L2250 ALU	Aluminum
910505103263	SP533P LED82S/940 PSD PI5 SM2 L2250 ALU	Aluminum
910505103269	SP530P LED38S/930 PSD LF1 PI5 L2810 ALU	Aluminum
910505103273	SP532P LED58S/930 PSD LF1 PI5 L2810 ALU	Aluminum
910505103274	SP533P LED66S/930 PSD LF1 PI5 L2810 ALU	Aluminum

Order Code	Full Product Name	Color
910505103258	SP530P LED50S/940 SRD U4 PI5 SM2L2290 BK	Black RAL 9004
910505103262	SP532P LED98S/940 SRD U4 PI5 SM2L2290 BK	Black RAL 9004
910505103270	SP530P LED62S/940 SRD U4 PI5 SM2L2850 BK	Black RAL 9004
910505103281	SP532P LED66S/TW9 SIA PI3 U4 L1450 BK	Black RAL 9004
910505103259	SP530P LED50S/930 PSD PI5 SM2 L2250 WH	White RAL 9003
910505103271	SP531P LED62S/930 PSD PI5 SM2L2810 WH	White RAL 9003
910505103272	SP532P LED94S/940 PSD PI5 SM2L2810 WH	White RAL 9003
910505103282	SP530P LED50S/TW9 SIA SM2 U4 L2290 ALU	Aluminum
910505103283	SP530P LED86S/TW9 SIA SM2 U4 L2850 ALU	Aluminum

